



Philadelphia Regional Port Authority
3460 North Delaware Ave. 2nd Floor
Philadelphia, PA 19134

July 19, 2023

To: All Bidders

From: Kate Bailey
Director of Procurement

Re: **ADDENDUM NO. 5**
23-026.1 - RFP for Design Build of Temperature Controlled Warehouse

This Addendum No. 5 is issued to:

1. Provide the Geotechnical Report. (attached)

All other terms and conditions remain unchanged.

Bidders shall acknowledge receipt of this addendum by immediately emailing a copy of the completed acknowledgment to Kate Bailey at procurement@philaport.com

ACKNOWLEDGMENT OF RECEIPT OF ADDENDUM NO. 5
Project #23-026.1
RFP for Design Build of Temperature Controlled Warehouse

Date _____

By _____

Company _____

Telephone _____

Fax _____

Email _____



Philadelphia Regional Port Authority
3460 North Delaware Ave. 2nd Floor
Philadelphia, PA 19134

Geotechnical Report

GEOTECHNICAL ENGINEERING SERVICES

*PhilaPort Distribution Warehouse
Packer Avenue
Philadelphia, PA*




Submitted To:

Philadelphia Regional Port Authority
3460 N. Delaware Avenue
Philadelphia, PA 19134

Submitted By:

Pennoni Associates Inc.
2041 Ave C, Suite 100
Bethlehem, PA 18017



Daniel P. Marano Jr., PE
Geotechnical Project Engineer



PRPAX 17013.04

January 25, 2018
(Revised May 13, 2019)

January 25, 2018
(Revised May 13, 2019)

PRPAX 17013.04

Ms. Lisa Magee, PE
Chief Engineer/Director of Engineering
Philadelphia Regional Port Authority
3460 N. Delaware Avenue
Philadelphia, PA 19134

**Re: Geotechnical Engineering Services
PhilaPort Distribution Warehouse
Philadelphia, Pennsylvania**

Ms. Magee:


We are pleased to submit our geotechnical engineering report for the referenced project. Work was initiated in general accordance with our revised proposal dated December 6, 2017, and your subsequent authorization to proceed.

In January of 2019 the project details began to finalize, this included building size, location, building loads and finished floor elevation. We have revised our report and recommendations based on the changes described above.

We trust that the information presented herein is what you require at this time and we thank you for the opportunity to assist you with this project. If you have any questions, or if you need any further assistance with this project, please contact this office at your earliest convenience.

Respectfully yours,

PENNONI ASSOCIATES INC.

A blue ink signature of Daniel P. Marano Jr. is written over the name and title.

Daniel P. Marano Jr., PE
Geotechnical Project Manager

A blue ink signature of Frederick A. Brinker is written over the name and title.

Frederick A. Brinker, PE
Associate Vice President
Geotechnical Division Manager

CONTENTS

SECTION PAGE

| | |
|---|-----------|
| 1. EXECUTIVE SUMMARY | 1 |
| 2. INTRODUCTION | 2 |
| 2.1. LOCATION | 2 |
| 2.2. PROPOSED CONSTRUCTION | 2 |
| 2.3. OBJECTIVES | 2 |
| 3. FIELD AND LABORATORY WORK | 3 |
| 3.1. PREVIOUS FIELD WORK | 3 |
| 3.2. FIELD WORK | 3 |
| 3.3. LABORATORY WORK | 3 |
| 4. SITE CHARACTERISTICS | 3 |
| 4.1. SITE HISTORY | 3 |
| 4.2. SURFACE FEATURES | 4 |
| 4.3. GEOLOGY | 4 |
| 4.4. SUBSOILS | 4 |
| 4.5. GROUND WATER | 6 |
| 5. ANALYSES AND RECOMMENDATIONS | 6 |
| 5.1. SEISMIC SITE CLASS | 6 |
| 5.2. SITE WORK | 6 |
| 5.3. FOUNDATIONS | 8 |
| 5.3.1. CONCRETE-FILLED STEEL PIPE PILES | 8 |
| 5.3.2. AUGER CAST PILES | 8 |
| 5.4. LOAD TESTING | 9 |
| 5.5. SETTLEMENT | 10 |
| 5.6. STRUCTURAL SLAB | 10 |
| 5.7. GROUND WATER AND SURFACE WATER MANAGEMENT | 11 |
| 5.8. LATERAL EARTH PRESSURE PARAMETERS | 11 |
| 5.9. CONSTRUCTION DIFFICULTIES | 12 |
| 6. RECOMMENDATIONS FOR FURTHER GEOTECHNICAL SERVICES | 12 |
| 7. LIMITATIONS | 12 |

APPENDICES

APPENDIX A – Field Data

Current Study

Boring Logs

Pennoni;
B-1 through B-20
TP1 through TP-10
P-1 through P-10
Drawing LP-1
Drawing LP-2

Boring Location Plan
Test Pits Location Plan
Boring Log Key Sheet

Preliminary Study

Boring Logs

Raudenbush Engineering, Inc.;
WH-01 through WH-05

APPENDIX B – Laboratory Data

Current Study

Summary of Laboratory Test Data
Gradation Curves
Unconfined Compression Test
Consolidation Test
Dial Readings vs. Time
Laboratory Testing Procedures

Table L-1
S-1 & S-2
UCC-1
CONS-1

Preliminary Study

Gradation Curves

APPENDIX C – Standard Symbols

APPENDIX D – Pavement Thickness

APPENDIX E – Important Information About This Geotechnical Engineering Report by GBA

1. EXECUTIVE SUMMARY

Pennoni Associates, Inc. (Pennoni) has completed field exploration for the proposed PhilaPort Distribution Warehouse, located in the City of Philadelphia, Pennsylvania. The project area will occupy the existing new car parking lot between Pattison and Packer Avenues. The purpose of our study was to determine the subsurface conditions at the project site within the footprint of the proposed warehouse building, evaluate these conditions with respect to the proposed development, and present foundation recommendations.

It is our understanding the proposed construction consists of an approximate 197,000 ft² dry storage building with 42 loading dock spaces on the west side of the building. The finished floor elevation is anticipated to be established at Elev. 13.5+/- . An approximate 215,000 ft² cold storage addition is proposed on the south side of the dry storage warehouse. It is our understanding that the dry storage building will be approximately 45 ft high and house four storage levels (first level is the floor and three pallet levels supported by pallet racks above). Additionally, the use of high mast fork trucks will be used inside of the building and will require minimal differential settlement in the floor slab (1/8 in.) in order to operate. Typical warehouse column, and floor loads are anticipated not to exceed 70 kips, and 450 psf respectively. Structural loading information was provided by our Structural Technologies group.

Between the period of July 25 through August 1, 2017, five borings were drilled by Allied Well Drilling, as part of a preliminary subsurface exploration conducted by others. Appendix A includes the preliminary boring logs.

Between the period of December 21, 2017 through January 3, 2018, 20 borings were drilled by C.G.C. Geoservices, LLC. within the proposed warehouse building footprint. Appendix A includes the boring logs and the Boring Location Plan.

On April 18 and April 19, 2019, 20 test pits were excavated by Ambient Group within the property; 10 shallow test pits were excavated to evaluate the pavement thickness, and 10 test pits were excavated for the infiltration testing. Appendix A includes all test pits logs.

Based on the results from the above explorations, laboratory testing, engineering analyses, and our experience, we conclude that construction of the proposed warehouse is feasible. Based on the soils encountered and the anticipated loading, it is our professional opinion that the proposed structure can be supported on either shallow foundations after ground improvement (Controlled modulus columns/Rigid inclusions) is performed, or on deep foundations. Additionally, the proposed floor slab has higher than normal loading and limited tolerances for movement, so we recommend that the ground floor slab should be constructed as a structural slab supported on improved soils or deep foundations. Encountering obstructions (construction debris) should be anticipated during foundation and utility installation. Encountering groundwater in excavations (on the order of 6 to 8 ft) should be anticipated. Due to the proximity to the Delaware River the groundwater elevation may vary with the tidal action. On-site existing inert granular portions of the fill soils can be reused in compacted load bearing fills. Stratum 1 and 2 soils are not suitable, in their current state, for re-use in compacted load bearing fill. Detrimental long-term post-construction settlements are not expected if the recommendations provided herein are followed.

This report provides a more detailed summary of the field and laboratory testing program as well as a discussion of the conclusions and recommendations pertaining to design and construction of the proposed structure.

2. INTRODUCTION

2.1. LOCATION

The project site is located west of the Delaware River in south Philadelphia, Pennsylvania. The site is bounded on the north by commercial buildings (seafood market, cold storage, bank) and South Galloway Street followed by Packer Avenue, on the east by South 3rd Street, on the south by Pattison Avenue, on the west by commercial buildings followed by South Lawrence Street.

2.2. PROPOSED CONSTRUCTION

It is our understanding the proposed construction consists of an approximate 197,000 ft² steel frame, dry storage building with 42 loading dock spaces on the west side of the building. An approximate 215,000 ft² cold storage addition is proposed on the south side of the dry storage warehouse. The finished floor elevation of the dry storage building is anticipated to be established at Elev. 13.5+/- . It is also anticipated that the exterior of the buildings will be clad with insulated metal sandwich wall panels with hardening of the lower exterior and interior face of the façade provided via masonry or concrete panel walls. The dry storage building will be approximately 45 ft high and house four storage levels (first level is the floor and three pallet levels supported by pallet racks above). Additionally, the use of high mast fork trucks will be used inside of the building and will require minimal differential settlement in the floor slab (no more than 1/8 in.) in order to operate. Typical warehouse column, and floor loads are anticipated not to exceed 70 kips, and 450 psf respectively. Structural loading information was provided by our Structural Technologies group.

2.3. OBJECTIVES

Our objectives were to determine the subsurface conditions at the project site within the footprint of the proposed building, evaluate these conditions with respect to the proposed construction, and present recommendations regarding:

- foundation design, including a discussion of alternate solutions, if applicable, anticipated total and differential settlements;
- design frost depth;
- floor slab design;
- lateral earth pressure parameters;
- discussion of potential for consolidation and/or differential settlements of substrata encountered;
- “general procedure” Seismic Soil Site Classification in accordance with Table 1613.5.2 of the 2009 International Building Code;
- evaluation and determination of the earthwork requirements for use in preparation of the site area, including material selection and placement operations;
- suitability of on-site material for re-use as fill/backfill as part of the site work for the project;
- ground water conditions;
- removal or treatment of objectionable material, and;
- quality assurance, field-testing, and observations during construction.

3. FIELD AND LABORATORY WORK

3.1. PREVIOUS FIELD WORK

Between the period of July 25 through August 1, 2017, five borings were drilled by Allied Well Drilling, as part of a due-diligence subsurface exploration conducted by others. Soil samples were reported to have been obtained in general accordance with ASTM D 1586. The data obtained from the previous exploration were used in our analyses.

3.2. FIELD WORK

Between the period of December 21, 2017 through January 3, 2018, 20 borings were drilled by C.G.C. Geoservices, LLC. within the proposed warehouse building footprint at the approximate locations presented on Drawing No. LP-1. The boring locations were selected and established in the field by Pennoni personnel. Soil samples were obtained in general accordance with ASTM D 1586 and ASTM D1587 methods. Appendix A includes the boring logs and Drawing No. LP-1.

Our D. Marano, PE directed the field work; our D. Copeland, EIT, and S. Corcoran, performed a site reconnaissance and full-timed monitored the drilling operations.

Additionally, on April 18 and April 19, 2019, 20 test pits were excavated by Ambient Group within the property; 10 shallow test pits were excavated to evaluate the pavement thickness, and 10 test pits were excavated for the infiltration testing. Appendix A includes all test pits logs. The test pits locations were selected and established in the field by Pennoni personnel.

Our D. Marano, PE directed the field work; our N. Rex and E. Iannetti, full-timed monitored the excavating operations.

3.3. LABORATORY WORK

The soil samples collected during our fieldwork were delivered to our laboratory. Representative samples were selected and tested to determine moisture contents, organic contents, plasticity indices, unconfined compressive strengths, volumetric (unit weight, void ratio), gradation and consolidation characteristics of the subsoils. Additionally, laboratory testing data from the preliminary study performed by others was used in our study. Appendix B includes the results from both studies and a list of testing procedures.

4. SITE CHARACTERISTICS

4.1. SITE HISTORY

Review of historical documents dating back to 1940 indicates the site underwent massive earthwork during the 1940's and 50's. Due to the limited detail and resolution of the published data it is not clear what the site was used for during this period. Between 1957 and 1963, two large rectangular commercial buildings were constructed. The buildings stretched from Packer Avenue to Pattison Avenue and were separated in the middle by South Galloway Street.

The site remained largely unchanged through 2013. Between 2013 and present day, the buildings were razed. Evidence of the razed buildings is evident where the ground cover consists of compacted

processed aggregate over the former building footprints. The site is currently being used as a parking lot for new cars.

4.2. SURFACE FEATURES

Currently the project site consists of a bituminous paved parking lot with associated curbing and light pole structures. The groundcover in the areas of the razed buildings consisted of compacted processed aggregate. The topography of the site is “bowl” shaped with perimeter elevations varying from Elev. 12 to Elev. 10 and descend towards the center of the site to approximate Elev. 9 to Elev. 8. Overhead electrical utilities were observed traversing in the northerly/southerly direction the center of the site. Stormwater inlets and associated underground utilizes were observed running bilaterally along the center of the site from the northern limit to the southern limit of the site.

4.3. GEOLOGY

The project site is located within the Lowland and Intermediate Upland section of the Atlantic Coastal Plain Province. The dominant topographic features of this section include very low local relief and a flat upper terrace surface cut by narrow, steep-sided to open valleys, shallow valleys; includes the Delaware River floodplain. The underlying subsurface material types consist of unconsolidated to poorly consolidated sand and gravel deposits, underlain by very complex, faulted and folded schist, gneiss, and other metamorphic rocks.

Available geological data indicates that the subject site is underlain by the Trenton Gravel Formation consisting of gray or pale-reddish-brown, very gravelly sand interstratified with crossbedded sand and clay-silt beds. This formation also includes areas of Holocene alluvium and swamp deposits

Underlying the Trenton Gravel Formation is the Wissahickon Formation. The Wissahickon Formation consists of a coarsely crystalline, excessively micaceous schist. Fracturing results in a well-developed, platy pattern. This formation is fissile to thinly bedded, moderately resistant to weathering, and often highly weathered to a moderate depth.

4.4. SUBSOILS

The borings and test pits revealed bituminous concrete/concrete/processed aggregate pavement or processed aggregate layer at the surface that varied in thickness from 5 to 13 inches. Appendix D presents pavement thickness encountered in all borings and test pits performed on site. The underlying subsoils have been grouped by us into six principal strata based on their physical and engineering properties and our interpretation of their origin. Following are descriptions of the subsoils encountered at this site.

Stratum F – Urban Fill

The borings and test pits disclosed an Urban Fill layer with a thickness that varies from approximately 7 to 18 ft. The fill generally consists of granular fine to medium SAND, some to trace gravel size rock fragments (brick, ash, cinder, glass, organics), some to trace silt, or SILT, some to trace fine to medium sand, some to trace gravel size rock fragments (brick, ash, cinder, glass, organics).

Standard penetration test (SPT) N-values indicate the density/consistency of this stratum varies from “very loose”/“soft” to “very dense”/“very hard”. Typical USCS Classifications associated with this stratum are SM, SP-SM, and ML.

Although not encountered in the borings, encountering remnants of previous foundations and shoring systems during construction, should be expected within Stratum F. If encountered, these obstructions will most likely impair the construction process, especially utility and foundation construction.

Stratum 1 – Silty Clay/Clay (Alluvial)

A stratum of Silty CLAY/CLAY with varying amounts of fine sand gravel and organics (7.9% to 10.5%) was encountered beneath Stratum F fill in many of the borings. The thickness of this layer varies from approximately 5 to 15 ft. SPT N-values indicate the consistency of this soil varies from “very soft” to “firm”. The typical USCS Classifications associated with this stratum are OL and OH.

Consolidation testing disclosed a preconsolidation pressure (tsf), compression and recompression index of 0.95, 0.49 and 0.03, respectively. Laboratory testing and visual classification disclosed this layer contained trace to little organics. These data disclose Stratum 1 soils to be compressible.

Stratum 2 – Clayey SILT (Alluvial)

A stratum of SILT with varying amounts of fine sand, gravel and organics (up to 26.2%) was encountered beneath the Stratum F Fill or Stratum 1 soils in many of the borings. The thickness of this layer varies from approximately 5 to 15 ft. SPT N-values indicate the consistency of this stratum varies from “very soft” to “stiff”. Typical USCS Classifications associated with this stratum are OH and ML.

Laboratory testing and visual classification disclosed this layer contained trace to some organics. The percentage of organics in Stratum 2 is generally associated with high compressibility, significant secondary compression, often unsatisfactory strength characteristics, and low unit weight. This stratum is also considered compressible.

Stratum 3 – Sand/Gravel (Alluvial)

A stratum of SAND ranging in gradation from poorly (generally, gap graded fine to medium) to well graded with varying amounts of gravel and silt, or GRAVEL with varying amounts of sand was encountered beneath Strata 1 and 2. The thickness of this layer varies from approximately 10 to 32 ft. SPT N-values indicate the relative density of this stratum generally varies from “very loose” to “medium dense”. Typical USCS Classifications associated with this stratum are SP and SP-SM.

Stratum 4 – Sand/Gravel (Alluvial)

A stratum of well graded SAND with varying amounts of gravel, or poorly to well graded GRAVEL with various amounts of sand was encountered above and/or beneath Stratum 3 in the borings. Stratum 4 was generally encountered at depths ranging from 43 to 80 ft below the ground surface. SPT N-values indicate that the density of this stratum generally varies from “medium dense” to “very dense”. Typical USCS Classifications associated with this stratum is SW-SM, GM and GP.

It should be noted that COBBLES encountered Borings B-2 and B-12 at depths ranging from 45 to 50 ft below the ground surface were included in this Stratum. The material was observed when the augers were extracted.

Stratum 5 – Raritan Clay

A stratum of CLAY/Sandy CLAY with varying amounts of fine sand and gravel was encountered beneath and or between Stratum 4 in some of the borings. Stratum 5 was generally encountered at depths ranging from 53 to 80 ft below the ground surface and generally varies in thickness from approximately 5 to 7 ft. SPT N-values indicate the consistency of this soil varies from “stiff” to “very hard”. The typical USCS Classification associated with this stratum is CL.

Auger refusal was encountered in Borings B-2 and B-12 at depths of 47 and 50 ft below existing grades, respectively. Auger refusal is thought to be due to cobbles, rather than the top of rock.

4.5. GROUND WATER

Observations for groundwater were made in the borings during sampling and shortly after completion of drilling. Evidence of groundwater was generally encountered in the borings at depths of approximately 6 to 13 ft below existing grades (Elev. 6.5 to Elev. 0.0). Borings B-17, B-18 and B-20 disclosed evidence of groundwater at depths ranging from 18 to 28 ft below existing grades (Elev. -2.0 and Elev.-11.5), respectively. It is our professional opinion that these latter readings were affected by hydraulically restrictive Stratum 1, and not indicative of the static groundwater table.

Additionally, evidence of ground water was generally encountered in test-pits at depths of approximately 8 to 10.5 ft below existing grades. These observations are for the times indicated and may not be indicative of seasonal, daily or tidal variations in the ground water levels.

Given the project site’s vicinity to the Delaware River, daily fluctuations in the groundwater table could be influenced by the tide. Daily and seasonal variations of several feet should be anticipated.

5. ANALYSES AND RECOMMENDATIONS

5.1. SEISMIC SITE CLASS

The borings disclosed subsurface conditions generally described according to the 2015 International Building Code (IBC) as having a soil-profile corresponding to Site Class E – soft clay soil profile.

5.2. SITE WORK

Comparison of the proposed grades to existing grades indicates that cuts as on the order of 1 ft deep and fills up to 5 ft high are expected to establish the ground floor slab. Comparison of the proposed grades to existing grades indicates that cuts as deep as 3 ft and fills up to 2 ft high are required for general site grading. The borings and laboratory testing disclosed Stratum 1 and 2 are compressible. Fills greater than 2 ft high will likely result in consolidation related settlement, which may be significant (> 3 inches). New fills should be placed as early as possible within the construction schedule to allow for settlements to occur.

Prior to the construction of foundations, structural slabs, and pavements, any bituminous concrete must be removed from within the proposed areas of construction. Existing utilities located within the proposed building footprint should be abandoned and relocated outside the limits of the new structure. Any existing

utility line abandoned in-place should be grouted or the line should be removed and the trench appropriately backfilled.

From historic aerial photography, it was disclosed that the site was once partially occupied by structures and associated paved parking. At the time of our field work evidence of previous structures was observed throughout the razed building footprints; however, remnants of the former foundations were not observed, or evident in the borings. The excavation of test pits prior to construction should be considered to better determine if remnants of the previous building will interfere with construction.

Any exposed subgrade should be proof-rolled in the presence of Pennoni personnel in an attempt to disclose unstable surface areas. During proof-rolling, any unstable area found should be stabilized by excavating and replacing those soils with suitable soil that is adequately compacted. This can be accomplished by properly adjusting the moisture content of the subgrade soils and compacting them, or by other methods (placing a geotextile and stone layer, etc.).

Our experience indicates that the clean inert granular portions of the Fill stratum can be reused in a compacted fill for backfill of utility excavations as long as it has a maximum particle size of 3 in., and is free of trash, environmental hazards, and other deleterious material. Additionally, demolition debris consisting of concrete and pavement millings can be used in compacted load bearing fills provided there are no environmental hazards associated with the materials and it is crushed to reduce the maximum particle size to less than 3 inches. Adjusting the moisture content prior to fill placement should be expected. Stratum 1 and Stratum 2 soils are not suitable, in their current state, for re-use in compacted load bearing fill.

Imported structural fill should be selected from suitable borrow sources and be approved by the Geotechnical Engineer's representative well in advance of fill construction. Granular fill ideally should consist of well-graded material with not more than 20 percent passing the No. 200 sieve and have a plasticity index not greater than 8 percent; PennDOT 2A, modified stone or recycled concrete can be considered. Other gradations can be considered based on laboratory testing and at the discretion of the Geotechnical Engineer.

Granular fills should be placed in layers not exceeding 10 to 12 in. loose thickness. This criterion might be adjusted by the geotechnical engineer in the field depending on the conditions present at the time of construction, on the compaction equipment used, and on the fill material selected. Fills for support of foundations and pavement should be compacted to at least 98 percent and 95 percent, respectively, of the laboratory determined maximum dry density, ASTM D 698, when small, hand-operated compaction equipment is used, and to at least 95 percent and 93 percent, respectively, of the laboratory determined maximum dry density, ASTM D 1557, when self-propelled, heavy-duty construction equipment is used. Fills should extend a minimum of 5 ft beyond the exterior edge of a loaded area and have side slopes not steeper than 2 horizontal to 1 vertical.

Specifications should indicate that the percentage of maximum dry density attained in the field is not the only criteria to be used for assessing fill compaction. Observation of the behavior of the fill under the loads of construction equipment should also be used. If the test results indicate that the percentage of compaction is being achieved, but the soil mass is moving under the equipment, placement of additional fill should not be continued until the movement is stabilized. Otherwise, settlement of the fill may occur.

5.3. FOUNDATIONS

Based on the soils encountered and the anticipated loading, it is our professional opinion that the proposed structure should be supported on shallow foundations bearing on improved soils or deep foundations. Controlled Modulus Columns/Rigid Inclusions (CMC's/RI's) can be considered to sufficiently improve the subsoils to allow the construction of shallow spread foundations. Alternatively, deep foundations like concrete filled steel pipe piles and auger cast-in-place piles can be considered for support. Because of the load carrying capacity of the deep foundations, as described, pile load tests (compression and tension) will be necessary.

5.3.1. CMC's/RI's

In order to support the structure on shallow spread footings we recommend improving the subgrade soil by installing CMCs/RIs elements. These elements improve the existing soil conditions to reduce both total and differential settlements by increasing the overall stiffness of the soil mass. A load transfer platform (LTP), sometimes reinforced with a geogrid, is constructed above the CMCs/RIs using granular fill with a thicknesses that may vary from 12 to 36 inches. CMCs/RIs are installed by a drill rig with a specially designed auger that drills down to the designed termination depth followed by a controlled pressure grouting during extraction. The instillation of the CMCs/RIs results in generating minimal auger spoils and vibration. Spread footings can then be designed to bear in the LTP layer for a maximum allowable net bearing capacity of up to 6,000 psf.

Continuous and isolated footings should be at least 1.5 ft wide and 3 ft square, respectively, to prevent localized shear failure in soil. The subgrade of all exterior footings exposed to freezing temperatures, during construction and/or the life of the structure should be established at least 30 in. below adjacent exposed grades or otherwise protected against frost action. Foundation subgrades should be checked by a representative of Pennoni to confirm conditions suitable for support of the design bearing pressure. Where an area is questionable, it should be further explored and/or remedied by removal and replacement of unsuitable material.

5.3.2. Concrete-filled Steel Pipe Piles

Concrete-filled steel pipe piles with an outside diameter (OD) of 16 in. and a minimum wall thickness of 0.5 in. driven into the dense to very dense sand and gravel deposit (Stratum 4) can be considered. Our analyses indicate piles installed to the recommended depths can obtain an allowable load carrying capacity in compression up to 125 tons. A temporary increase in the capacity of up to 33% can be applied to transient loads including wind, etc.

Based on the findings of the test borings and our analyses, the pile tips will be located approximately 60 to 80 ft. below the existing grades. The steel pipe pile should conform to ASTM A-252, Grade 3, specifications. The piles should have a flat boot plate of at least 2 in. thickness fully welded at the tip and flush with the outside wall of the pipe (no projection). The minimum pile spacing should be at least 3 times the pile diameter. In addition to the allowable compression capacity recommended above, the vertical piles can be designed for an allowable uplift capacity of 25 tons, and an allowable lateral capacity of 8 tons per pile.

To facilitate pile installations, the piles may be installed by pre-augering through upper portions of fill layer, if necessary. After pre-augering, the piles should be driven into the dense to very dense sands of Stratum 4, to attain the recommended design capacity. The piles should be driven for at least the last 10 ft. of their length to a resistance determined in accordance with Pile Dynamic Analysis (PDA) testing a suitable dynamic formula, such as a WEAP Analysis, and as verified by successful pile load tests. Production piles may be used for load tests.

5.3.3. Auger Cast Piles

Auger Cast Piles (ACIP) can also be considered for support of the proposed structure. This pile type is constructed by first drilling to the pre-determined depth/elevation using a standard continuous flight auger that removes or displaces material. After reaching the design depth, cement grout is injected, under pressure, as the auger is gradually withdrawn, forming an uncased grout shaft. A 28-day compressive strength of at least 5,000 psi is recommended for the cement grout. The pile shaft can be reinforced with one full-length reinforcing bar extending to the bottom and, if necessary, a reinforcing steel cage can be installed into the upper portion of the grout column while the grout is still fluid.

The piles will derive their capacity by a combination of skin friction and end bearing. An 16-in. diameter ACIP pile will have an estimated allowable axial load carrying capacity of 100 tons per pile. These piles should be constructed estimated to depths of 60 to 80 ft. below existing grade. We estimate these piles as described will have tension and lateral capacities on the order of 50 tons and 8 tons per pile, respectively.

Piles designed to resist uplift loads (tension) should have reinforcing steel extending all the way to the pile tip. Moreover, piles subjected to lateral loads should have properly designed reinforcing in the upper portion of the pile shaft. We further recommend that the piles designed to carry uplift and lateral loads be spaced at least 3 pile diameters apart. The final design and/or allowable capacities should be determined by a specialty contractor with adequate experience in auger cast concrete pile design and construction. Production piles may be used for load tests but should failure occur, the pile can no longer be used. The auger cast pile installer is responsible for closely monitoring the pile during the load test and proving the pile was damaged during testing.

5.4. LOAD TESTING

CONCRETE FILLED STEEL PIPE PILES

The Wave Equation analysis should be used to determine the suitability of the proposed driving equipment. The contractor should incorporate the results of the wave equation analysis within any submittals that are due prior to construction for approval. Consideration should be given to performing dynamic monitoring on a minimum of 5% piles using a Pile Driving Analyzer (PDA). The PDA will provide information on the actual driving stresses, verification of ultimate geotechnical resistance, energy transfer efficiency, pile damage assessments, and verify the refusal criteria during pile installation. A minimum factor of safety of 2.25 should be used during the PDA testing to confirm the recommended installed pile capacity. In addition to the PDA we recommend that static load test piles be installed to better define pile length(s) and to confirm/refine pile installation procedures. We recommend that 2 sets of static load tests (axial, tension and lateral) be conducted.

We recommend that the installation of each pile should be monitored and documented by geotechnical personnel under the direct supervision of a professional engineer.

ACIP

Prior to production pile installation, we recommend that test piles be installed to better define pile length(s) and to confirm/refine pile installation procedures. We recommend that 2 sets of static load tests (axial, tension and lateral) be conducted and dynamic tests conducted on 5% of the production piles. The dynamic integrity testing for the auger cast piles should consist of Pile Integrity Testing (PIT) to confirm the construction of the piles.

GENERAL PILE LOAD TESTING RECOMMENDATIONS

The proposed pipe and auger cast piles are essentially a combination of tip bearing and/or friction piles. The load tests must verify a safe load carrying capacity and they must demonstrate that only a very small net settlement will occur while the full design load is carried by the pile. Therefore, the load test should be conducted in such a fashion and provided with such instrumentation that the loads carried by the pile shaft and pile tip, and the strains of the top, mid-point, and base of the test pile can be measured, where feasible.

The maximum test load should be not less than specified by Code and it is recommended to be higher to facilitate total load transfer to the tip of the pile. Experience has shown that testing a pile to a load greater than the Code requirement, although costlier initially, can prove advantageous during installation because of inconsistencies during construction. Therefore, we recommend that a maximum test load at least 2.5 times the maximum design load carrying capacity of the selected pile should be considered for evaluating maximum load carrying capabilities and load-settlement relationships.

Static and dynamic load tests should be conducted in accordance with the provisions of the latest version of the ASTM Standards. For static testing instrumentation, load test set-up, and loading procedures should be governed by ASTM D-1143 except that the procedures described under "Apparatus for Measuring Movements", "Lateral Movements", and "Incremental Loading Procedures" should be mandatory. PDA testing on driven piles should be performed in accordance with ASTM D-4945.

The geotechnical engineer should select load test locations. Load tests should not be production piles; if the pile/soil interface is failed during testing it will no longer be capable of supporting loads. No construction activity transmitting vibratory or impact loads should be permitted on the project site during load testing. The load test set-up should be protected from inclement weather (wind, rain, intense heat, sunlight, etc.), provided with lights for nighttime readings, and guarded on a full-time basis.

Technical details of the intended pile installation equipment and of the load test set-up (sketch, description, etc.) together with certification of the loading device, etc. should be submitted to the geotechnical engineer at least 1 week in advance of load test construction. Each load test must be monitored on a full-time basis and test results analyzed by a registered geotechnical engineer.

5.5. SETTLEMENT

Settlement of a soil mass is a function of the characteristics of the supporting materials and the stresses imposed on the soils from an external source. Our calculations indicate that settlements will occur due to the stresses imposed on the subsoils by newly placed load bearing fill for site fills and are proportional to the amount of pressure applied (fill height). Additionally, the organic layer of soil was determined to contain approximately 26% of organic material. Long term, secondary settlement is also anticipated in this layer as the material breaks down and consolidates.

The fill heights and secondary settlement may lead to uneven settlement below the floor slab. Therefore, consideration should be given to suspending the utilities from the structural slabs to prevent any serious differential movements in different portions of the utilities. Moreover, flexible connections should be used where the suspended pipes meet the outside pipelines not supported by piling.

Provided the building and structural slab are supported on deep foundations (driven piles, ACIP piles), determinantal total and differential settlements are not anticipated.

5.6. STRUCTURAL SLAB

Because of the differential settlement tolerances the ground floor slab should be designed as structural slab supported by piles and grade beams or they should be designed as “flat plates” supported by piles. The required new fill to attain the finish ground floor subgrade level should be placed as recommended in the Earthwork Section 5.2 to serve as an underside form for slab construction, but it will eventually settle away from the bottoms of the slabs due to consolidation of the compressible organic silt layers.

5.7. GROUND WATER AND SURFACE WATER MANAGEMENT

Observations for groundwater made in each test pit and boring indicate that water was generally encountered 6 to 13 ft. below existing grades. Water table fluctuations may occur with the tidal action of Delaware River. Static water levels could affect utility installation if they are proposed at depths greater than the Mean High Water (MHW) Elevation. The use of sumps and pumps should be expected; well points and/or a sheeting/shoring system comprised of steel interlocking sheeting and high capacity pumps may be required to control ground water during utility installation in deeper excavations (>5 ft. deep).

Surface runoff should be prevented from entering or ponding in excavations by creating soil berms or diversion swales along the perimeter, if the excavation will be left open for an extended period. Where ponding does occur, the water should be removed immediately by pumping. Grades should then be established to prevent further ponding.

5.8. LATERAL EARTH PRESSURE PARAMETERS

The soil parameters presented in Table 1 can be used to estimate earth pressures to design below grade structures and temporary shoring. If the top of the structure is restrained from movement, thereby preventing the mobilization of active soil pressures, the structure should be designed using the at-rest pressure coefficient.

The earth pressure coefficients are based on the assumption of vertical walls, horizontal backfill, no surcharges, no wall friction, and a safety factor of 1.0. A clear distance of 10 ft should be maintained during construction, between perimeter walls and stored materials or the wall must be design to resist the surcharge load from the stored materials. Where sufficient drainage cannot be provided to intercept and re-direct seepage and perched water from structures, hydrostatic pressures must also be considered in the design.

Table 1. Lateral Earth Pressure Design Parameters

| Parameter | Strata | | | | | | |
|--------------------------------------|--------|------|------|------|------|------|---------------------------------------|
| | F | 1 | 2 | 3 | 4 | 5 | Processed Aggregate (PennDOT Type 2A) |
| Unit Weight (pcf) | 120 | 100 | 90 | 125 | 130 | 118 | 135 |
| Angle of Internal Friction (degrees) | 28 | 17 | 23 | 32 | 38 | 32 | 38 |
| Cohesion (psf) | - | 200 | 0 | - | - | 1000 | - |
| Friction Factor (concrete) | 0.35 | 0.20 | 0.20 | 0.40 | 0.50 | 0.40 | 0.50 |
| Friction Factor (steel) | 0.25 | 0.20 | 0.20 | 0.25 | 0.30 | 0.25 | 0.30 |
| k_a | 0.36 | 0.55 | 0.44 | 0.31 | 0.24 | 0.31 | 0.24 |
| k_o | 0.53 | 0.71 | 0.61 | 0.47 | 0.38 | 0.47 | 0.38 |
| k_p | 2.77 | 1.83 | 2.28 | 3.25 | 4.20 | 3.25 | 4.20 |

5.9. CONSTRUCTION DIFFICULTIES

Experience has shown that remnant construction and obstructions are often encountered when building within similar, previously developed urban sites. Encountering remnants of previous foundations and shoring systems should be expected. If encountered, these obstructions will most likely impair the construction process. Existing foundations or other structural components disclosed should be removed to a minimum depth of 18 in. below the bottom of new ground floor slabs and 36 in. below the bottom of new foundations.

6. RECOMMENDATIONS FOR FURTHER GEOTECHNICAL SERVICES

Our experience on numerous construction projects is that the interests of the project team are best served by retaining the Geotechnical Engineer to provide construction observations during earthwork and foundation construction operations. To determine if soils, other materials, and ground water conditions encountered during construction are similar to those encountered in the borings and test pits, and that they have comparable engineering properties or influences on the design of the structures, we recommend that Pennoni should provide field observation services during pile driving and load testing, and excavation; construction of compacted fill; preparation of foundation, floor slabs, and pavement subgrades; and installation/construction of foundations, floor slabs, and pavements. Pennoni’s Geotechnical Technology should review specifications for earthwork and foundation design/construction when they are prepared.

7. LIMITATIONS

This work has been done in accordance with our authorized scope of work and in accordance with generally accepted professional practice in the fields of geotechnical and foundation engineering. This warranty is in lieu of all other warranties either expressed or implied. Our conclusions and recommendations are based on the data revealed by this exploration. We are not responsible for any conclusions or opinions drawn from the data included herein, other than those specifically stated, nor are the recommendations presented in this report intended for direct use as construction specifications.

This report is intended for use with regard to the specific project described herein; any changes in loads, structures, or locations should be brought to our attention so that we may determine how they may affect our conclusions. An attempt has been made to provide for normal contingencies but the possibility remains that unexpected conditions may be encountered during construction. If this should occur, or if additional or contradictory data are revealed in the future, we should be notified so that modifications to this report can be made, if necessary. If we do not review relevant construction documents and witness the relevant construction operations, then we cannot be responsible for any problems that may result from misinterpretation or misunderstanding of this report or failure to comply with our recommendations.

APPENDICES

APPENDIX A - Field Data



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 1/4/18 **COMPLETED** 1/4/18 **GROUND ELEVATION** 15.5 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger **DURING DRILLING** 13.00 / Elev 2.50
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY S. Corcoran **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|--|-----------|
| 0 | | | | | | Depth | |
| | | | | | | Elev. | |
| | | | | | P | 1.0 5.0 in. BITUMINOUS CONCRETE | 14.5 |
| | | | | | | 2.0 7.0 in. Gray C/F gravel size ROCK FRAGMENTS AND F/M SAND, trace Silt | 13.5 |
| 5 | S-1 | 12 | 16-24 | | | 4.0 FILL: Black to tan F/M SAND, little Fine Gravel, trace Silt, trace Brick Fragments | 11.5 |
| | S-2 | 24 | 16-20-32-40 | | | 6.0 FILL: Black to tan F/M SAND, some Fine Gravel, Cinder Fragments | 9.5 |
| | S-3 | 24 | 23-20-21-27 | | | 8.0 FILL: Black to red F/M SAND, little Fine Gravel, some Brick Fragments, trace Cinder and Concrete Fragments | 7.5 |
| | S-4 | 12 | 15-8-9-7 | | | FILL: Black to dark gray Silty CLAY, some F/M Sand, trace Brick and Cinder Fragments | |
| | S-5 | 12 | 4-4-5-5 | | F | FILL: Dark gray Silty CLAY AND F/M SAND, some organic pieces of Wood, trace Cinder | |
| | | | | | | 13.0 FILL: Dark gray Fine SAND, Micaceous, some Silt | 2.5 |
| 15 | S-6 | 12 | 3-2-3-2 | | | | |
| | | | | | | 18.0 Dark gray Silty CLAY, trace Fine Sand | -2.5 |
| | | | | | 1 | | |
| | | | | | | 23.0 Gray F/M SAND AND brown SILT, little Organics | -7.5 |
| 25 | S-8 | 12 | 1-1-1-1 | | | | |
| | | | | | | 28.0 Gray to tan M/F SAND, trace Silt | -12.5 |
| 30 | S-9 | 20 | 5-6-4-7 | | 3 | | Added mud |
| | | | | | | | |
| 35 | S-10 | 18 | 4-6-9-9 | | | | |

NOTES:



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|--|----------------|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | | 3 | Gray to tan M/F SAND, trace Silt (<i>continued</i>) | |
| 40 | S-11 | 12 | 8-9-13-15 | | | 38.0 _____ -22.5 Brown to tan to gray F/C GRAVEL, some C/M/F Sand, trace Silt | Very wet |
| 45 | S-12 | 12 | 12-26-20-15 | | | | |
| 50 | S-13 | 0 | 10-14-13-25 | | | 48.0 _____ -32.5 NO RECOVERY | |
| 55 | S-14 | 0 | 39-50/3" | | 4 | 53.0 _____ -37.5 NO RECOVERY | Pushing gravel |
| 60 | S-15 | 3 | 50/4" | | | 58.0 _____ -42.5 White C/F GRAVEL, little C/M/F Sand, trace Silt | |
| | | | | | | 60.0 _____ -44.5 | |

Boring terminated at 60.0 feet.

NOTES:



TEST BORING LOG

BORING B-2
PAGE 1 OF 2

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/28/17 **COMPLETED** 12/29/17 **GROUND ELEVATION** 16 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger **DURING DRILLING** 10.00 / Elev 6.00
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY S. Corcoran **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|---|---------|
| 0 | | | | | | Depth | Elev. |
| | | | | | P | 0.9 5.0 in. BITUMINOUS CONCRETE | 15.1 |
| | | | | | | 2.0 6.0 in. Gray C/F gravel size ROCK FRAGMENTS AND F/M SAND, trace Silt | 14.0 |
| | | | | | | Tan to white F/M SAND, trace Silt | |
| 5 | S-1 | 10 | 15-22 | | | 4.0 Tan to white F/M SAND, little Fine Gravel, trace Silt | 12.0 |
| | S-2 | 20 | 14-27-22-11 | | | 6.0 Black to tan F/M SAND AND Fine GRAVEL | 10.0 |
| | S-3 | 12 | 6-6-7-7 | | | Brown F/M SAND, little Fine Gravel, Organics | |
| | S-4 | 12 | 12-13-8-5 | | | 8.0 Black M/C/F SAND AND F/C gravel size ROCK FRAGMENTS, little Clay, little Organics, Debris | 8.0 |
| 10 | S-5 | 7 | 1-1-1-1 | | F | | |
| | | | | | | 13.0 Dark gray F/M SAND, little Silt, trace Glass and Brick Fragments | 3.0 |
| 15 | S-6 | 16 | 1-2-1-1 | | | | |
| | | | | | | 18.0 Gray Silty CLAY, trace Fine Sand, trace Organics | -2.0 |
| 20 | S-7 | 24 | WOH/24" | | | | |
| | | | | | | 23.0 Gray Silty CLAY, trace Fine Sand, little Organics | -7.0 |
| 25 | S-8 | 24 | 1-1-2-2 | | | | |
| | | | | | 1 | 28.0 Gray Silty CLAY, little to some Fine Gravel, Micaceous | -12.0 |
| 30 | S-9 | 24 | 4-4-4-5 | | | | |
| | | | | | | 33.0 Tan to gray M/F SAND, trace Silt | -17.0 |
| 35 | S-10 | 12 | 6-7-7-6 | | 3 | | |

NOTES:

(Continued Next Page)



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|---|------------------------|
| 35 | | | | | | Depth _____ Elev. _____ | |
| 40 | S-11 | 12 | 4-4-5-7 | | 3 | Tan to gray M/F SAND, trace Silt (<i>continued</i>) | |
| 45 | S-12 | 12 | 7-17-18-15 | | 4 | Gray C/M/F SAND, little Fine gravel | |
| | S-13 | 2 | 50/2" | | | COBBLES | Auger refusal at 47 ft |
| | | | | | | Boring terminated at 47.2 feet. | |

NOTES:



TEST BORING LOG

BORING B-3
PAGE 1 OF 2

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/26/17 **COMPLETED** 12/26/17 **GROUND ELEVATION** 16 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger **DURING DRILLING** 8.00 / Elev 8.00
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY S. Corcoran **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|--|---------|
| 0 | | | | | | Depth _____ Elev. _____ | |
| | | | | | P | 0.4 5.0 in. BITUMINOUS CONCRETE 15.6 | |
| | S-1 | 10 | 35-45 | | P | 2.0 FILL: Gray C/F gravel size ROCK FRAGMENTS AND M/F/C SAND, trace Silt 14.0 | |
| | S-2 | 5 | 50/5" | | P | 4.0 FILL: Gray to tan F/M SAND, some F/C Gravel 12.0 | |
| 5 | S-3 | 8 | 15-13-7-6 | | F | 6.0 FILL: Black to gray F/M SAND, some F/C Gravel, trace Silt, trace Brick and Cinder Fragments 10.0 | |
| | S-4 | 16 | 8-5-3-3 | | F | 8.0 FILL: Black SILT, some F/M Sand 8.0 | |
| | S-5 | 6 | 3-3-2-2 | | F | 10.0 FILL: Black C/F GRAVEL AND F/M/C SAND, little Silt 8.0 | Wet |
| | | | | | | 13.0 3.0 | |
| 15 | S-6 | 14 | 2-1-1-1 | | 2 | Black SILT AND F/M SAND, trace Organics | |
| | | | | | 2 | 18.0 -2.0 | |
| 20 | S-7 | 22 | WOH/24" | | 1 | Gray Silty CLAY, trace Fine Sand | Wet |
| | | | | | 1 | 23.0 -7.0 | |
| 25 | S-8 | 24 | 1-1-1-1 | | 1 | Gray Silty CLAY, trace Fine Sand, trace Organics | |
| | | | | | 1 | 28.0 -12.0 | |
| 30 | S-9 | 12 | 5-5-5-9 | | 2 | Brown SILT AND ORGANICS, trace Fine Sand | |
| | | | | | 2 | 33.0 -17.0 | |
| 35 | S-10 | 9 | 5-6-7-6 | | 3 | Gray to tan M/F/C SAND, trace Silt | |

NOTES:

(Continued Next Page)



TEST BORING LOG

BORING B-3

PAGE 2 OF 2

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
 PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|----------------|-------------|--------|---|---------|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | | | Gray to tan M/F/C SAND, trace Silt <i>(continued)</i> | |
| | | | | | | 38.0 _____ -22.0 | |
| 40 | X S-11 | 10 | 5-5-7-14 | | 3 | Gray to tan M/F/C SAND, little to some C/F Gravel, trace Silt | |
| | | | | | | 43.0 _____ -27.0 | |
| 45 | X S-12 | 12 | 6-7-13-36 | | | 44.5 _____ -28.5 | |
| | | | | | | Gray to tan C/F GRAVEL, some C/M/F Sand, trace Silt | |
| 50 | X S-13 | 24 | 28-33-42-50/3" | | | 49.0 _____ -33.0 | |
| | | | | | | Gray to tan F/M/C SAND, trace Fine Gravel, trace Silt | |
| 55 | X S-14 | 16 | 50-40-9-13 | | 4 | 53.0 _____ -37.0 | |
| | | | | | | Gray to tan C/F GRAVEL, some C/M/F Sand, trace Silt | |
| 60 | X S-15 | 18 | 8-20-7-34 | | | 58.0 _____ -42.0 | |
| | | | | | | 60.0 _____ -44.0 | |
| | | | | | | Gray to tan C/M/F SAND AND C/F GRAVEL, trace Silt | |

Boring terminated at 60.0 feet.

NOTES:



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/22/17 **COMPLETED** 12/22/17 **GROUND ELEVATION** 13.5 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger w/ Mud **DURING DRILLING** 13.00 / Elev 0.50
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY D. Copeland **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS | |
|------------|--------------------|----------------|-------------|-------------|--------|--|---|-------|
| 0 | | | | | | Depth _____ Elev. _____ | | |
| | S-1 | 12 | 29-26-50 | | P | 0.5 6.0 in. BITUMINOUS CONCRETE FILL: Brown C/F gravel size ROCK FRAGMENTS AND M/F SAND | Dry | |
| | S-2 | 4 | 50/4" | | | | | |
| 5 | S-3 | 16 | 5-8-9-6 | | F | 4.0 | FILL: Black SILT, some M/F Sand, trace Incinerated Material, trace Organics | |
| | S-4 | 16 | 6-6-6-7 | | | | | |
| | S-5 | 18 | 7-9-8-7 | | | | 8.0 Gray Fine SAND, trace Silt | Moist |
| 10 | | | | | | | | |
| | S-6 | 24 | WOH/24" | | | | 13.0 Gray Silty CLAY, trace Organics, trace Fine Sand | |
| 15 | | | | | | | | |
| | S-7 | 24 | 1/12"-1/12" | | | | 18.0 Gray Silty CLAY, some Organics | |
| 20 | | | | | | | | |
| | S-8 | 24 | 2-2-2-2 | | | 23.0 Dark brown SILT AND ORGANICS | | |
| 25 | | | | | | | | |
| | S-9 | 24 | 5-7-9-12 | | | | | |
| 30 | | | | | | | | |
| | S-10 | 22 | 4-7-7-9 | | | 33.0 Brown M/F SAND, trace Silt | | |
| 35 | | | | | | | | |

NOTES:



TEST BORING LOG

BORING B-4

PAGE 2 OF 2

CLIENT Philadelphia Regional Port Authority

PROJECT NAME PhilaPort Distribution Warehouse

PROJECT NUMBER PRPAX17013.04

PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|---|---------------|
| 35 | | | | | | Depth | Elev. |
| | | | | | | Brown M/F SAND, trace Silt (<i>continued</i>) | |
| | | | | | | 38.0 | -24.5 |
| 40 | S-11 | 22 | 4-6-7-5 | | 3 | Brown M/C/F SAND, trace Silt | |
| | | | | | | 43.0 | -29.5 |
| 45 | S-12 | 10 | 43-45-45-45 | | | Brown M/F/C SAND, some C/F Gravel, trace Silt | Auger Chatter |
| | | | | | | | |
| 50 | S-13 | 22 | 19-20-24-19 | | | | |
| | | | | | | | |
| 55 | S-14 | 2 | 15-15-15-16 | | 4 | | |
| | | | | | | | |
| 60 | S-15 | 20 | 6-10-11-12 | | | | |
| | | | | | | 60.0 | -46.5 |

Boring terminated at 60.0 feet.

NOTES:



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/21/17 **COMPLETED** 12/21/17 **GROUND ELEVATION** 13.5 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger w/ Mud **DURING DRILLING** 13.00 / Elev 0.50
DRILLER / HELPER Eric Blamings **AT END OF DRILLING** ---
LOGGED BY D. Copeland **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|---|---------|
| 0 | | | | | | Depth _____ Elev. _____ | |
| 0.4 | S-1 | 14 | 25-11-50/3" | | P | 5.0 in. BITUMINOUS CONCRETE | Dry |
| | S-2 | 5 | 50/5" | | | FILL: Brown F/C gravel size ROCK FRAGMENTS AND F/M/C SAND | |
| 4.0 | | | | | F | | |
| 5 | S-3 | 6 | 5-3-2-2 | | | FILL: Brown SILT, some F/M Sand, trace Mica | Moist |
| | S-4 | 24 | 2-2-2-2 | | | | |
| | S-5 | 24 | 2-4-3-3 | | | Gray Silty CLAY, trace Organics | |
| 10 | | | | | 1 | | |
| 13.0 | | | | | | | |
| 15 | S-6 | 22 | 1/12"-1/12" | | | Brown Fine SAND, some Silt | Wet |
| | | | | | 3 | | |
| 20 | U-1 | 0 | REC=0% | | | | |
| 20.0 | | | | | | | |
| | S-7 | 24 | 2-2-2-2 | | | Dark brown Silty CLAY, some F/M Sand, little Organics | |
| | U-2 | 20 | REC=83% | | 1 | | |
| 25 | S-8 | 24 | 2-2-4-4 | | | | |
| | | | | | | | |
| 28.0 | | | | | | | |
| 30 | S-9 | 22 | 4-4-4-4 | | | Brown M/F SAND | |
| | | | | | 3 | | |
| 35 | S-10 | 22 | 8-8-9-11 | | | | |

NOTES:



TEST BORING LOG

BORING B-5

PAGE 2 OF 2

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
 PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS | |
|------------|--------------------|----------------|-------------|-------------|--------|---------------------------------|-----------------------------------|--|
| 35 | | | | | | Depth | Elev. | |
| | | | | | | Brown M/F SAND (continued) | | |
| | | | | | 38.0 | -24.5 | | |
| 40 | X S-11 | 22 | 10-11-14-16 | | | | Brown C/F GRAVEL AND M/F SAND | |
| | | | | | | | | |
| 45 | X S-12 | 22 | 5-6-6-5 | | | | Brown M/F SAND, trace Fine Gravel | |
| | | | | | | | | |
| | | | | | | 3 | | |
| 50 | X S-13 | 16 | 7-8-10-11 | | | Brown F/C GRAVEL AND M/C/F SAND | | |
| | | | | | | | | |
| 55 | X S-14 | 18 | 12-11-10-12 | | | Brown C/M/F SAND | | |
| | | | | | | | | |
| 60 | X S-15 | 18 | 4-6-8-8 | | | | | |
| | | | | | | 60.0 | -46.5 | |

Boring terminated at 60.0 feet.

NOTES:



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 1/3/18 **COMPLETED** 1/3/18 **GROUND ELEVATION** 12.5 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger ∇ **DURING DRILLING** 13.00 / Elev -0.50
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY S. Corcoran **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|--|----------|
| 0 | | | | | | Depth _____ Elev. _____ | |
| | S-1 | 5 | 50/5" | | P | 1.1 8.0 in. BITUMINOUS CONCRETE 5.0 in. M/C/F SAND, little F/C gravel size Rock Fragments, trace Silt | 11.4 |
| | S-2 | 10 | 37-50/3" | | | FILL: Black M/F/C SAND, some F/C Gravel, little Silt, trace Brick, Cinder, and Asphalt Fragments | |
| 5 | S-3 | 10 | 12-5-4-3 | | | 6.0 | 6.5 |
| | S-4 | 20 | 6-5-5-5 | | F | FILL: Black F/M/C SAND AND CLAY, little Fine Gravel, trace Brick and Cinder Fragments | |
| | S-5 | 10 | 5-2-2-2 | | | 13.0 | -0.5 |
| 15 | S-6 | 24 | 1-1-1-1 | | | Dark gray Silty CLAY, trace Fine Sand | Wet |
| | S-7 | 24 | WOH/24" | | 1 | 18.0 Gray Silty CLAY, trace Fine Sand, trace Organics | -5.5 |
| | S-8 | 24 | 2-3-2-2 | | | 23.0 -10.5 24.0 Gray Silty CLAY, some Organics, trace Fine Sand Tan to gray F/M SAND, little Silt | Very wet |
| | S-9 | 24 | 7-8-7-8 | | 3 | 28.0 Tan to gray M/F SAND, trace Silt | -15.5 |
| 35 | S-10 | 20 | 5-6-9-6 | | | 33.0 Tan to gray M/F SAND, trace Silt, trace Fine Gravel | -20.5 |

NOTES:



TEST BORING LOG

BORING B-6
PAGE 2 OF 2

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|--|---------|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | | 3 | Tan to gray M/F SAND, trace Silt, trace Fine Gravel (continued) | |
| | | | | | | 38.0 _____ -25.5 | |
| 40 | X S-11 | 12 | 13-18-10-7 | | | Tan to gray M/F/C SAND, little Fine Gravel, trace Silt | |
| | | | | | | 43.0 _____ -30.5 | |
| 45 | X S-12 | 7 | 20-13-16-14 | | | Gray to tan C/M/F SAND, little Fine Gravel, trace Silt | |
| | | | | | | 48.0 _____ -35.5 | |
| 50 | X S-13 | 10 | 4-10-10-11 | | | Gray to tan C/M/F SAND, some F/C Gravel, trace Silt | |
| | | | | | | 53.0 _____ -40.5 | |
| 55 | X S-14 | 2 | 50/3" | | 4 | Gray C/F GRAVEL, little C/M/F Sand | |
| | | | | | | 58.0 _____ -45.5 | |
| 60 | X S-15 | 12 | 24-38-42-44 | | | Yellow to white to tan F/M SAND, trace Fine Gravel, trace Silt, mottled | |
| | | | | | | 63.0 _____ -50.5 | |
| 65 | X S-16 | 24 | 12-16-19-21 | | | Yellow to white to tan F/M SAND, little Clay, trace Fine Gravel, trace Silt, mottled | |
| | | | | | | 68.0 _____ -55.5 | |
| | | | | | | 69.0 _____ -56.5 | |
| 70 | X S-17 | 24 | 17-12-15-13 | | 5 | White to gray CLAY, some to little Fine Sand | |
| | | | | | | 70.0 _____ -57.5 | |

Boring terminated at 70.0 feet.

NOTES:



TEST BORING LOG

BORING B-7
PAGE 1 OF 3

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/27/17 **COMPLETED** 12/27/17 **GROUND ELEVATION** 12 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger **DURING DRILLING** 8.00 / Elev 4.00
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY S. Corcoran **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|---|---------|
| 0 | | | | | | Depth _____ Elev. _____ | |
| 0.6 | S-1 | 6 | 45-50/5" | | P | 7.0 in. BITUMINOUS CONCRETE | |
| 5 | S-2 | 18 | 38-27-20-31 | | F | FILL: Gray to black to brown M/F/C SAND, some Silt, little Fine gravel size Brick, Cinder, Ash and Rock Fragments | Wet |
| | S-3 | 17 | 7-10-6-4 | | | | |
| | S-4 | 18 | 3-4-3-5 | | | | |
| | S-5 | 6 | 3-2-1-1 | | | | |
| 10 | | | | | | | |
| 13.0 | | | | | | NO RECOVERY | TRAP OK |
| 15 | S-6 | 0 | 5-3-2-2 | | | | |
| 18.0 | | | | | | Gray Silty CLAY, trace Organics, trace Fine Sand | |
| 20 | S-7 | 24 | WOH/24" | | | | |
| 23.0 | | | | | 1 | Dark gray Silty CLAY AND F/M SAND, little Organics | Add mud |
| 25 | S-8 | 24 | 1-1-1-1 | | | | |
| 28.0 | | | | | | Tan to gray M/F SAND, trace Silt | |
| 30 | S-9 | 14 | 4-6-7-10 | | 3 | | |
| 35 | S-10 | 12 | 4-7-5-5 | | | | |

NOTES:



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|--|--|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | | | Tan to gray M/F SAND, trace Silt (<i>continued</i>) | |
| | | | | | | 38.0 _____ -26.0 | |
| 40 | X S-11 | 11 | 4-3-3-5 | | 3 | Tan to gray F/M SAND, trace Silt, Micaceous | |
| | | | | | | 43.0 _____ -31.0 | Auger Chatter |
| 45 | X S-12 | 11 | 38-50/5" | | 4 | Tan to gray to purple C/F GRAVEL, some Clay, little F/M Sand | Auger Chatter |
| | | | | | | 48.0 _____ -36.0 | |
| 50 | X S-13 | 12 | 12-8-14-17 | | | Tan to brown to gray C/M/F SAND, little F/C Gravel, trace Silt | |
| | | | | | | 53.0 _____ -41.0 | |
| 55 | X S-14 | 14 | 4-5-6-12 | | | Tan to brown to gray C/M/F SAND, some F/C Gravel, trace Silt | |
| | | | | | 3 | | |
| 60 | X S-15 | 10 | 4-4-14-24 | | | | |
| | | | | | | 63.0 _____ -51.0 | |
| 65 | X S-16 | 12 | 6-6-16-38 | | | Tan to yellow F/M SAND, trace Silt | |
| | | | | | | 68.0 _____ -56.0 | |
| 70 | X S-17 | 20 | 35-32-25-25 | | | Tan M/F SAND, little Fine Gravel, trace Silt | |
| | | | | | 4 | | |
| 75 | X S-18 | 0 | NA | | | 73.0 _____ -61.0 | No SPT sampling possible due to soil rising through augers |
| | | | | | | NO RECOVERY | |

NOTES:



TEST BORING LOG

BORING B-7

PAGE 3 OF 3

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
 PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | | REMARKS |
|---------------|-----------------------|----------------|----------------|----------------|--------|-------------|-------------------------|--|
| | | | | | | Depth | Elev. | |
| | | | | | | | | |
| | | | | | | | NO RECOVERY (continued) | |
| | | | | | 4 | 78.0 | | -66.0 |
| | S-19 | 0 | NA | | | | NO RECOVERY | No SPT sampling possible due to soil rising through augers |
| 80 | | | | | | 80.0 | | -68.0 |

Boring terminated at 80.0 feet.

NOTES:



TEST BORING LOG

BORING B-8
PAGE 1 OF 2

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 1/3/18 **COMPLETED** 1/3/18 **GROUND ELEVATION** 12.5 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger **DURING DRILLING** 8.00 / Elev 4.50
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY S. Corcoran **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-----------------------|-------------|----------------------------------|--|---------|
| 0 | | | | | | Depth _____ Elev. _____ | |
| 0.4 | S-1 | 3 | 50/3" | | P | 5.0 in. BITUMINOUS CONCRETE | |
| | S-2 | 5 | 50/5" | | F | FILL: Gray to black F/M SAND, some Fine Gravel, trace Silt | |
| 5 | S-3 | | 12-26-21-20 | | | | |
| | S-4 | 24 | 21-19-6-4 | | | FILL: Black F/M SAND, little Fine Gravel, trace Silt, trace Brick and Cinder Fragments | |
| | S-5 | 6 | 5-3-3-1 | | | Black F/M SAND AND CLAY, trace Brick and Cinder Fragments | Wet |
| 10 | | | | | | | |
| | S-6 | 20 | 4-5-6-6 | | | Black to dark gray F/M SAND, little Fine Gravel, little Clay | |
| 15 | | | | | | | |
| | S-7 | 24 | WOH/6"-1- WOH/6"-1 | | | Gray Silty CLAY, trace Fine Sand, trace Organics | |
| 20 | | | | | | | |
| | S-8 | 24 | 2-2-2-2 | | Brown SILT AND ORGANICS | | |
| 25 | | | | | | | |
| | S-9 | 24 | 5-6-5-5 | | Gray to tan F/M SAND, trace Silt | | |
| 30 | | | | | | | |
| | S-10 | 5 | 8-12-9-8 | | | | |
| 35 | | | | | | | |

NOTES:



TEST BORING LOG

BORING B-8

PAGE 2 OF 2

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
 PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|---------------------------------|--------------------|----------------|-------------|-------------|--------|---|--------------------|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | 3 | | Gray to tan F/M SAND, trace Silt <i>(continued)</i> | |
| 40 | X S-11 | 20 | 9-14-15-12 | 3 | | | Auger chatter |
| | | | | | | 43.0 _____ -30.5 | |
| 45 | X S-12 | 15 | 24-25-32-32 | 4 | | Gray to tan C/M/F SAND, some F/C Gravel, trace Silt | |
| | | | | | | 48.0 _____ -35.5 | |
| 50 | X S-13 | 0 | 22-24-24-27 | | | Pushing Gravel - NO RECOVERY | |
| | | | | | | 53.0 _____ -40.5 | |
| 55 | X S-14 | 12 | 8-11-12-24 | | | White to gray C/M/F SAND, little to some Clay, little Fine Gravel | |
| | | | | | | 58.0 _____ -45.5 | |
| 60 | X S-15 | 12 | 7-17-23-27 | | | Gray to white Fine SAND, trace Silt | |
| | | | | | | 63.0 _____ -50.5 | |
| 65 | X S-16 | 14 | 9-23-27-33 | | | Gray to white to yellow M/C/F SAND, trace Silt | |
| | | | | | | 68.0 _____ -55.5 | |
| 70 | X S-17 | 0 | 28-50-50/3" | | | NO RECOVERY | Spoon lost in hole |
| | | | | | | 70.0 _____ -57.5 | |
| Boring terminated at 70.0 feet. | | | | | | | |

NOTES:



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/29/17 **COMPLETED** 12/29/17 **GROUND ELEVATION** 12.5 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger **DURING DRILLING** 6.00 / Elev 6.50
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY S. Corcoran **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | Elev. | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|---|-------|--------------|
| 0 | | | | | | Depth | | |
| | | | | | P | 0.8 6.0 in. BITUMINOUS CONCRETE | 11.7 | |
| | | | | | | 2.0 4.0 in. Gray C/F gravel size ROCK FRAGMENTS AND F/M SAND, trace Silt | 10.5 | |
| | | | | | | 4.0 Gray F/M/C SAND, some Fine gravel size Rock Fragments, trace Silt | 8.5 | |
| 5 | S-1 | 10 | 22-18 | | | 5.0 Black to dark gray F/M SAND, little Fine gravel size Rock Fragments, trace Brick, trace Asphalt Fragments | 7.5 | |
| | S-2 | 14 | 24-14-7-8 | | | 7.0 Black to dark gray F/M SAND, little Fine gravel size Rock Fragments, trace Brick, Asphalt, Cinder, and Concrete Fragments | 5.5 | Wet on spoon |
| | S-3 | 18 | 16-10-7-6 | | F | 8.0 Black F/M SAND, little Silt, trace Glass | 4.5 | |
| | S-4 | 20 | 9-6-5-7 | | | Black SILT, some F/M Sand, trace Organics, trace Brick Fragments | | |
| 10 | S-5 | 24 | 7-8-7-4 | | | 13.0 Black C/M/F SAND AND F/C GRAVEL, Debris, Organics, Brick, Concrete, little Clay | -0.5 | Very soft |
| 15 | S-6 | 24 | 1-2-1-1 | | | Gray Silty CLAY, trace Fine Sand | | |
| 20 | S-7 | 24 | WOH/24" | | 1 | | | Very soft |
| 25 | S-8 | 24 | 2-4-4-2 | | 2 | 23.0 Brown to gray SILT, Organics, trace F/M Sand | -10.5 | |
| | | | | | | 24.5 Tan to gray M/F SAND, trace Silt | -12.0 | Added mud |
| 30 | S-9 | 12 | 5-7-9-7 | | 3 | 28.0 Tan to gray M/F SAND, little Silt | -15.5 | |
| 35 | S-10 | 10 | 6-7-7-7 | | | 33.0 Gray M/F SAND, trace Silt | -20.5 | |

NOTES:



TEST BORING LOG

BORING B-9
PAGE 2 OF 2

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|----------------|-------------|--------|--|---------------|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | | | Gray M/F SAND, trace Silt (<i>continued</i>) | |
| 40 | S-11 | 18 | 6-9-5-8 | | 3 | 38.0 -25.5 Gray M/F SAND, trace Fine Gravel, trace Silt | |
| 45 | S-12 | 9 | 38-50/5" | | | 43.0 -30.5 Tan C/F GRAVEL, some M/C/F Sand, trace Silt | Trap replaced |
| 50 | S-13 | 13 | 38-36-15-13 | | | 48.0 -35.5 Tan to gray C/F Gravel, some C/M/F Sand, little Clay | |
| 55 | S-14 | 9 | 37-45-48-38 | | | 53.0 -40.5 Light gray F/M SAND, little Silt, trace Coarse Gravel | |
| 60 | S-15 | 17 | 15-30-35-39 | | 4 | 58.0 -45.5 Yellow to tan to white C/M/F SAND, trace Silt, mottled | |
| 65 | S-16 | 18 | 11-30-45-50/5" | | | 64.0 -51.5 Light gray to white F/M SAND, trace Silt, mottled | |
| 70 | S-17 | 18 | 12-35-35-35 | | | 70.0 -57.5 | |

Boring terminated at 70.0 feet.

NOTES:



TEST BORING LOG

BORING B-10

PAGE 1 OF 3

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/26/17 **COMPLETED** 12/26/17 **GROUND ELEVATION** 13 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger **DURING DRILLING** 13.00 / Elev 0.00
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY S. Corcoran **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|--|---------|
| 0 | | | | | | Depth | Elev. |
| | | | | | P | 0.4 5.0 in. BITUMINOUS CONCRETE | 12.6 |
| | | | | | | 1.0 FILL: Gray to dark gray C/F gravel size ROCK FRAGMENTS AND M/F/C SAND, trace Silt | 12.0 |
| | | | | | | 2.0 FILL: Black to dark gray F/M SAND, some F/C Gravel, trace Brick Fragments | 11.0 |
| 5 | | | | | | 4.0 FILL: Black to dark gray F/M SAND, some F/C Gravel, trace Brick and Cinder Fragments | 9.0 |
| | | | | | F | FILL: Dark gray F/M/C SAND AND SILT, little Fine gravel size Brick, Cinder, Ash and Rock Fragments | |
| | | | | | | 13.0 | 0.0 |
| | | | | | | Dark gray Silty CLAY AND F/M SAND | |
| 15 | | | | | 1 | | |
| | | | | | | 18.0 Gray Silty CLAY, trace Fine Sand, trace Organics | -5.0 |
| | | | | | | 18.5 Brown SILT, some Organics, trace Fine Sand | -5.5 |
| 20 | | | | | 2 | | |
| | | | | | | 23.0 | -10.0 |
| | | | | | | Gray to brown Silty CLAY to Clayey SILT, trace Organics, trace Fine Sand | |
| 25 | | | | | 1 | | |
| | | | | | | 28.0 | -15.0 |
| | | | | | | 29.0 Brown SILT, trace Organics, trace Fine Sand | -16.0 |
| 30 | | | | | 2 | | |
| | | | | | | Tan to gray M/F/C SAND, trace Fine Gravel, trace Silt | |
| | | | | | 3 | | |
| 35 | | | | | | | |

NOTES:



TEST BORING LOG

BORING B-10

PAGE 2 OF 3

CLIENT Philadelphia Regional Port Authority

PROJECT NAME PhilaPort Distribution Warehouse

PROJECT NUMBER PRPAX17013.04

PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|----------------|-------------|--------|--|----------------------|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | | 3 | Tan to gray M/F/C SAND, trace Fine Gravel, trace Silt <i>(continued)</i> | |
| | | | | | | 38.0 _____ -25.0 | |
| 40 | X S-11 | 15 | 9-15-15-12 | | | Gray to tan C/F GRAVEL AND C/M/F SAND, trace Silt | |
| | | | | | | 43.0 _____ -30.0 | |
| 45 | X S-12 | 8 | 14-22-35-22 | | | Gray to tan C/F GRAVEL, some C/M/F Sand, trace Silt | |
| | | | | | 4 | 48.0 _____ -35.0 | |
| 50 | X S-13 | 18 | 35-40-25-32 | | | Gray to tan C/M/F SAND, little C/F Gravel, trace Silt | |
| | | | | | | 53.0 _____ -40.0 | |
| 55 | X S-14 | 0 | 11-9-19-17 | | | NO RECOVERY | No Recovery, TRAP OK |
| | | | | | | 58.0 _____ -45.0 | |
| 60 | X S-15 | 9 | 10-6-10-10 | | 3 | Gray to tan C/F GRAVEL, some C/M/F Sand, trace Silt | |
| | | | | | | 63.0 _____ -50.0 | |
| 65 | X S-16 | 10 | 15-27-36-50/2" | | | Gray to tan C/M/F SAND, little C/F Gravel, trace Silt | |
| | | | | | | 68.0 _____ -55.0 | |
| 70 | X S-17 | 15 | 8-12-46-30 | | 4 | Tan F/M SAND, trace Silt, trace Fine Gravel | |
| | | | | | | 73.0 _____ -60.0 | |
| 75 | X S-18 | 20 | 7-31-50/5" | | | Tan F/M SAND, trace Fine Gravel, trace Silt | |

NOTES:



TEST BORING LOG

BORING B-10

PAGE 3 OF 3

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse

PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | | REMARKS |
|---------------|-----------------------|----------------|----------------|----------------|--------|-------------|---|---------|
| | | | | | | Depth | Elev. | |
| | | | | | 4 | 78.0 | Tan F/M SAND, trace Fine Gravel, trace Silt <i>(continued)</i> | |
| 80 | S-19 | 18 | 5-6-7-7 | | 5 | 80.0 | Red to white to purple Silty CLAY, trace Fine Sand | |

Boring terminated at 80.0 feet.

NOTES:



TEST BORING LOG

BORING B-11
PAGE 1 OF 3

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 1/2/18 **COMPLETED** 1/2/18 **GROUND ELEVATION** 12.5 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger w/ Mud **DURING DRILLING** 13.00 / Elev -0.50
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY D. Copeland **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|---|-----------------|
| 0 | | | | | | Depth | |
| | | | | | | Elev. | |
| | | | | | P | 0.8 4.0 in. BITUMINOUS CONCRETE | 11.7 |
| | | | | | | 2.0 6.0 in. CONCRETE | 10.5 |
| | | | | | | FILL: Brown F/C gravel size BRICK AND ROCK FRAGMENTS | |
| 5 | S-1 | 10 | 30-26 | | | 4.0 FILL: Brown to green Micaceous F/M SAND, some Silt | 8.5 |
| | S-2 | 12 | 38-5-7-6 | | | FILL: Black F/M SAND AND SILT, trace Fine gravel size Ash, Cinders, Coal and Rock Fragments | |
| | S-3 | 12 | 16-4-5-8 | | F | | Wet |
| | S-4 | 6 | 49-10-9-4 | | | | |
| | S-5 | 12 | 4-4-4-5 | | | | |
| 10 | | | | | | | |
| | | | | | | | |
| 15 | S-6 | 0 | 12-9-5-4 | | | 15.0 Dark brown SILT, some Organics | -2.5 |
| 20 | S-7 | 16 | 1/12"-1/12" | | | | |
| 25 | S-8 | 24 | 1-2-1-2 | | 2 | 23.0 Brown to gray Clayey SILT, trace Organics | -10.5 |
| 30 | S-9 | 24 | 5-6-8-9 | | | | Added drill mud |
| 35 | S-10 | 16 | 6-8-8-11 | | 3 | 33.0 Brown F/M SAND trace Silt | -20.5 |

NOTES:

(Continued Next Page)



TEST BORING LOG

BORING B-11
PAGE 2 OF 3

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|---|---------|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | | | Brown F/M SAND trace Silt <i>(continued)</i> | |
| 40 | X S-11 | 16 | 8-9-8-9 | | 3 | | |
| 45 | X S-12 | 18 | 42-37-27-38 | | | 43.0 _____ -30.5 | |
| | | | | | | Brown F/C GRAVEL, some M/C/F Sand, trace Silt | |
| 50 | X S-13 | 18 | 17-12-15-21 | | | | |
| 55 | X S-14 | 18 | 14-28-32-24 | | 4 | | |
| 60 | X S-15 | 18 | 12-14-14-18 | | | | |
| 65 | X S-16 | 0 | 5-6-7-6 | | | 63.0 _____ -50.5 | |
| | | | | | | Tan C/M/F SAND, some F/C Gravel, trace Silt | |
| 70 | X S-17 | 20 | 10-13-20-14 | | 3 | 68.0 _____ -55.5 | |
| | | | | | | Brown F/C GRAVEL, some M/C/F Sand, trace Silt | |
| 75 | X S-18 | 24 | 8-8-10-17 | | 4 | 73.0 _____ -60.5 | |
| | | | | | 5 | Red to gray CLAY | |

NOTES:

(Continued Next Page)




TEST BORING LOG

BORING B-11

PAGE 3 OF 3

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
 PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | | REMARKS |
|---------------|-----------------------|----------------|----------------|---|--------|-------------|-------|---|
| | | | | | | Depth | Elev. | |
| 80 | S-19 | 24 | 6-6-9-14 |  | 5 | 80.0 | -67.5 | Red to gray CLAY (continued) Boring terminated at 80.0 feet. |

NOTES:



TEST BORING LOG

BORING B-12
PAGE 1 OF 2

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/22/17 **COMPLETED** 12/22/17 **GROUND ELEVATION** 13 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger w/ Mud **DURING DRILLING** 8.00 / Elev 5.00
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY D. Copeland **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|--|------------------------------|
| 0 | | | | | | Depth _____ Elev. _____ | |
| | S-1 | 6 | 43-50/3" | | P | 0.8 4.0 in. BITUMINOUS CONCRETE 6.0 in. CONCRETE | |
| | S-2 | 12 | 15-11-12-17 | | | FILL: Green to brown Micaceous Fine SAND AND SILT | Damp |
| 5 | S-3 | 18 | 11-19-18-8 | | | FILL: Brown SILT AND M/F SAND, some Fine gravel size Brick, Concrete, Coal, and Rock Fragments | |
| | S-4 | 0 | 8-9-14-21 | | F | 8.0 _____ 5.0 | |
| | S-5 | 16 | 20-10-12-6 | | | FILL: Black Fine gravel size ROCK FRAGMENTS, some C/M/F Sand, some Silt | Wet Strong petroleum odor |
| | | | | | | 13.0 _____ 0.0 | |
| 15 | S-6 | 24 | 1/12"-1/12" | | 1 | Dark brown Silty CLAY, some Organics | |
| | | | | | | 18.0 _____ -5.0 | |
| 20 | S-7 | 24 | 1/24" | | | Dark brown Clayey SILT AND ORGANICS | |
| | | | | | | | |
| 25 | S-8 | 24 | 1-1-1-1 | | 2 | | |
| | | | | | | | |
| 30 | S-9 | 8 | 5-6-7-7 | | | | |
| | | | | | | | |
| 35 | S-10 | 14 | 5-6-6-7 | | 3 | Brown F/M SAND, trace Silt | Added drilling mud |

NOTES:

(Continued Next Page)



TEST BORING LOG

BORING B-12

PAGE 2 OF 2

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
 PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|---|------------------------|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | | | Brown F/M SAND, trace Silt (<i>continued</i>) | |
| | | | | | | 38.0 _____ -25.0 | |
| 40 | S-11 | 16 | 6-6-6-6 | | 3 | Brown M/F/C SAND | |
| | | | | | | 43.0 _____ -30.0 | |
| 45 | S-12 | 12 | 18-18-7-10 | | | Brown M/F/C SAND AND F/C GRAVEL, trace Silt | |
| | | | | | | 45.0 _____ -32.0 | Auger Chatter |
| | | | | | | COBBLES | |
| | | | | | 4 | | |
| | S-13 | 1 | 50/1" | | | | |
| 50 | | | | | | 50.0 _____ -37.0 | Auger refusal at 50 ft |

Boring terminated at 50.0 feet.

NOTES:



TEST BORING LOG

BORING B-13
PAGE 1 OF 2

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/21/17 **COMPLETED** 12/21/17 **GROUND ELEVATION** 13 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger w/ Mud **DURING DRILLING** 13.00 / Elev 0.00
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY D. Copeland **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS | |
|------------|--------------------|----------------|-------------|-------------|--------|---|------------------------------------|-----|
| 0 | | | | | | Depth _____ Elev. _____ | | |
| 0.8 | S-1 | 16 | 8-8-7 | | P | 7.0 in. BITUMINOUS CONCRETE 2.0 in. PROCESSED AGGREGATE FILL: Gray Micaceous Fine SAND, some Silt | Dry | |
| 4.0 | S-2 | 16 | 9-7-5-5 | | F | FILL: Black SILT, some F/M Sand, trace Fine gravel size Brick and Rock Fragments | Damp | |
| 5 | S-3 | 10 | 5-4-4-4 | | | FILL: Black Silty CLAY | Moist | |
| 8.0 | S-4 | 1 | 40-30-17-9 | | | | Rock fragment clogged spoon | |
| 10 | S-5 | 14 | 8-7-6-6 | | | | Strong petroleum odor 4' to 10' | |
| 13.0 | | | | | | | | |
| 15 | S-6 | 6 | 1/12"-1/12" | | | | Gray to brown Fine SAND, some Silt | Wet |
| 18.0 | | | | | | | | |
| 20 | S-7 | 16 | WOH/24" | | | | Dark gray Silty CLAY | |
| 23.0 | | | | | | | | |
| 25 | S-8 | 24 | 1-1-1-1 | | | Dark brown SILT AND ORGANICS | | |
| 28.0 | | | | | | | | |
| 30 | S-9 | 22 | 1-2-2-4 | | | Brown M/F SAND | Wet | |
| 35 | S-10 | 22 | 6-5-4-6 | | | | | |

NOTES:



TEST BORING LOG

BORING B-13

PAGE 2 OF 2

CLIENT Philadelphia Regional Port Authority

PROJECT NAME PhilaPort Distribution Warehouse

PROJECT NUMBER PRPAX17013.04

PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS | |
|------------|--------------------|----------------|-------------|-------------|--------|-------------------------------------|----------------------------------|-------|
| 35 | | | | | | Depth | Elev. | |
| | | | | | | Brown M/F SAND (continued) | | |
| | | | | | 38.0 | -25.0 | Brown M/C/F SAND | |
| 40 | X S-11 | 22 | 3-6-5-5 | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| 45 | X S-12 | 22 | 10-5-6-6 | | | | 43.0 | -30.0 |
| | | | | | | | Brown Fine GRAVEL AND C/M/F SAND | |
| | | | | | | | | |
| | | | | | 3 | | | |
| | | | | | | 48.0 | -35.0 | |
| 50 | X S-13 | 20 | 8-12-13-25 | | | Brown F/C GRAVEL, some C/M Sand | | |
| | | | | | | | | |
| | | | | | | | | |
| 55 | X S-14 | 22 | 6-8-10-14 | | | 53.0 | -40.0 | |
| | | | | | | Brown C/M/F SAND, trace Fine Gravel | | |
| | | | | | | | | |
| 60 | X S-15 | 22 | 10-13-15-17 | | | 60.0 | -47.0 | |

Boring terminated at 60.0 feet.

NOTES:



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 1/2/18 **COMPLETED** 1/2/18 **GROUND ELEVATION** 13 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger w/ Mud **DURING DRILLING** 13.00 / Elev 0.00
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY D. Copeland **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|---|-----------------|
| 0 | | | | | | Depth | |
| | | | | | | Elev. | |
| | S-1 | 24 | 34-6-5-7 | | P | 1.0 12.0 in. PROCESSED AGGREGATE 12.0 | |
| | S-2 | 4 | 5-7-8-7 | | P | 2.0 FILL: Brown Micaceous Fine SAND AND SILT 11.0 FILL: Brown Micaceous Fine SAND | Damp |
| 5 | S-3 | 22 | 4-4-4-5 | | F | 4.0 FILL: White Micaceous Fine SAND AND SILT 9.0 | |
| | S-4 | 4 | 5-5-3-3 | | F | 6.0 FILL: Black SILT, some Fine Sand, trace Ash, Cinder 7.0 | Wet |
| | S-5 | 24 | 2-2-2-2 | | F | 8.0 Dark brown SILT, trace Organics 5.0 | |
| 10 | | | | | | | |
| | S-6 | 0 | 1/24" | | 2 | | |
| 15 | | | | | | | |
| | S-7 | 24 | 1/12"-1/12" | | 2 | | |
| 20 | | | | | | | |
| | S-8 | 24 | 1/12"-1/12" | | 1 | 23.0 Gray Silty CLAY -10.0 | |
| 25 | | | | | | | |
| | S-9 | 18 | 5-5-8-10 | | 3 | 28.0 Brown F/M SAND, trace Silt -15.0 | Added drill mud |
| 30 | | | | | | | |
| | S-10 | 18 | 10-15-15-15 | | 4 | 33.0 Brown F/M SAND, some F/C Gravel, trace Silt -20.0 | |
| 35 | | | | | | | |

NOTES:



TEST BORING LOG

BORING B-14

PAGE 2 OF 2

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
 PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|------------------|--|---|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | | | Brown F/M SAND, some F/C Gravel, trace Silt (continued) | |
| 40 | X S-11 | 12 | 9-13-14-17 | | | | |
| | | | | | | | |
| 45 | X S-12 | 16 | 49-50/5 | | | 43.0 _____ -30.0 | Brown F/C GRAVEL, some M/C/F Sand, trace Silt |
| | | | | | | | |
| 50 | X S-13 | 20 | 10-20-23-26 | | | 48.0 _____ -35.0 | Light gray Fine SAND, trace Silt |
| | | | | | | | |
| 55 | X S-14 | 4 | 39-50/4" | | 4 | | |
| | | | | | | | |
| 60 | X S-15 | 10 | 33-50/4" | | | | |
| | | | | | | | |
| 65 | X S-16 | 18 | 10-15-17-21 | | | | |
| | | | | | | | |
| 70 | X S-17 | 18 | 7-10-16-19 | | 70.0 _____ -57.0 | | |

Boring terminated at 70.0 feet.

NOTES:



TEST BORING LOG

BORING B-15
PAGE 1 OF 3

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/27/17 **COMPLETED** 12/27/17 **GROUND ELEVATION** 13 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger **DURING DRILLING** 13.00 / Elev 0.00
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY S. Corcoran **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|---|-----------------------------|
| 0 | | | | | | Depth _____ Elev. _____ | |
| 0.7 | S-1 | 18 | 9-8-7-7 | | F | FILL: Dark gray to black F/C gravel size ROCK FRAGMENTS AND F/M/C SAND, trace Silt | 12.3 |
| 2.0 | S-2 | 24 | 16-11-5-3 | | | FILL: Brown to black Micaceous F/M SAND, some Silt, little Fine Gravel | 11.0 |
| 4.0 | S-3 | 24 | 3-4-3-4 | | | FILL: White to tan to brown F/M SAND, some Organics, Debris, some Fine Gravel, little Silt, Micaceous | 9.0 |
| 6.5 | S-4 | 20 | 8-7-13-17 | | | FILL: White to tan F/M SAND, some to AND SILT, Micaceous | 6.5 |
| 8.0 | S-5 | 18 | 8-14-13-10 | | | FILL: Black F/M SAND, little Silt, Organics | 5.0 |
| | | | | | | FILL: Black to tan F/M SAND, some gravel size Rock Fragments, Cinders, Brick, trace Silt | |
| 13.0 | | | | | | | 0.0 |
| 14.0 | S-6 | 24 | 3-2-2-2 | | | FILL: Black to dark gray Silty CLAY, trace Fine Sand, trace Organics, trace Fine Gravel | -1.0 |
| | | | | | | Gray Silty CLAY, trace Fine Sand | |
| 23.0 | | | | | | | -10.0 |
| 25 | S-8 | 20 | 1-2-1-2 | | 1 | Gray Silty CLAY, trace Fine SAND, trace Organics | Petroleum odor Mud added |
| 28.0 | | | | | | | -15.0 |
| 30 | S-9 | 15 | 7-7-8-12 | | | Brown to tan M/F SAND, trace Silt | |
| 35 | S-10 | 12 | 7-8-9-13 | | 3 | | |
| | | | | | | | |

NOTES:



TEST BORING LOG

BORING B-15

PAGE 2 OF 3

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
 PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|---------------|-------------|--------|--|---------------|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | | 3 | Brown to tan M/F SAND, trace Silt (<i>continued</i>) | |
| | | | | | | 38.0 _____ -25.0 | |
| 40 | X S-11 | 12 | 24-22-13-12 | | | 39.5 _____ -26.5 Tan to brown C/F GRAVEL some C/M/F Sand, trace Silt | |
| | | | | | | 43.0 _____ -30.0 Tan to brown M/F/C SAND, some Fine Gravel, trace Silt | |
| 45 | X S-12 | 16 | 18-14-26-15 | | | Tan to brown M/F SAND, little Silt | |
| | | | | | 4 | 48.0 _____ -35.0 | Auger Chatter |
| 50 | X S-13 | 12 | 49-23-19-17 | | | Tan to brown M/F/C SAND, little Silt | |
| | | | | | | 53.0 _____ -40.0 | |
| 55 | X S-14 | 14 | 7-10-9-11 | | | Tan to pink Silty CLAY, little fine Sand, trace Fine Gravel | |
| | | | | | 5 | 58.0 _____ -45.0 | |
| 60 | X S-15 | 16 | 6-26-50-50/5" | | | Tan F/M SAND, some Silt/Clay | |
| | | | | | 4 | 63.0 _____ -50.0 | |
| 65 | X S-16 | 3 | 50/3" | | | Tan to white Silty CLAY, trace Fine Gravel, trace F/M Sand | |
| | | | | | 5 | 68.0 _____ -55.0 | |
| 70 | X S-17 | 12 | 40-50-50/2" | | | Tan to yellow to white M/C/F SAND, little clay, trace Fine Gravel, mottled | |
| | | | | | 4 | 73.0 _____ -60.0 | |
| 75 | X S-18 | 9 | 44-50/3" | | | Tan to gray M/F/C SAND, some to AND C/F GRAVEL, trace Silt, mottled | |

NOTES:



TEST BORING LOG

BORING B-15

PAGE 3 OF 3

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
 PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | | REMARKS |
|---------------|-----------------------|----------------|----------------|----------------|--------|-------------|-------|--|
| | | | | | | Depth | Elev. | |
| 80 | S-19 | 7 | 10-40-50/3" | | 4 | | | |
| | | | | | | 78.0 | -65.0 | Tan to gray M/F/C SAND, some to AND C/F GRAVEL, trace Silt, mottled (<i>continued</i>) |
| | | | | | | 80.0 | -67.0 | Tan to gray to white M/C/F SAND, trace Silt |

Boring terminated at 80.0 feet.

NOTES:



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 1/3/18 **COMPLETED** 1/3/18 **GROUND ELEVATION** 16 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger **DURING DRILLING** 13.00 / Elev 3.00
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY S. Corcoran **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS | |
|------------|--------------------|----------------|-------------|-------------|--------|--|---|---------|
| 0 | | | | | | Depth _____ Elev. _____ | | |
| | S-1 | 24 | 47-20-10-9 | | F | FILL: Tan to gray to black F/M SAND, some to little F/C Gravel | | |
| | S-2 | 12 | 12-14-9-7 | | | 2.0 _____ 14.0 | FILL: Tan to black F/M SAND AND Fine GRAVEL, some Clay, trace Brick Fragments | |
| 5 | S-3 | 12 | 8-9-10-20 | | | 4.0 _____ 12.0 | FILL: Black F/M SAND, some Fine Gravel, trace Cinders, Brick | |
| | S-4 | 0 | 50/5" | | | 6.0 _____ 10.0 | NO RECOVERY | TRAP OK |
| | S-5 | 7 | 2-4-4-3 | | | 8.0 _____ 8.0 | FILL: Red C/F gravel size BRICK FRAGMENTS, some F/M Sand | |
| 10 | | | | | | | | |
| | S-6 | 5 | 1-1-1-1 | | | 13.0 _____ 3.0 | FILL: Black F/C gravel size ROCK FRAGMENTS, some F/M/C Sand, trace Silt | Wet |
| 15 | | | | | | | | |
| | S-7 | 0 | 1-1-1-1 | | | 18.0 _____ -2.0 | NO RECOVERY | TRAP OK |
| 20 | | | | | | | | |
| | S-8 | 24 | 2-2-2-2 | | 1 | 23.0 _____ -7.0 | Gray Silty CLAY, trace Fine Sand, trace Organics | |
| 25 | | | | | | 24.5 _____ -8.5 | Tan to gray F/M SAND, trace Silt | |
| | S-9 | 10 | 3-4-6-9 | | 3 | | | |
| 30 | | | | | | | | |
| | S-10 | 10 | 16-11-20-17 | | | 33.0 _____ -17.0 | Gray F/M SAND, little Fine Gravel, little Clay | |
| 35 | | | | | | | | |

NOTES:



TEST BORING LOG

BORING B-16

PAGE 2 OF 2

CLIENT Philadelphia Regional Port Authority

PROJECT NAME PhilaPort Distribution Warehouse

PROJECT NUMBER PRPAX17013.04

PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|----------------|-------------|--------|---|---------|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | | | Gray F/M SAND, little Fine Gravel, little Clay (continued) | |
| | | | | | | 38.0 _____ -22.0 | |
| 40 | S-11 | 12 | 5-6-7-7 | | 3 | Gray F/M SAND, trace Silt | |
| | | | | | | 43.0 _____ -27.0 | |
| 45 | S-12 | | 29-33-36-28 | | | Tan to gray to red F/M SAND AND F/C GRAVEL, trace Silt | |
| | | | | | | 48.0 _____ -32.0 | |
| 50 | S-13 | 0 | 21-11-18-19 | | 4 | NO RECOVERY | TRAP OK |
| | | | | | | 53.0 _____ -37.0 | |
| 55 | S-14 | 24 | 7-7-10-11 | | 5 | Tan to gray to white CLAY, little F/M Sand | |
| | | | | | | 58.0 _____ -42.0 | |
| 60 | S-15 | 12 | 14-22-47-50/3" | | 4 | Gray Fine SAND, trace Silt | |
| | | | | | | 60.0 _____ -44.0 | |

Boring terminated at 60.0 feet.

NOTES:



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/29/17 **COMPLETED** 12/29/17 **GROUND ELEVATION** 16 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger **DURING DRILLING** 18.00 / Elev -2.00
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY S. Corcoran **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|--|-----------------------|
| 0 | | | | | | Depth _____ Elev. _____ | |
| 0 | S-1 | 12 | 12-10-10-5 | | F | Dark gray F/M SAND AND F/C GRAVEL, trace Silt | Strong petroleum odor |
| 0 | S-2 | 24 | 10-7-8-5 | | | Tan to yellow F/M SAND, little Silt, Micaceous | |
| 5 | S-3 | 16 | 4-4-4-5 | | | Black to brown F/M SAND, little Silt, trace C/F Gravel, trace Brick, Cinders | |
| 5 | S-4 | 17 | 5-6-12-18 | | | Black to tan F/M SAND, little Fine Gravel, little Silt, Micaceous | |
| 10 | S-5 | 17 | 15-6-8-20 | | | Gray Silty CLAY, Organics, some F/M Sand | |
| 15 | S-6 | 12 | 10-3-2-2 | | | | |
| 18.0 | | | | | | 18.0 _____ -2.0 | |
| 20 | S-7 | 10 | 2-1-2-1 | | 1 | Gray Silty CLAY, trace Fine Sand | Wet |
| 25 | U-1 | 23 | REC=95% | | | 25.0 _____ -9.0 | |
| 25 | S-8 | 18 | 8-5-6-6 | | 3 | Gray M/F SAND, trace Silt | |
| 30 | S-9 | 20 | 5-5-5-7 | | | Gray M/F SAND, trace Silt, trace Fine Gravel | |
| 35 | S-10 | 24 | 20-32-13-11 | | | Gray M/F SAND, little C/F Gravel, trace Silt | |

NOTES:



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|--|---------|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | | | Gray M/F SAND, little C/F Gravel, trace Silt <i>(continued)</i> | |
| 40 | X S-11 | 20 | 9-9-10-18 | | | | |
| | | | | | | | |
| 45 | X S-12 | 11 | 10-33-40-47 | | 4 | Tan to gray M/F/C SAND, some to AND F/C GRAVEL, trace Silt | |
| | | | | | | | |
| 50 | X S-13 | 0 | 20-35-20-14 | | | 48.0 _____ -32.0 NO RECOVERY | |
| | | | | | | | |
| 55 | X S-14 | 15 | 7-7-9-15 | | 5 | 53.0 _____ -37.0 White to light gray CLAY, trace Fine Gravel | |
| | | | | | | | |
| 60 | X S-15 | 12 | 30-35-50/3' | | 3 | 58.0 _____ -42.0 Light gray to yellow F/M SAND, trace Silt, mottled | |
| | | | | | | 60.0 _____ -44.0 | |

Boring terminated at 60.0 feet.

NOTES:



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/26/17 **COMPLETED** 12/16/17 **GROUND ELEVATION** 17 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger **DURING DRILLING** 28.00 / Elev -11.00
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY S. Corcoran **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|--------------|-------------|--------|--|--------------|
| 0 | | | | | | Depth _____ Elev. _____ | |
| | S-1 | 14 | 5-10-13-15 | | F | FILL: Black to tan F/M/C SAND, some F/C Gravel, little Silt | |
| | S-2 | 16 | 16-4-5-3 | | | FILL: Brown to tan F/M SAND, little Silt, Micaceous | |
| 5 | S-3 | 5 | 4-13-7-7 | | | FILL: Brown to tan F/M SAND AND C/F GRAVEL, trace Silt | |
| | S-4 | 6 | 18-14-7-7 | | | FILL: Black to brown F/M SAND, little F/C Gravel, some Silt | |
| | S-5 | 15 | 5-5-20-22 | | | FILL: Black F/M SAND AND SILT, trace Fine Gravel, trace Brick and Cinder Fragments | |
| 10 | | | | | | | |
| | S-6 | 16 | 2-1-1-1 | | 1 | Dark gray Silty CLAY, trace Fine Sand | |
| 15 | | | | | | | |
| | S-7 | 24 | WOH/6"-1-2-2 | | 2 | Dark gray to brown Clayey SILT, trace Fine Sand | |
| 20 | | | | | | | |
| | S-8 | 24 | 1-1-1-1 | | | Brown Clayey SILT, Organics, trace Fine Sand Brown SILT AND F/M SAND | |
| 25 | | | | | | | |
| | S-9 | 8 | 4-6-7-8 | | 3 | Tan to gray M/F SAND, trace Silt | Wet on spoon |
| 30 | | | | | | | |
| | S-10 | 14 | 4-6-7-9 | | | Gray M/F SAND, trace Silt | |
| 35 | | | | | | | |

NOTES:



TEST BORING LOG

BORING B-18

PAGE 2 OF 2

CLIENT Philadelphia Regional Port Authority

PROJECT NAME PhilaPort Distribution Warehouse

PROJECT NUMBER PRPAX17013.04

PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|---------------|------------------|--------|---|---------|
| 35 | | | | | | Depth _____ Elev. _____ | |
| | | | | [Dotted pattern] | | Gray M/F SAND, trace Silt <i>(continued)</i> | |
| 40 | X S-11 | 18 | 7-14-13-11 | | | | |
| | | | | [Dotted pattern] | | | |
| 45 | X S-12 | 0 | 15-18-17-14 | | 3 | 43.0 _____ -26.0 NO RECOVERY | TRAP OK |
| | | | | [Dotted pattern] | | | |
| 50 | X S-13 | 0 | 5-6-7-9 | | | 48.0 _____ -31.0 NO RECOVERY | TRAP OK |
| | | | | [Dotted pattern] | | | |
| 55 | X S-14 | 10 | 7-14-20-50/3" | | | 53.0 _____ -36.0 Tan to gray CLAY, trace Fine Sand | |
| | | | | [Wavy pattern] | 5 | | |
| 60 | X S-15 | 16 | 13-36-50/5" | | | 58.0 _____ -41.0 Tan to white F/M SAND AND CLAY, mottled | |
| | | | | [Wavy pattern] | | 60.0 _____ -43.0 | |

Boring terminated at 60.0 feet.

NOTES:



TEST BORING LOG

BORING B-19
PAGE 1 OF 2

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/22/17 **COMPLETED** 12/22/17 **GROUND ELEVATION** 16.5 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger w/ Mud **DURING DRILLING** 8.00 / Elev 8.50
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY D. Copeland **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------------------------------|--|---------|
| 0 | | | | | | Depth _____ Elev. _____ | |
| | S-1 | 18 | 1-10-5-5 | | P | 0.5 6.0 in. PROCESSED AGGREGATE FILL: Brown Fine SAND AND Fine gravel size ROCK FRAGMENTS, trace Silt | |
| | S-2 | 6 | 8-7-10-11 | | | 4.0 _____ 12.5 | |
| 5 | S-3 | 8 | 6-8-7-9 | | | FILL: Brown Micaceous Fine SAND AND SILT | Moist |
| | S-4 | 3 | 15-8-6-6 | | | 8.0 _____ 8.5 | |
| | S-5 | 18 | 8-6-6-5 | | | FILL: Black SILT, some F/M Sand size Incinerate Material, trace Organics | Wet |
| | | | | | | 13.0 _____ 3.5 | |
| 15 | S-6 | 24 | 1/12"-1/12" | | | Brown to gray Silty CLAY, trace Organics | |
| | | | | | | 18.0 _____ -1.5 | |
| 20 | S-7 | 24 | WOH/24" | | | 1 Brown to gray Silty CLAY, some Organics | |
| | | | | | | 23.0 _____ -6.5 | |
| 25 | S-8 | 24 | 1-1-1-1 | | 2 Dark brown SILT AND ORGANICS | | |
| | | | | | 28.0 _____ -11.5 | | |
| 30 | S-9 | 18 | 7-9-12-13 | | 3 Brown M/F SAND, trace Silt | Added drilling mud | |
| | | | | | | | |
| 35 | S-10 | 18 | 6-8-7-5 | | | | |

NOTES:



TEST BORING LOG

BORING B-19

PAGE 2 OF 2

CLIENT Philadelphia Regional Port Authority

PROJECT NAME PhilaPort Distribution Warehouse

PROJECT NUMBER PRPAX17013.04

PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|----------------|-------------|-------------|--------|---|---------|
| 35 | | | | | | Depth | Elev. |
| | | | | | | Brown M/F SAND, trace Silt <i>(continued)</i> | |
| 40 | X S-11 | 18 | 5-5-7-6 | | 3 | | |
| | | | | | | 43.0 | -26.5 |
| 45 | X S-12 | 16 | 22-29-6-9 | | | Brown F/C GRAVEL AND M/F SAND, trace Silt | |
| 50 | X S-13 | 16 | 10-13-15-18 | | 4 | | |
| 55 | X S-14 | 16 | 10-11-12-15 | | | | |
| 60 | X S-15 | 16 | 10-10-8-13 | | | 60.0 | -43.5 |

Boring terminated at 60.0 feet.

NOTES:



TEST BORING LOG

BORING B-20
PAGE 1 OF 2

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 12/21/17 **COMPLETED** 12/21/17 **GROUND ELEVATION** 16.5 +/- feet NAVD88
DRILLING CONTRACTOR CGC Geoservices, LLC **WATER ENCOUNTERED:**
DRILLING METHOD Hollow Stem Auger w/ Mud ∇ **DURING DRILLING** 28.00 / Elev -11.50
DRILLER / HELPER Eric Blemings **AT END OF DRILLING** ---
LOGGED BY D. Copeland **CHECKED BY** D. Marrano **AFTER DRILLING** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS | | |
|------------|--------------------|----------------|-------------|-------------|--------|-------------|--------------------------------|--|---------------------------------|
| 0 | | | | | | Depth | | | |
| | | | | | | Elev. | | | |
| | S-1 | 18 | 16-20-21 | | P | 0.6 | 6.0 in. BITUMINOUS CONCRETE | 15.9 | |
| | S-2 | 5 | 50/5" | | | | 2.0 | 1.0 in. PROCESSED AGGREGATE | 14.5 |
| | | | | | | | | FILL: Brown F/M/C SAND AND Fine gravel size ROCK FRAGMENTS | |
| 5 | S-3 | 20 | 4-5-5-7 | | | | | FILL: Dark brown SILT, some F/M Sand, trace gravel size Rock Fragments | Moist |
| | S-4 | 20 | 3-3-4-5 | | F | | 6.0 | FILL: Black SILT, some Fine Sand | 10.5 |
| | S-5 | 20 | 6-7-7-7 | | | | | | Wet |
| 10 | | | | | | | | | Strong petroleum odor 4' to 10' |
| | | | | | | | 13.0 | Dark gray Silty CLAY, trace Organics | 3.5 |
| 15 | S-6 | 24 | 1-1-1-2 | | | | | | |
| | S-7 | 24 | 1-1-1-1 | | 1 | | | | |
| 20 | | | | | | | | | |
| | S-8 | 24 | 1-1-1-2 | | | 23.0 | Dark brown SILT, some Organics | -6.5 | |
| 25 | | | | | 2 | | | | |
| | S-9 | 22 | 2-3-4-5 | | | 28.0 | Brown M/F SAND | -11.5 | |
| 30 | | | | | | | | Drilling mud added | |
| | S-10 | 22 | 3-4-4-5 | 3 | | | | | |
| 35 | | | | | | | | | |

NOTES:



TEST BORING LOG

CLIENT Philadelphia Regional Port Authority PROJECT NAME PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013.04 PROJECT LOCATION Philadelphia, PA

| DEPTH (ft) | SAMPLE TYPE NUMBER | RECOVERY (in.) | BLOW COUNTS | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS | |
|------------|--------------------|----------------|-------------|-------------|--------|---------------------------------|---------|-------|
| 35 | | | | | | Depth _____ Elev. _____ | | |
| | | | | | | Brown M/F SAND (continued) | | |
| 40 | X S-11 | 22 | 5-5-6-8 | | 3 | | | |
| 45 | X S-12 | 22 | 5-6-7-6 | | | | | |
| 48.0 | | | | | | | | -31.5 |
| 50 | X S-13 | 22 | 10-9-8-11 | | 48 | Brown F/C GRAVEL, some M/F Sand | | |
| 55 | X S-14 | 22 | 12-10-9-11 | | | | | |
| 60.0 | X S-15 | 22 | 10-14-17-13 | | | | | -43.5 |
| | | | | | | | | |

Boring terminated at 60.0 feet.

NOTES:



TEST PIT LOG

Test Pit TP-1

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 8.5'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY N. Di Sessa **CHECKED BY** D. Marano **0 HRS AFTER EXCAVATION** 8.0' / Elev 0.5'

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|-------------|--------|--|------------------------------|
| 0 | | | | Depth _____ Elev. _____ | |
| | | | P | 0.3 ASPHALT 8.3 | |
| | | | | 1.0 Processed Aggregate similar to 3A 7.5 | |
| | | | | FILL: Gray F/M/C SAND and F GRAVEL and BRICK FRAGMENTS, trace Silt | |
| | | | | 4.0 4.5 | |
| 5 | | | F | FILL: Black SILT, some F/M Sand, trace F/C Gravel | |
| | | | | 9.0 -0.5 | Trace Timber Asphalt Odor |

Test Pit terminated at 9.0 feet.

NOTES:










TEST PIT LOG

Test Pit TP-2

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 8.5'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY N. Di Sessa **CHECKED BY** D. Marano **0 HRS AFTER EXCAVATION** 9.0' / Elev -0.5'

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|---|--------|---|--------------------|
| 0 | | | | Depth _____ Elev. _____ | |
| | |  | P | 0.3 ASPHALT _____ 8.3 | |
| | |  | | 1.0 Processed Aggregate similar to 3A _____ 7.5 | |
| | |  | | FILL: Red-Brown F SAND and SILT | |
| | |  | | 3.0 FILL: Green micaceous F SAND and SILT, trace F/C Gravel _____ 5.5 | |
| | |  | | 4.0 FILL: Black F SAND, some SILT and F/C Gravel _____ 4.5 | |
| 5 | |  | F | | |
| | |  | | | Oily water surface |
| | | | | 9.0 _____ -0.5 | |

Test Pit terminated at 9.0 feet.

NOTES:



TEST PIT LOG

Test Pit TP-3

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 8.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY N. Di Sessa **CHECKED BY** D. Marano **AFTER EXCAVATION** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|-------------|--------|--|---------|
| 0 | | | | Depth _____ Elev. _____ | |
| | | | P | 0.3 ASPHALT 7.7 | |
| | | | | 1.0 Processed Aggregate similar to 3A 7.0 | |
| | | | | FILL: Tan F/M SAND, some Clay and F Gravel | |
| | | | | 4.0 4.0 | |
| 5 | | | | FILL: Black F/M SAND, some C/F Gravel, trace Silt | |
| | | | F | 6.0 2.0 | |
| | | | | FILL: Black F/M SAND, some to little Silt, little F Gravel | |
| 10 | | | | | |
| | | | | 11.0 -3.0 | |

Test Pit terminated at 11.0 feet.

NOTES:



TEST PIT LOG

Test Pit TP-4

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 8.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY N. Di Sessa **CHECKED BY** D. Marano **0 HRS AFTER EXCAVATION** 9.0' / Elev -1.0'

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|---|--------|---|---------|
| 0 | | | | Depth _____ Elev. _____ | |
| | | | P | 0.3 ASPHALT 7.7 | |
| | | | | 1.0 Processed Aggregate similar to 3A 7.0 | |
| | | | | FILL: Gray F/M SAND and F Gravel, some Clay, trace Brick Fragments | |
| | | | | 4.0 FILL: Black F/M SAND, some F Gravel, trace Brick Fragments and Silt 4.0 | |
| 5 | | | F | | |
| | | | | 9.5 -1.5 | |

Test Pit terminated at 9.5 feet.

NOTES:



TEST PIT LOG

Test Pit TP-5

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 10.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY N. Di Sessa **CHECKED BY** D. Marano **0 HRS AFTER EXCAVATION** 9.0' / Elev 1.0'

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|-------------|--------|--|-------------------|
| 0 | | | | Depth _____ Elev. _____ | |
| | | | P | 0.3 ASPHALT 9.7 | |
| | | | | Processed Aggregate similar to 3A | |
| | | | | 1.0 9.0 | |
| | | | | 1.5 FILL: Brown C/F gravel size ROCK FRAGMENTS and F/M SAND, trace Silt 8.5 | |
| | | | | FILL: Tan F/M SAND, little F Gravel, trace Silt and Brick Fragments | Rebar Encountered |
| | | | | 3.0 7.0 | |
| | | | | FILL: Black F/M SAND, some Brick Fragments, little F Gravel, trace Cinder Fragments, glass | |
| 5 | | | F | 5.0 5.0 | |
| | | | | FILL: Brown-Orange-Gray F/M/C SAND, some F/C Gravel, some Silt | |
| | | | | 9.0 1.0 | |

Test Pit terminated at 9.0 feet.

NOTES:



TEST PIT LOG

Test Pit TP-6

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 12.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY N. Di Sessa **CHECKED BY** D. Marano **0 HRS AFTER EXCAVATION** 10.5' / Elev 1.5'

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|-------------|--------|---|-----------------------------------|
| 0 | | | | Depth _____ Elev. _____ | |
| | | | P | 0.2 ASPHALT 11.8 | |
| | | | | 1.0 Processed Aggregate similar to 3A 11.0 | |
| | | | | 2.0 FILL: Brown F/M SAND, some C/F Gravel, trace Silt 10.0 | |
| | | | | 3.0 FILL: Brown to Tan F/M SAND, little F Gravel, trace Silt 9.0 | |
| | | | | 4.0 FILL: Brown to Black F/M SAND, little F Gravel, trace Cinder Fragments and Silt 8.0 | |
| 5 | | | F | 5.0 FILL: Black F/M SAND, some Silt, some to little F/C Gravel and Brick Fragments 7.0 | |
| 10 | | | | 10.5 Test Pit terminated at 10.5 feet. 1.5 | Telephone poles Hole collapsed |

NOTES:



TEST PIT LOG

Test Pit TP-7

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/19/19 **COMPLETED** 4/19/19 **GROUND ELEVATION** 10.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY N. Di Sessa **CHECKED BY** D. Marano **AFTER EXCAVATION** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|-------------|--------|--|----------------------------|
| 0 | | | | Depth _____ Elev. _____ | |
| | | | P | 0.5 ASPHALT 9.5 | |
| | | | | 1.0 Processed Aggregate similar to 3A 9.0 | |
| | | | | FILL: Tan to Brown F/M SAND, some C/F Gravel, trace Silt | Wood Post (telephone pole) |
| 5 | | | | | Moist |
| | | | F | 6.0 FILL: Black M/C/F SAND and F/C GRAVEL and BRICK FRAGMENTS, little Clay, little organics, debris, wood 4.0 | |
| 10 | | | | | |
| | | | | 11.0 _____ -1.0 | |

Test Pit terminated at 11.0 feet.

NOTES:



TEST PIT LOG

Test Pit TP-8

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/19/19 **COMPLETED** 4/19/19 **GROUND ELEVATION** 10.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY N. Di Sessa **CHECKED BY** D. Marano **AFTER EXCAVATION** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|-------------|--------|---|---------|
| 0 | | | | Depth _____ Elev. _____ | |
| | | | P | 0.3 ASPHALT 9.7 | |
| | | | | 1.0 Processed Aggregate similar to 3A 9.0 | |
| | | | | FILL: Tan to Brown F/M SAND, some C/F Gravel, trace Silt | |
| | | | | 4.0 6.0 | |
| 5 | | | F | FILL: Black M/C/F SAND and F/C BRICK FRAGMENTS, little Clay, debris | |
| 10 | | | | | |
| | | | | 11.0 -1.0 | |

Test Pit terminated at 11.0 feet.

NOTES:










TEST PIT LOG

Test Pit TP-9

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/19/19 **COMPLETED** 4/19/19 **GROUND ELEVATION** 9.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY N. Di Sessa **CHECKED BY** D. Marano **0 HRS AFTER EXCAVATION** 9.0' / Elev 0.0'

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|---|--------|--|---------|
| 0 | | | | Depth _____ Elev. _____ | |
| | |  | | 0.3 ASPHALT 8.7 | |
| | |  | | 1.0 Processed Aggregate similar to 3A 8.0 | |
| | |  | | FILL: Black F/C GRAVEL and F/M/C SAND, little Silt | |
| | |  | | 4.0 5.0 | |
| 5 | |  | | FILL: Brown SILT, some F/M SAND, trace F Gravel | |
| | |  | | 6.0 3.0 | |
| | |  | F | FILL: Black Silty Clay, some F/M SAND | |
| 10 | | | | | |
| | | | | 11.0 -2.0 | |

Test Pit terminated at 11.0 feet.

NOTES:







TEST PIT LOG

Test Pit TP-10

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/19/19 **COMPLETED** 4/19/19 **GROUND ELEVATION** 9.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY N. Di Sessa **CHECKED BY** D. Marano **0 HRS AFTER EXCAVATION** 9.0' / Elev 0.0'

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|--|--------|--|---------|
| 0 | | | | Depth _____ Elev. _____ | |
| | |  | P | 0.3 ASPHALT 8.8 | |
| | |  | | 1.0 Processed Aggregate similar to 3A 8.0 | |
| | |  | | FILL: Black F/C GRAVEL and F/M/C SAND, little Silt | |
| | |  | F | 4.0 FILL: Brown F/M SAND, some Silt, little F/C Gravel and Brick Fragments, trace Clay 5.0 | |
| 5 | | | | | |
| | | | | 9.0 0.0 | |

Test Pit terminated at 9.0 feet.

NOTES:



TEST PIT LOG

Test Pit P-1

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 8.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY E. Iannetti **CHECKED BY** D. Marano **AFTER EXCAVATION** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|-------------|--------|--|---------|
| 0 | | | | Depth | Elev. |
| | | | P | 0.5 6" ASPHALT | 7.5 |
| | | | | 1.0 6" Processed Aggregate similar to 3A | 7.0 |
| | | | | 1.3 Tan F/M/C SAND | 6.7 |

Test Pit terminated at 1.3 feet.

NOTES:



TEST PIT LOG

Test Pit P-2

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 12.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY E. Iannetti **CHECKED BY** D. Marano **AFTER EXCAVATION** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|-------------|--------|--------------------------------------|---------|
| 0 | | | | Depth | Elev. |
| | | | P | 0.4 5" ASPHALT | 11.6 |
| | | | | 9" Processed Aggregate similar to 3A | |
| | | | | 1.2 | 10.8 |
| | | | | 1.5 Tan F/M/C SAND | 10.5 |

Test Pit terminated at 1.5 feet.

NOTES:



TEST PIT LOG

Test Pit P-3

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 12.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY E. Iannetti **CHECKED BY** D. Marano **AFTER EXCAVATION** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|---|--------|--------------------------------------|---------|
| 0 | | | | Depth | Elev. |
| | |  | P | 0.4 5" ASPHALT | 11.6 |
| | |  | | 8" Processed Aggregate similar to 3A | |
| | | | | 1.1 | 10.9 |

Test Pit terminated at 1.1 feet.

NOTES:





TEST PIT LOG

Test Pit P-4

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 9.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY E. Iannetti **CHECKED BY** D. Marano **AFTER EXCAVATION** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | Elev. | REMARKS |
|------------|--------------------|---|--------|---------------------------------------|-------|---|
| 0 | | | | Depth | | |
| | |  | P | 0.3 4" ASPHALT | 8.7 | Concrete slab encountered on one side of test pit |
| | |  | | 11" Processed Aggregate similar to 3A | | |
| | | | | 1.3 | 7.8 | |

Test Pit terminated at 1.3 feet.

NOTES:




TEST PIT LOG

Test Pit P-5

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 9.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY E. Iannetti **CHECKED BY** D. Marano **AFTER EXCAVATION** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|---|--------|--|---------|
| 0 | | | | Depth | Elev. |
| | |  | P | 0.3 4" ASPHALT | 8.7 |
| | |  | | 1.0 8" Processed Aggregate similar to 3A | 8.0 |

Test Pit terminated at 1.0 feet.

NOTES:





TEST PIT LOG

Test Pit P-6

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 11.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY E. Iannetti **CHECKED BY** D. Marano **AFTER EXCAVATION** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|----------------------------------|--------------------|---|--------|--------------------------------------|---------|
| 0 | | | | Depth | Elev. |
| | |  | P | 0.3 4" ASPHALT | 10.7 |
| | |  | | 9" Processed Aggregate similar to 3A | |
| | | | | 1.1 | 9.9 |
| | | | | 1.2 Tan F/M/C SAND | 9.8 |
| Test Pit terminated at 1.2 feet. | | | | | |

NOTES:





TEST PIT LOG

Test Pit P-7

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 12.5'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY E. Iannetti **CHECKED BY** D. Marano **AFTER EXCAVATION** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|---|--------|---------------------------------------|---------|
| 0 | | | | Depth | Elev. |
| | |  | P | 0.3 4" ASPHALT | 12.2 |
| | |  | | 10" Processed Aggregate similar to 3A | |
| | | | | 1.2 | 11.3 |

Test Pit terminated at 1.2 feet.

NOTES:





TEST PIT LOG

Test Pit P-8

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 9.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY E. Iannetti **CHECKED BY** D. Marano **AFTER EXCAVATION** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|---|--------|---------------------------------------|---------|
| 0 | | | | Depth | Elev. |
| | |  | P | 0.3 4" ASPHALT | 8.7 |
| | |  | | 10" Processed Aggregate similar to 3A | |
| | | | | 1.2 | 7.8 |

Test Pit terminated at 1.2 feet.

NOTES:



TEST PIT LOG

Test Pit P-9

PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 9.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY E. Iannetti **CHECKED BY** D. Marano **AFTER EXCAVATION** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|-------------|--------|--------------------------------------|---------|
| 0 | | | | Depth | Elev. |
| | | | P | 7" ASPHALT | |
| | | | | 0.6 | 8.4 |
| | | | | 6" Processed Aggregate similar to 3A | |
| | | | | 1.1 | 7.9 |

Test Pit terminated at 1.1 feet.

NOTES:






TEST PIT LOG

Test Pit P-10


PAGE 1 OF 1

CLIENT Philadelphia Regional Port Authority **PROJECT NAME** PhilaPort Distribution Warehouse
PROJECT NUMBER PRPAX17013 **PROJECT LOCATION** Philadelphia, PA
DATE STARTED 4/18/19 **COMPLETED** 4/18/19 **GROUND ELEVATION** 13.0'
EXCAVATION CONTRACTOR Ambient Group, LLC **WATER ENCOUNTERED:**
EXCAVATION METHOD Rubber Tire Backhoe **DURING EXCAVATION** ---
OPERATOR / HELPER Victor **AT END OF EXCAVATION** ---
LOGGED BY E. Iannetti **CHECKED BY** D. Marano **AFTER EXCAVATION** ---

| DEPTH (ft) | SAMPLE TYPE NUMBER | GRAPHIC LOG | STRATA | DESCRIPTION | REMARKS |
|------------|--------------------|---|--------|--|---------|
| 0 | | | | Depth | Elev. |
| | |  | P | 0.3 4" ASPHALT | 12.7 |
| | |  | | 8.5" Processed Aggregate similar to 3A | |
| | |  | | 1.2 | 11.8 |
| | | | | 1.5 Tan F/M/C SAND | 11.5 |

Test Pit terminated at 1.5 feet.

NOTES:



| REVISIONS | | | |
|-----------|-------------|------|----|
| NO. | DESCRIPTION | DATE | BY |
| # | # | # | # |
| | | | |
| | | | |

LEGEND

- B-1 INDICATES APPROXIMATE TEST BORING LOCATION AND IDENTIFYING NUMBER FOR THE CURRENT STUDY.
- WH-01 INDICATES APPROXIMATE TEST BORING LOCATION AND IDENTIFYING NUMBER CONDUCTED BY OTHERS FOR THE PRELIMINARY STUDY.

NOTES

WATER LEVELS, WHERE SHOWN, ARE THOSE OBSERVED AT THE TIME NOTED AND MAY NOT REFLECT DAILY OR SEASONAL VARIATIONS IN THE GROUND WATER LEVEL.

THE SUBSURFACE CONDITIONS REVEALED BY THIS STUDY REPRESENT CURRENT CONDITIONS AT THE SPECIFIED TEST LOCATIONS ONLY AND MAY NOT BE INDICATIVE OF CONDITIONS AT OTHER LOCATIONS.



U:\ACCOUNTS\PRPAX\17013 - PHILAPORT DISTRIBUTION CENTER\DESIGN\BILP-1.DWG
 PLOTTED: 1/23/2018 1:38:26 PM BY: DAVID A. COPELAND PLOTSTYLE: PENNONI.NCS,STB, PROJECT STATUS: ---



PENNONI ASSOCIATES INC.
 2041 Avenue C, Suite 100
 Bethlehem, PA 18017
 T 610.231.0600 F 610.231.2033

ALL DOCUMENTS PREPARED BY PENNONI ASSOCIATES ARE INSTRUMENTS OF SERVICE IN RESPECT OF THE PROJECT. THEY ARE NOT INTENDED OR REPRESENTED TO BE SUITABLE FOR REUSE BY OWNER OR OTHERS ON THE EXTENSIONS OF THE PROJECT OR ON ANY OTHER PROJECT. ANY REUSE WITHOUT WRITTEN VERIFICATION OR ADAPTATION BY PENNONI ASSOCIATES FOR THE SPECIFIC PURPOSE INTENDED WILL BE AT OWNERS SOLE RISK AND WITHOUT LIABILITY OR LEGAL EXPOSURE TO PENNONI ASSOCIATES; AND OWNER SHALL INDEMNIFY AND HOLD HARMLESS PENNONI ASSOCIATES FROM ALL CLAIMS, DAMAGES, LOSSES AND EXPENSES ARISING OUT OF OR RESULTING THEREFROM.

PHILAPORT DISTRIBUTION WAREHOUSE
 PACKER AVENUE
 PHILADELPHIA, PA

BORING LOCATION PLAN

PHILADELPHIA REGIONAL PORT AUTHORITY
 3460 N. DELAWARE AVENUE
 PHILADELPHIA, PA 19134

| | |
|---------------|-------------|
| PROJECT | PRPAX 17013 |
| DATE | 2018-01-23 |
| DRAWING SCALE | 1"=100' |
| DRAWN BY | DAC |
| APPROVED BY | DPM |
| DRAWING NO. | LP-1 |
| SHEET | 1 OF 1 |


ALL DIMENSIONS MUST BE VERIFIED BY CONTRACTOR
 DISCREPANCIES BEFORE PROCEEDING WITH WORK

PHILAPORT DISTRIBUTION CENTER
 3309 SOUTH GALLOWAY AVENUE & 3401 SOUTH LAWRENCE STREET
 PHILADELPHIA, PA 19148

GRADING PLAN
 PHILADELPHIA REGIONAL PORT AUTHORITY
 3400 NORTH DELAWARE AVENUE
 PHILADELPHIA, PA 19134

| NO. | DATE | BY | REVISIONS |
|-----|------------|-----|----------------------|
| 1 | 2018-04-01 | JAS | 30% DESIGN DOCUMENTS |

| PROJECT | PRPAX17013 |
|---------------|------------|
| DATE | 2019-04-01 |
| DRAWING SCALE | 1" = 60' |
| DRAWN BY | SJK |
| APPROVED BY | KEW |



LEGEND

- | | | | |
|-----------|-----------------------------|-----------|-------------------------------|
| — — — — — | PROPERTY LINE | — — — — — | PROPOSED LIMIT OF DISTURBANCE |
| — — — — — | ADJACENT PROPERTY LINE | — — — — — | PROPOSED CURB |
| — — — — — | RIGHT OF WAY LINE | — — — — — | PROPOSED EDGE OF PAVEMENT |
| — — — — — | HISTORIC BUILDING | — — — — — | PROPOSED BUILDING |
| — — — — — | BUILDING SETBACK LINE | — — — — — | PROPOSED FUTURE BUILDING |
| — — — — — | EXISTING FENCE | — — — — — | PROPOSED STORM SEWER |
| — — — — — | EXISTING TELEPHONE EASEMENT | — — — — — | PROPOSED SANITARY SEWER |
| — — — — — | EXISTING GAS EASEMENT | — — — — — | PROPOSED FIRE SERVICE |
| — — — — — | EXISTING EASEMENT | — — — — — | PROPOSED WATER SERVICE |
| — — — — — | EXISTING BUILDING | — — — — — | PROPOSED ELECTRIC SERVICE |
| — — — — — | EXISTING CURB | — — — — — | PROPOSED GAS SERVICE |
| — — — — — | EXISTING CONCRETE | — — — — — | PROPOSED SURFACE UTILITIES |
| — — — — — | EXISTING MANHOLE | — — — — — | PROPOSED STOP BAR |
| — — — — — | EXISTING VALVES | — — — — — | PROPOSED SIGN |
| — — — — — | EXISTING INLET | — — — — — | PROPOSED MAJOR CONTOUR |
| — — — — — | EXISTING SEWER VENT | — — — — — | PROPOSED MINOR CONTOUR |
| — — — — — | EXISTING LIGHT POLE | — — — — — | PROPOSED FLOW ARROW |
| — — — — — | EXISTING ELECTRIC UTILITIES | — — — — — | PROPOSED SPOT ELEVATION |
| — — — — — | EXISTING OVERHEAD ELECTRIC | — — — — — | |
| — — — — — | EXISTING GAS METER | — — — — — | |
| — — — — — | EXISTING HYDRANT | — — — — — | |
| — — — — — | EXISTING TRAFFIC SIGNAL | — — — — — | |
| — — — — — | EXISTING BOLLARD | — — — — — | |
| — — — — — | EXISTING POST | — — — — — | |
| — — — — — | EXISTING SIGN | — — — — — | |
| — — — — — | EXISTING TREE | — — — — — | |

NOTES:

- SITE INFORMATION:**
 CURRENT SITE ADDRESS:
 3309 SOUTH GALLOWAY AVENUE & 3401 SOUTH LAWRENCE STREET
 39TH WARD, CITY & COUNTY OF PHILADELPHIA
 COMMONWEALTH OF PENNSYLVANIA 19148
 CPA #S 885900807 & 885052875
- OWNER/CLIENT:**
 PHILADELPHIA REGIONAL PORT AUTHORITY
 3400 NORTH DELAWARE AVENUE
 PHILADELPHIA, PA 19134
- DESIGNER:**
 PENNONI
 1900 MARKET STREET, SUITE 300
 PHILADELPHIA, PA 19103
- SITE NOTES:**
- A FIELD SURVEY OF THE SITE WAS PERFORMED BY PENNONI ASSOCIATES IN APRIL 2017.
 - LOCATIONS OF ON AND OFF SITE UTILITIES AS SHOWN ARE APPROXIMATE AND MAY OR MAY NOT BE COMPLETE. THE NATURE AND EXACT LOCATION OF EXISTING UTILITIES SHOULD BE VERIFIED PRIOR TO INITIATING ANY ACTIVITY THAT MAY AFFECT THEIR USE OR LOCATION.
 - THE LOCATION OF THE EXISTING UNDERGROUND UTILITIES SHOWN ON THIS PLAN HAVE BEEN TAKEN FROM EXISTING UTILITY RECORDS AVAILABLE AT THE TIME THESE PLANS WERE PREPARED AND FROM SURFACE OBSERVATION OF THE SITE. COMPLETENESS OR ACCURACY OF LOCATION AND DEPTH OF UNDERGROUND UTILITIES AND STRUCTURES IS NOT GUARANTEED.
 - IN ACCORDANCE WITH PA ACT 267 OF 1974 AS AMENDED BY PA ACT 121 OF 2008 ENTITLED "UNDERGROUND UTILITY LINE PROTECTION LAW," THE CONTRACTOR SHALL NOTIFY ALL UTILITIES WITHIN THE WORK AREA VIA THE PENNSYLVANIA ONE CALL SYSTEM, INC. (800-242-1776) A MINIMUM OF 3 WORKING DAYS BEFORE THE START OF EXCAVATION.
 - THE CONTRACTOR SHALL VERIFY LOCATIONS AND DEPTHS OF ALL UNDERGROUND UTILITIES AND STRUCTURES BEFORE THE START OF WORK.
 - IF CONFLICTS ARE FOUND THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE OWNER AND DESIGN ENGINEER FOR INSTRUCTION BEFORE PROCEEDING WITH WORK.
 - ALL BOUNDARY DIMENSIONS SHOWN ARE IN CITY OF PHILADELPHIA DISTRICT STANDARD MEASURE (DS) UNLESS DESIGNATED (US) TO DENOTE U.S. SURVEY FOOT.
 - THE HORIZONTAL DATUM FOR THIS PROJECT REFERENCES THE PENNSYLVANIA STATE PLANE COORDINATE SYSTEM, SOUTH ZONE, NORTH AMERICAN DATUM OF 1983.
 - THE VERTICAL DATUM FOR THIS PROJECT REFERENCES THE VERTICAL DATUM OF THE CITY OF PHILADELPHIA (CITY).

FLOOD ZONE INFORMATION:

BY GRAPHIC PLOTTING ONLY, BASED UPON THE FLOOD INSURANCE RATE MAP, PANEL NOS. 191-194 OF 230, COMMUNITY MAP NO. 420770191-4H WHICH BEARS AN EFFECTIVE DATE OF NOVEMBER 18TH 2015, THE SITE IS LOCATED IN THE FOLLOWING AREA:

ZONE X AREA DETERMINED TO BE OUTSIDE THE 0.2% ANNUAL CHANCE FLOODPLAIN

NO FIELD SURVEYING WAS PERFORMED TO DETERMINE THIS ZONE AND AN ELEVATION CERTIFICATE MAY BE NEEDED TO VERIFY THIS DETERMINATION OR APPLY FOR A VARIANCE FROM THE FEDERAL EMERGENCY MANAGEMENT AGENCY.

MUNICIPAL ZONING INFORMATION:
 THE SITE IS LOCATED IN THE FOLLOWING ZONE IN THE CITY OF PHILADELPHIA:
 I-2 (MEDIUM INDUSTRIAL)


FOR COMPLETE ZONING INFORMATION PLEASE REFER TO THE ZONING CODE OF THE CITY OF PHILADELPHIA AS CURRENTLY AMENDED

REFERENCE PLANS:

EXISTING CONDITIONS SURVEY PERFORMED IN APRIL 2017 BY PENNONI ASSOCIATES INC.
 BOUNDARY AND TOPOGRAPHIC INFORMATION SHOWN HEREON IS TAKEN FROM THE PLANS ENTITLED "ALTANSPIS LAND TITLE SURVEY - SHEETS V0301, V0302, AND V0303, DATED 05-23-2017."

GRADING NOTES:

- A GEOTECHNICAL ENGINEER IS REQUIRED TO INSPECT, TEST AND CERTIFY TO THE COMPACTION OF ALL LOAD BEARING FILLS.
- MINIMUM PAVEMENT GRADE SHALL BE 1.5% UNLESS NOTED OTHERWISE.
- BEDDING REQUIREMENTS SPECIFIED HEREIN ARE TO BE CONSIDERED AS MINIMUMS FOR RELATIVELY DRY, STABLE EARTH CONDITIONS. ADDITIONAL BEDDING SHALL BE REQUIRED FOR ROCK TRENCHES AND WET AREAS. CONTRACTOR SHALL HAVE THE RESPONSIBILITY TO PROVIDE SUCH ADDITIONAL BEDDING AS MAY BE REQUIRED TO PROPERLY CONSTRUCT THE WORK.
- COMPACTION OF THE BACKFILL OF ALL TRENCHES SHALL BE COMPACTED TO THE DENSITY OF 95% OF THEORETICAL MAXIMUM DRY DENSITY (ASTM D998). BACKFILL MATERIAL SHALL BE FREE FROM ROOTS, STUMPS, OR OTHER FOREIGN DEBRIS AND SHALL BE PLACED IN LIFTS NOT TO EXCEED 6 INCHES IN COMPACTED FILL THICKNESS. CORRECTION OF ANY TRENCH SETTLEMENT WITHIN A YEAR FROM THE DATE OF APPROVAL WILL BE THE RESPONSIBILITY OF THE CONTRACTOR.
- THE CONTRACTOR SHALL ENSURE THAT POSITIVE AND ADEQUATE DRAINAGE IS MAINTAINED AT ALL TIMES WITHIN THE PROJECT LIMITS. THIS MAY INCLUDE, BUT NOT BE LIMITED TO, REPLACEMENT OR RECONSTRUCTION OF EXISTING DRAINAGE STRUCTURES THAT HAVE BEEN DAMAGED OR REMOVED OR REGRADING AS REQUIRED BY THE ENGINEER, EXCEPT FOR THOSE DRAINAGE ITEMS SHOWN AT SPECIFIC LOCATIONS AND HAVING SPECIFIC PAY ITEMS IN THE DETAILED ESTIMATE. NO SEPARATE PAYMENT WILL BE MADE FOR ANY COSTS INCURRED TO COMPLY WITH THIS REQUIREMENT.
- THE CONTRACTOR SHALL PROVIDE ANY AND ALL EXCAVATION AND MATERIAL SAMPLES NECESSARY TO CONDUCT REQUIRED SOIL TESTS. ALL ARRANGEMENTS AND SCHEDULING FOR THE TESTING SHALL BE THE CONTRACTOR'S RESPONSIBILITY.
- SOILS TESTING AND ON-SITE INSPECTION SHALL BE PERFORMED BY AN INDEPENDENT GEOTECHNICAL ENGINEER. THE SOILS ENGINEER SHALL PROVIDE COPIES OF TEST REPORTS TO THE CONTRACTOR, THE OWNER AND THE CONTRACTOR. SHOULD WORK PERFORMED BY THE CONTRACTOR FAIL TO MEET THESE SPECIFICATIONS.
- CONTRACTOR SHALL FURNISH AND MAINTAIN ALL NECESSARY BARRICADES AROUND THE WORK AREA AND SHALL PROVIDE PROTECTION AGAINST WATER DAMAGE AND SOIL EROSION.
- MAXIMUM SIDEWALK CROSS SLOPE IS 2% AND MINIMUM SIDEWALK CROSS SLOPE IS 1.5% WITHIN THE RIGHT OF WAY.
- ELEVATIONS ARE BASED ON CITY OF PHILADELPHIA VERTICAL DATUM.
- CONTRACTOR SHALL RESET EXISTING MANHOLE RIMS TO FINISHED GRADE. CONTRACTOR SHALL COORDINATE DETAIL WITH RESPECTIVE UTILITY COMPANIES.



NOT FOR CONSTRUCTION

TEST BORING/TEST PIT/AUGER PROBE LOG KEY SHEET

| | |
|--------------------|--|
| <u>COLUMN</u> | <u>DESCRIPTION</u> |
| <u>Depth</u> | Depth in feet below ground surface |
| <u>Description</u> | Description of sample including color, texture, and classification of subsurface material as applicable. Estimated depths to bottom of strata as interpolated from the boring are also shown. |
| <u>Stratum</u> | Strata numbers as assigned by the geotechnical engineer |
| <u>Sample No.</u> | Split barrel sample and sample number (S-x) Undisturbed Tube sample and sample number (U-x) Rock core run and core number (R-x) NR indicates no recovery |
| <u>Blow Counts</u> | For soils sample (ASTM D 1586): indicates number of blows obtained for each 6 inches penetration of the standard split-barrel sampler. For rock coring (ASTM D 2113): indicates percent recovery (REC) per run and rock quality designation (RQD). RQD is the sum of rock pieces that are 4 inches or longer in length in one core run divided by the total core run. |
| <u>Recovery</u> | For soil samples indicates the length of recovery in the sample spoon |
| <u>Remarks</u> | Special conditions or test data as noted during drilling |

Ground Water: Free water level as shown (*); * Free water level as noted may not be indicative of daily, seasonal, or long term fluctuations.

DESCRIPTIVE TERMS

RELATIVE PROPORTIONS

| <u>Descriptive Term</u> | <u>Symbol</u> | <u>Estimated Percentages</u> |
|-------------------------|---------------|------------------------------|
| Trace | tr | 1 to 10 |
| Little | l | 10 to 20 |
| Some | sm | 20 to 35 |
| And | and | 35 to 50 |

GRADATION OF COARSE GRAINED COMPONENTS

| <u>Soil Component</u> | <u>Size Range</u> | <u>Particle Size</u> <u>Maximum</u> | <u>Minimum</u> |
|-----------------------|-------------------|--|----------------|
| Boulders | | - | 12" |
| Cobbles | | 12" | 3" |
| Gravel | Coarse | 3" | ¾" |
| | Fine | ¾" | #4 Sieve |
| Sand | Coarse | #4 Sieve | #10 Sieve |
| | Medium | #10 Sieve | #40 Sieve |
| | Fine | #40 Sieve | #200 Sieve |
| Silt | | #200 Sieve | .005 mm |
| Clay | | .005 mm | - |


COMPOSITION OF COARSE-GRAINED COMPONENTS

| <u>Gradation Designation</u> | <u>Symbol</u> | <u>Defining Proportions</u> |
|------------------------------|---------------|---|
| Coarse to Fine | CF | All fractions greater than 10% of the component |
| Coarse to Medium | CM | Less than 10% Fine |
| Medium to Fine | MF | Less than 10% Coarse |
| Coarse | C | Less than 10% Fine and Medium |
| Medium | M | Less than 10% Coarse and Fine |
| Fine | F | Less than 10% Coarse and Medium |

ENGINEER'S LOG

Boring **WH-01** ECMS
 District: ___ County: Philadelphia
 SR _____ Section _____
 Baseline: FDC Site - Port Authority
 Sta. _____ Offset _____
 Segment _____ Offset _____
 Coordinates:
 Lat. _____ Long. _____
219498.7770 E 2696490.0640 N
 Ground Elev. 14.0 ft.
 Water Level Elev./Elapsed Time:
 ∇ Initial -6.4 ft. Elapsed 0.0 hr.
 ▼ Final -7.8 ft. Elapsed 96.0 hr.
 Driller: Gary B.
 Company: Allied Well Drilling

Drilling Start: 07/27/2017 5:30 pm
 Drilling Complete: 07/28/2017 1:05 pm
 Grouting Complete: 08/02/2017 8:45 am
 Rig: Acker XLS Track Rig
 Hammer Type: Automatic
 SPT Hammer Efficiency:
 Assumed 0.8 Measured _____
 Hammer Calibration Date: _____
 Hole Type: _____
 Casing Type: HSA/FJC - Spun
 Casing I.D.: 3.25 in Casing Depth: 35.0 ft.
 Rock Core Method: _____
 Inspector: Jeremy Boozer
 Inspector Cert. No. 410-17



Final Log Checked and Approved
 By: Carrie Nicholson
 Date: 9/21/2017

Lab Testing Performed on Sample
 NOTE: N values and all graphical plots are for information only.

PENNDOT ENGINEERS LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEO\TECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | ◇ RQD % ◇ | |
|-------|---------|--|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|----------------------------|
| | | | | | | | | | | Soil/Rock Rec. % | Soil/Rock Rec. % |
| | | | | | | | | | | | ▲ SPT (N ₆₀) ▲ |
| 14.0 | | BITUMINOUS CONCRETE, - 5" White crushed gravel between two layers of pavement. | | 1.0 | S-1 | 20-14 | 19 | 1.0 | 100 | | |
| 13.2 | | 0.8'/El. 13.2 | | | | | | | | | |
| 12.0 | | Subbase. | | 2.0 | S-2 | 15-13-19-22 | 43 | 1.6 | 80 | | |
| 10.0 | | SAND and GRAVEL, little Silt, medium dense, moist, heterogeneous, well graded, sub-angular to angular, non-plastic, gray to dark gray, fill. - organics, brick, and mica in S-3. | a-2-4 / sm | 4.0 | S-3 | 15-4-4-11 | 11 | 2.0 | 100 | | |
| 8.0 | | - quartz piece stuck in S-4 shoe. - mica in S-4. | | 6.0 | S-4 | 37-15-10-12 | 33 | 0.5 | 25 | | |
| 6.0 | | 8.0'/El. 6.0 | | | | | | | | | |
| 5.0 | | SILT and CLAY, some Sand, soft to very soft, wet, heterogeneous, poorly graded, rounded to sub-angular, low plastic fines, black, fill, - tar odor. | a-2-4 / ml | 8.0 | S-5 | 2-2-1-4 Pen=0.50 tsf | 4 | 2.0 | 100 | | |
| 3.5 | | 10.5'/El. 3.5 | | | | | | | | | |
| 0.5 | | CLAY and SILT, little Sand, very soft, wet, heterogeneous, poorly graded, rounded, medium plastic fines, black to dark gray, alluvium, Class. on jar samples collected from SB-6B & SB-7T A-7-5(16)/ML N.M.C.=62.4%. | A-7-5 / ML | 12.0 | S-6 | 2-1-1-2 Pen=0.25 tsf | 3 | 2.0 | 100 | | |
| 0.0 | | 13.5'/El. 0.5 | | | S-7 | WOH-WOH-WOH-4 Pen=0.25 tsf | 0 | 2.0 | 100 | | |
| | | | A-4 / ML | 14.0 | | 1-3-2-3 | | | | | |

ENGINEER'S LOG

Boring **WH-01** ECMS

District: _____ County: Philadelphia

Sheet 2 of 5

SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample

PENNDOT ENGINEER'S LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEO\TECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ RQD % | REC (ft.) | REC (%) | Soil/Rock Rec. % | |
|-------|---------|---|---------------|--------------|------------|---------------------------------|-----------------------|-----------|---------|------------------|------|
| | | | | | | | | | | Soil | Rock |
| -5 | | SILT and CLAY , some Sand, very soft, wet, lensed, poorly graded, rounded, non-plastic, brown, alluvium, <i>Class. on jar samples collected from S-9 & S-10</i> A-4(0)/ML <i>N.M.C.=52.9%.</i> <i>(Layer continued from the previous page.)</i> <i>- pocket penetrometer readings are from clay seams; soil is lensed.</i> | A-4 / ML | 16.0 | S-8 | Pen=0.25 tsf | 7 | 1.6 | 80 | | |
| | | | | 18.0 | S-9 | WOH-WOH-WOH-3 Pen=0.25 tsf | 0 | 1.6 | 80 | | |
| | | | | 20.0 | S-10 | WOH-WOH-WOH-WOH Pen=0.25 tsf | 0 | 2.0 | 100 | | |
| -10 | | CLAY and SILT , some Sand, very soft, wet, homogeneous, poorly graded, rounded, medium plastic fines, black to dark gray, alluvium. 24.0'/El. -10.0 | a-6 / cl | 24.0 | S-11 | WOH-2-3-3 Pen=0.25 tsf | 7 | 1.1 | 55 | | |
| -15 | | SAND , little Silt, little Gravel, medium dense, wet, heterogeneous, poorly graded, sub-rounded to sub-angular, non-plastic, brown, alluvium. 29.0'/El. -15.0 | a-3 / sp | 29.0 | S-12 | 6-7-6-6 | 17 | 1.6 | 80 | | |
| -20 | | | | 31.0 | | | | | | | |
| | | | | 34.0 | | | | | | | |

ENGINEER'S LOG

Boring **WH-01** ECMS _____

District: _____ County: Philadelphia

Sheet 3 of 5



SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample

PENNDOT ENGINEERS LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEOTECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | Soil/Rock Rec. % | |
|-------|---|---|------------------|-----------------|--|-------------------------------------|------------------------------------|--------------|------------|------------------|------|
| | | | | | | | | | | Soil | Rock |
| -25 |  | SAND , little Silt, little Gravel, medium dense, wet, heterogeneous, poorly graded, sub-rounded to sub-angular, non-plastic, brown, alluvium. <i>(Layer continued from the previous page.)</i> | | 36.0 | S-13 | 6-7-7-8 | 19 | 1.6 | 80 | | |
| 39.0 | | | | | S-14 | 5-5-8-6 | 17 | 1.4 | 70 | | |
| 41.0 | | | | | <i>- hard to very hard, coarse gravel caused drill rig to abnormally vibrate when boring was advanced with tri-cone roller bit while applying downward pressure between 41.0' and 44.0'.</i> | | | | | | |
| 44.0 | | | | | | | | | | | |
| 46.0 | | | | 46.0 | S-15 | 17-7-8-6 | 20 | 1.0 | 50 | | |
| 49.0 | | 49.0'/El. -35.0 | | 49.0 | S-16 | 20-19-16-16 | 47 | 0.8 | 40 | | |
| 51.0 |  | SAND and GRAVEL , trace Silt, medium dense, wet, heterogeneous, well graded, sub-angular to angular, non-plastic, brown, alluvium, <i>Class. on jar samples collected from S-16 to S-19</i> <i>A-1-b/SP-SM</i> <i>N.M.C.=10.5%.</i> | | 51.0 | | | | | | | |
| 54.0 | | | | | | | | | | | |

ENGINEER'S LOG

Boring **WH-01** ECMS _____

District: _____ County: Philadelphia

Sheet 4 of 5



SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample

PENNDOT ENGINEER'S LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEO\TECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | Soil/Rock Rec. % | |
|-------|---|---|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|------|
| | | | | | | | | | | Soil | Rock |
| -45 |  | SAND and GRAVEL , trace Silt, medium dense, wet, heterogeneous, well graded, sub-angular to angular, non-plastic, brown, alluvium, <i>Class. on jar samples collected from S-16 to S-19</i> A-1-b/SP-SM N.M.C.=10.5%. <i>(Layer continued from the previous page.)</i> | A-1-b / SP-SM | 56.0 | S-17 | 14-12-10-11 | 29 | 1.5 | 75 | 20 | 40 |
| 59.0 | | | | S-18 | 10-9-8-7 | 23 | 1.2 | 60 | 20 | 40 | |
| 61.0 | | | | S-19 | 11-7-6-7 | 17 | 1.5 | 75 | 20 | 40 | |
| -55 |  | 69.0'/El. -55.0 GRAVEL and SAND , little Clay, dense to very dense, wet, heterogeneous, poorly graded, sub-angular to angular, medium plastic fines, tan to light brown, alluvium. | a-1-b / gp | 69.0 | S-20 | 9-11-14-17 | 33 | 2.0 | 100 | 20 | 40 |
| 71.0 | | | | S-21 | 32-33-50/.4' | 111 | 1.4 | 100 | 20 | 40 | |
| 74.0 | | | | | | | | | | | |

ENGINEER'S LOG

Boring **WH-01** ECMS _____

District: _____ County: Philadelphia

Sheet 5 of 5

SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

Lab Testing Performed on Sample


PENNDOT ENGINEERS LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:\6 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEOTECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | ◇ RQD % ◇ | |
|-------|---------|---|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|--|
| | | | | | | | | | | Soil/Rock Rec. % | REC % |
| | | | | | | | | | | | ◎ 20 40 60 80 ◎ ▲ SPT (N ₆₀) ▲ 10 20 30 40 |
| | | 75.4'/El. -61.4 | | | | | | | | | |
| | | Bottom of boring. | | | | | | | | | |
| -65 | | | | | | | | | | | |
| -70 | | | | | | | | | | | |
| -75 | | | | | | | | | | | |
| -80 | | | | | | | | | | | |

ENGINEER'S LOG

Boring **WH-02** ECMS
 District: _____ County: Philadelphia
 SR _____ Section _____
 Baseline: FDC Site - Port Authority
 Sta. _____ Offset _____
 Segment _____ Offset _____
 Coordinates:
 Lat. _____ Long. _____
219294.3170 E 2695829.6000 N
 Ground Elev. 13.9 ft.
 Water Level Elev./Elapsed Time:
 ∇ Initial -0.1 ft. Elapsed 0.0 hr.
 ▼ Final -3.9 ft. Elapsed 24.0 hr.
 Driller: Gary B.
 Company: Allied Well Drilling

Drilling Start: 07/25/2017 12:58 pm
 Drilling Complete: 07/26/2017 11:55 am
 Grouting Complete: 08/01/2017 2:40 pm
 Rig: Acker XLS Track Rig
 Hammer Type: Automatic
 SPT Hammer Efficiency:
 Assumed 0.8 Measured _____
 Hammer Calibration Date: _____
 Hole Type: _____
 Casing Type: HSA/FJC - Spun
 Casing I.D.: 3.25 in Casing Depth: 20.0 ft.
 Rock Core Method: _____
 Inspector: Jeremy Boozer
 Inspector Cert. No. 410-17



Final Log Checked and Approved
 By: Carrie Nicholson
 Date: 9/21/2017

Lab Testing Performed on Sample
 NOTE: N values and all graphical plots are for information only.

PENNDOT ENGINEERS LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL/17001-13 PRPA PORT DEVELOPMENT/GEOTECH/DRILLING LOGS/WAREHOUSE/PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | ◇ RQD % ◇ | |
|-------|-----------|--|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|------------------|
| | | | | | | | | | | Soil/Rock Rec. % | Soil/Rock Rec. % |
| 13.9 | [Pattern] | BITUMINOUS CONCRETE. 0.3'/El. 13.6 | | | | | | | | | |
| 13.6 | [Pattern] | <i>Subbase.</i> 1.0'/El. 12.9 | | 1.0 | S-1 | 9-8 | 11 | 0.8 | 80 | | |
| 12.9 | [Pattern] | Coarse SAND , trace Gravel, loose, moist, homogeneous, poorly graded, sub-rounded, non-plastic, light brown, fill. 3.7'/El. 10.2 | a-3 / sp | 2.0 | S-2 | 6-4-4-6 | 11 | 1.2 | 60 | | |
| 10.2 | [Pattern] | SLAG, ASPHALT MILLINGS. 4.0'/El. 9.9 | | 4.0 | S-3 | 4-1-2-1 Pen=0.50 tsf | 4 | 1.5 | 75 | | |
| 9.9 | [Pattern] | SAND and SILT , very loose to loose, wet, lensed, well graded, sub-rounded, low plastic fines, dark gray to black, alluvium, - clay and silt seams from 4.2' to 4.5' and 7.5' to 8.0'. - pocket penetrometer readings are from clay seams. | a-2-4 / sm | 6.0 | S-4 | 1-1-1-1 Pen=0.25 tsf | 3 | 2.0 | 100 | | |
| 6.0 | [Pattern] | 10.8'/El. 3.1 | | 8.0 | S-5 | WOH-2-5-7 Pen=0.25 tsf | 9 | 0.3 | 15 | | |
| 3.1 | [Pattern] | CLAY and SILT , some Sand, very soft, wet, homogeneous, poorly graded, rounded, medium plastic fines, dark gray to black, alluvium. | a-6 / cl | 10.0 | S-6 | 4-4-5-5 Pen=0.25 tsf | 12 | 1.8 | 90 | | |
| 10.0 | [Pattern] | 14.0'/El. -0.1 | | 12.0 | S-7 | 3-4-6-7 Pen=0.25 tsf | 13 | 2.0 | 100 | | |
| -0.1 | [Pattern] | | a-3 / sp | 14.0 | | | | | | | |

ENGINEER'S LOG

Boring **WH-02** ECMS

District: _____ County: Philadelphia

Sheet 2 of 4




SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample

PENNDOT ENGINEERS LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEOCHDRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | Soil/Rock Rec. % | |
|-------|---|---|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|------|
| | | | | | | | | | | Soil | Rock |
| -5 |  | SAND and GRAVEL , some Silt, loose, wet, heterogeneous, well graded, angular, non-plastic, dark gray, alluvium, <i>- tan, coarse gravel-sized pieces of angular, very hard, quartz frequent in samples S-8 and S-9. (Layer continued from the previous page.)</i> | a-3 / sp | 16.0 | S-8 | WOH-2-4-2 | 8 | 1.5 | 75 | 10 | 20 |
| | | 18.9'/El. -5.0 | | 18.0 | S-9 | 2-1-1-1 | 3 | 1.8 | 90 | 20 | 40 |
| |  | CLAY and SILT , trace Sand, trace Gravel, soft, wet, homogeneous, poorly graded, rounded, high plastic fines, dark gray, alluvium, <i>Class. on jar samples collected from S-10B to S-11 A-7-5(31)/MH N.M.C.=57.7%.</i> | A-7-5 / MH | 20.0 | S-10 | 2-2-3-4 Pen=0.50 tsf | 7 | 1.6 | 80 | 20 | 40 |
| | | 30.2'/El. -16.3 | | 24.0 | S-11 | WOH-WOH-WOH-2 Pen=0.25 tsf | 0 | 2.0 | 100 | 20 | 40 |
| |  | SAND , some Gravel, trace Silt, medium dense to very dense, wet, heterogeneous, poorly graded, sub-rounded, non-plastic, red gray, alluvium. | A-1-b / SW-SM | 26.0 | S-12 | 3-4-4-6 Pen=0.25 tsf | 11 | 1.2 | 60 | 20 | 40 |
| | | | | 29.0 | | | | | | 20 | 40 |
| | | | | 31.0 | | | | | | 20 | 40 |
| | | | | 34.0 | | | | | | 20 | 40 |

ENGINEER'S LOG

Boring **WH-02** ECMS

District: _____ County: Philadelphia

Sheet 3 of 4

SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample

PENNDOT ENGINEERS LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEOTECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | ◇ RQD % ◇ | |
|-------|---------|---|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|----------------------------|
| | | | | | | | | | | Soil/Rock Rec. % | Soil/Rock Rec. % |
| | | | | | | | | | | | ▲ SPT (N ₆₀) ▲ |
| | | SAND , some Gravel, trace Silt, medium dense to very dense, wet, heterogeneous, poorly graded, sub-rounded, non-plastic, red gray, alluvium. <i>(Layer continued from the previous page.)</i> | | 36.0 | S-13 | 7-7-10-11 | 23 | 1.3 | 65 | | |
| -25 | | - tan, coarse gravel-sized pieces of angular, very hard, quartz frequent in samples S-13, S-14, and S-15 Class. on jar samples collected from S-14 to S-16 A-1-b/SW-SM N.M.C.=13.4%. | | 39.0 | S-14 | 7-8-10-13 | 24 | 1.4 | 70 | | |
| -30 | | | A-1-b / SW-SM | 44.0 | S-15 | 6-7-8-18 | 20 | 1.5 | 75 | | |
| -35 | | - brown, gray, white, green, red and purple, coarse gravel, subrounded to rounded, medium hard to very hard with frequent minerals in alluvial deposit in bottom 6" of S-16. | | 49.0 | S-16 | 17-35-49-42 | 112 | 1.9 | 95 | | |
| -40 | | 54.0'/El. -40.1 | | 54.0 | | | | | | | |
| | | | A-1-a / SP | | | | | | | | |

ENGINEER'S LOG

Boring **WH-02** ECMS

District: _____ County: Philadelphia

Sheet 4 of 4

SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample


PENNDOT ENGINEER'S LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEOTECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | ◇ RQD % ◇ | |
|-------|---------|--|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|---|
| | | | | | | | | | | Soil/Rock Rec. % | Soil/Rock Rec. % |
| | | | | | | | | | | | ▲ SPT (N ₆₀) ▲ 10 20 30 40 |
| -45 | | GRAVEL and SAND , trace Silt, medium dense to dense, wet, heterogeneous, poorly graded, angular, non-plastic, brown, alluvium, <i>Class. on jar samples collected from S-17 to S-18</i> A-1-a/SP N.M.C.=17.6%. (Layer continued from the previous page.) <i>- low recovery in S-18 due to coarse gravel in shoe and broken basket.</i> | A-1-a / SP | 56.0 | S-17 | 5-12-12-13 | 32 | 1.5 | 75 | | |
| -50 | | 64.0'/El. -50.1 | | 59.0 | S-18 | 6-6-7-9 | 17 | 1.0 | 50 | | |
| -55 | | GRAVEL and SAND , little Clay, medium dense to dense, wet, heterogeneous, poorly graded, sub-angular to angular, medium plastic fines, tan to light brown, alluvium, <i>- heaving sand and gravel clogged tri-cone bit and AWS rod, required tool cleaning and hole reaming.</i> | a-1-b / gp | 64.0 | S-19 | 4-7-12-16 | 25 | 1.3 | 65 | | |
| -60 | | 71.0'/El. -57.1 | | 66.0 | | | | | | | |
| | | <i>Abandoned hole due to heaving sands. Ran casing advancer down to 74.0' twice; the first time it caved at 48.0' and the second time it caved at 54.0' when trying to sample. Bottom of boring.</i> | | 69.0 | S-20 | 3-5-18-49 | 31 | 2.0 | 100 | | |

ENGINEER'S LOG

Boring **WH-03** ECMS _____
 District: _____ County: Philadelphia
 SR _____ Section _____
 Baseline: FDC Site - Port Authority
 Sta. _____ Offset _____
 Segment _____ Offset _____
 Coordinates:
 Lat. _____ Long. _____
219044.6650 E 2696277.2210 N
 Ground Elev. 13.1 ft.
 Water Level Elev./Elapsed Time:
 ∇ Initial -8.7 ft. Elapsed 0.0 hr.
 ▼ Final 6.0 ft. Elapsed 23.0 hr.
 Driller: Gary B.
 Company: Allied Well Drilling

Drilling Start: 07/31/2017 2:05 pm
 Drilling Complete: 08/01/2017 12:45 pm
 Grouting Complete: 08/02/2017 11:45 am
 Rig: Acker XLS Track Rig
 Hammer Type: Automatic
 SPT Hammer Efficiency:
 Assumed 0.8 Measured _____
 Hammer Calibration Date: _____
 Hole Type: _____
 Casing Type: HSA/FJC - Spun
 Casing I.D.: 3.25 in Casing Depth: 30.0 ft.
 Rock Core Method: _____
 Inspector: Jeremy Boozer
 Inspector Cert. No. 410-17



Final Log Checked and Approved
 By: Carrie Nicholson
 Date: 9/21/2017

Lab Testing Performed on Sample
 NOTE: N values and all graphical plots are for information only.

PENNDOT ENGINEER'S LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P.16 - (M) MUNICIPAL/17001-13 PRPA PORT DEVELOPMENT/TECHDRILLINGLOGSWAREHOUSE/PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | ◇ RQD % ◇ | |
|-------|---------|--|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|------------------|
| | | | | | | | | | | Soil/Rock Rec. % | Soil/Rock Rec. % |
| 13.1 | | BITUMINOUS CONCRETE. 0.4'/Ei. 12.8 | | 1.0 | | | | | | | |
| 12.7 | | <i>Subbase, coarse cobble-sized limestone pieces.</i> 1.0'/Ei. 12.1 | a-2-4 / sm | 2.0 | S-1 | 16-12 | 16 | 1.0 | 100 | | |
| 11.7 | | SAND and GRAVEL , some Silt, medium dense, wet, heterogeneous, well graded, sub-rounded to sub-angular, low plastic fines, brown and red black, fill. 3.0'/Ei. 10.1 | a-6 / cl | 4.0 | S-2 | 8-5-7-10 Pen=3.00 tsf | 16 | 1.0 | 50 | | |
| 8.7 | | CLAY and SILT , some Gravel, very stiff, wet, heterogeneous, poorly graded, sub-rounded to sub-angular, medium plastic fines, light brown to light gray, fill, - trace pyrite in S-2. 4.0'/Ei. 9.1 | | 6.0 | S-3 | 7-4-3-3 | 9 | 0.3 | 15 | | |
| 4.7 | | SAND and SILT , some Gravel, loose, wet, lensed, well graded, rounded to angular, low plastic fines, dark brown to black, fill. - tar odor in S-5 and S-6. 12.5'/Ei. 0.6 | a-2-4 / sm | 8.0 | S-4 | 2-1-2-3 Pen=0.25 tsf | 4 | 2.0 | 100 | | |
| 2.2 | | | | 10.0 | S-5 | 1-1-2-1 Pen=0.25 tsf | 4 | 2.0 | 100 | | |
| 0.2 | | | | 12.0 | S-6 | 1-1-1-1 Pen=0.25 tsf | 3 | 1.7 | 85 | | |
| -1.8 | | | A-2-4 / SM | 14.0 | S-7 | WOH-1-8-8 | 12 | 0.6 | 30 | | |

ENGINEER'S LOG

Boring **WH-03** ECMS _____

District: _____ County: Philadelphia

Sheet 2 of 5







SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample

PENNDOT ENGINEER'S LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEOTECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | Soil/Rock Rec. % | |
|-------|---|---|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|------|
| | | | | | | | | | | Soil | Rock |
| -5 |  | SAND , little Silt, trace Gravel, medium dense, wet, heterogeneous, poorly graded, sub-rounded to sub-angular, non-plastic, brown, fill, <i>Class. on jar samples collected from S-8 to S-9</i> A-2-4(0)/SM N.M.C.=19.8%. <i>(Layer continued from the previous page.)</i> 19.2'/El. -6.1 | A-2-4 / SM | 16.0 | S-8 | 2-3-7-7 | 13 | 1.6 | 80 | 20 | 80 |
| -5 |  | CLAY and SILT , trace Sand, stiff, wet, homogeneous, poorly graded, rounded, medium plastic fines, dark gray, fill. <i>- organics/weeds in sample from 25.2' to 26.0'.</i> 26.0'/El. -12.9 | a-6 / cl | 18.0 | S-9 | 5-4-3-3 | 9 | 2.0 | 100 | 20 | 100 |
| -10 |  | SAND , trace Silt, trace Gravel, medium dense to dense, wet, heterogeneous, poorly graded, sub-rounded to angular, non-plastic, brown, alluvium, <i>Class. on jar samples collected from S-12 to S-13</i> A-3/SP-SM N.M.C.=22.3% | A-3 / SP-SM | 20.0 | S-10 | 2-2-2-3 Pen=1.00 tsf | 5 | 2.0 | 100 | 20 | 100 |
| -15 |  | | | 24.0 | S-11 | WOH-2-2-4 Pen=2.00 tsf | 5 | 2.0 | 100 | 20 | 100 |
| -20 |  | | | 26.0 | S-12 | 3-4-5-5 | 12 | 1.6 | 80 | 20 | 80 |
| -20 |  | | | 29.0 | | | | | | 20 | |
| -20 | | | | 31.0 | | | | | | 20 | |
| -20 | | | | 34.0 | | | | | | 20 | |

ENGINEER'S LOG

Boring **WH-03** ECMS

District: _____ County: Philadelphia

Sheet 3 of 5



SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample

PENNDOT ENGINEER'S LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEO\TECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | Soil/Rock Rec. % | |
|-------|---|---|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|------------------|
| | | | | | | | | | | Soil/Rock Rec. % | Soil/Rock Rec. % |
| -25 |  | SAND , trace Silt, trace Gravel, medium dense to dense, wet, heterogeneous, poorly graded, sub-rounded to angular, non-plastic, brown, alluvium, <i>Class. on jar samples collected from S-12 to S-13 A-3/SP-SM N.M.C.=22.3%. (Layer continued from the previous page.)</i> | A-3 / SP-SM | 36.0 | S-13 | 4-7-5-6 | 16 | 1.9 | 95 | | |
| -30 | | | | 39.0 | S-14 | 6-7-19-24 | 35 | 1.4 | 70 | | |
| -35 |  | GRAVEL and SAND , trace Clay, dense to very dense, wet, heterogeneous, poorly graded, sub-angular to angular, medium plastic fines, brown, alluvium, <i>- gravel stuck in S-15 shoe.</i> | a-1-b / gp | 44.0 | S-15 | 10-14-11-9 | 33 | 0.1 | 5 | | |
| -40 | | | | 49.0 | S-16 | 20-40-46-50/4' | >115 | 1.8 | 95 | | |
| -45 | | | a-3 / sp | 54.0 | | | | | | | |

ENGINEER'S LOG

Boring **WH-03** ECMS

District: _____ County: Philadelphia

Sheet 4 of 5






SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample

PENNDOT ENGINEER'S LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:\6 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEOCHDRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | ◇ RQD % ◇ | | | |
|-------|---|---|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|----------------------------|------------------|----|----|
| | | | | | | | | | | Soil/Rock Rec. % | Soil/Rock Rec. % | | |
| | | | | | | | | | | ▲ SPT (N ₆₀) ▲ | | | |
| | | | | | | | | | | 10 | 20 | 30 | 40 |
| -45.0 |  | SAND and GRAVEL , little Silt, dense, wet, heterogeneous, gap graded, angular, non-plastic, brown, alluvium. <i>(Layer continued from the previous page.)</i> | a-3 / sp | 56.0 | S-17 | 19-20-16-17 | 48 | 2.0 | 100 | ◇ | ◇ | ▲ | ▲ |
| | | 59.0'/El. -45.9 | | 59.0 | | | | | | | | | |
| -50.0 |  | GRAVEL and SAND , trace Silt, dense to very dense, wet, heterogeneous, poorly graded, non-plastic, brown, alluvium. | | 61.0 | S-18 | 10-12-12-11 | 32 | 2.0 | 100 | ◇ | ◇ | ▲ | ▲ |
| -55.0 |  | | a-1-b / gp | 64.0 | S-19 | 13-20-22-33 | 56 | 1.0 | 50 | ◇ | ◇ | ▲ | ▲ |
| -60.0 |  | | | 66.0 | S-20 | 9-26-50/.4' | 101 | 1.4 | 100 | ◇ | ◇ | ▲ | ▲ |
| -65.0 |  | | | 69.0 | | | | | | | | | |
| -70.0 | | | A-7-6 / CL | 70.4 | | | | | | | | | |
| | | 74.0'/El. -60.9 | | 74.0 | | | | | | | | | |
| | | | | | | 9-12-13-16 | | | | | | | |

ENGINEER'S LOG

Boring **WH-03** ECMS _____

District: _____ County: Philadelphia

Sheet 5 of 5




SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample


PENNDOT ENGINEERS LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:\6 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEOTECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | ◇ RQD % ◇ | |
|-------|---|--|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|---|
| | | | | | | | | | | Soil/Rock Rec. % | Soil/Rock Rec. % |
| | | | | | | | | | | |  |
| -65 |  | <p>CLAY and SILT, trace Sand, trace Gravel, stiff, wet, heterogeneous, poorly graded, high plastic fines, red and white, alluvium,</p> <p><i>Class. on jar samples collected from S-21 A-7-6(30)/CL N.M.C.=22.2%. (Layer continued from the previous page.) 76.0'/El. -62.9</i></p> <p>Bottom of boring.</p> | A-7-6 / CL | | S-21 | Pen=1.50 tsf | 33 | 2.0 | 100 | |  |
| -70 | | | | | | | | | | | |
| -75 | | | | | | | | | | | |
| -80 | | | | | | | | | | | |

ENGINEER'S LOG

Boring **WH-04** ECMS
 District: _____ County: Philadelphia
 SR _____ Section _____
 Baseline: FDC Site - Port Authority
 Sta. _____ Offset _____
 Segment _____ Offset _____
 Coordinates:
 Lat. _____ Long. _____
218778.3140 E 2695791.4020 N
 Ground Elev. 12.9 ft.
 Water Level Elev./Elapsed Time:
 ∇ Initial -4.0 ft. Elapsed 0.0 hr.
 ▼ Final -0.1 ft. Elapsed 24.0 hr.
 Driller: Gary B.
 Company: Allied Well Drilling

Drilling Start: 07/26/2017 1:00 pm
 Drilling Complete: 07/27/2017 4:10 pm
 Grouting Complete: 08/01/2017 3:45 pm
 Rig: Acker XLS Track Rig
 Hammer Type: Automatic
 SPT Hammer Efficiency:
 Assumed 0.8 Measured _____
 Hammer Calibration Date: _____
 Hole Type: _____
 Casing Type: HSA/FJC - Spun
 Casing I.D.: 3.25 in Casing Depth: 35.0 ft.
 Rock Core Method: _____
 Inspector: Jeremy Boozer
 Inspector Cert. No. 410-17



Final Log Checked and Approved
 By: Carrie Nicholson
 Date: 9/21/2017

Lab Testing Performed on Sample
 NOTE: N values and all graphical plots are for information only.

PENNDOT ENGINEERS LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEOTECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | ◇ RQD % ◇ | |
|-------|---------|---|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|------------------|
| | | | | | | | | | | Soil/Rock Rec. % | Soil/Rock Rec. % |
| 12.9 | | BITUMINOUS CONCRETE. 0.5'/El. 12.5 | | | | | | | | | |
| | | <i>Subbase.</i> 1.0'/El. 11.9 | | | | | | | | | |
| 10 | | GRAVEL and SAND , some Silt, medium dense, wet, heterogeneous, gap graded, angular, non-plastic, dark gray, fill. | a-1-b / gp | 1.0 | S-1 | 19-12 | 16 | 0.2 | 20 | | |
| | | 4.5'/El. 8.4 | | 2.0 | S-2 | 5-6-5-6 | 15 | 1.0 | 50 | | |
| | | SLAG, ASPHALT MILLINGS, AND TAR, fill. 6.0'/El. 6.9 | | 4.0 | S-3 | 8-5-6-8 | 15 | 1.6 | 80 | | |
| 5 | | GRAVEL and SAND , some Silt, very loose to medium dense, moist, heterogeneous, well graded, sub-angular, non-plastic, dark gray to black, fill, - brick, wood, and asphalt fragments. | a-2-4 / gm | 6.0 | S-4 | 9-10-9-9 | 25 | 1.6 | 80 | | |
| | | - piece of wood stuck in S-6 shoe. | | 8.0 | S-5 | WOH-WOH-2-2 | 3 | 1.0 | 50 | | |
| | | 12.0'/El. 0.9 | | 10.0 | S-6 | 2-WOH-WOH-3 | 0 | 0.3 | 15 | | |
| 0 | | Coarse SAND , little Silt, little Gravel, loose to medium dense, wet, homogeneous, poorly graded, sub-rounded to sub-angular, non-plastic, dark gray, alluvium. | a-3 / sp | 12.0 | S-7 | 4-5-7-5 | 16 | 2.0 | 100 | | |
| | | | | 14.0 | | | | | | | |

ENGINEER'S LOG

Boring **WH-04** ECMS

District: _____ County: Philadelphia

Sheet 2 of 5

SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ RQD % | REC (ft.) | REC (%) | Soil/Rock Rec. % | |
|-------|---------|--|---------------|--------------|------------|---------------------------------|-----------------------|-----------|---------|------------------|------|
| | | | | | | | | | | Soil | Rock |
| -3.6 | | 16.5'/El. -3.6 | a-3 / sp | 16.0 | S-8 | 2-2-2-2 | 5 | 0.8 | 40 | | |
| -5.0 | | CLAY and SILT, trace Sand, very soft to soft, wet, homogeneous, poorly graded, rounded, medium plastic fines, dark gray, alluvium. | a-6 / cl | 18.0 | S-9 | WOH-WOH-WOH-WOH Pen=0.25 tsf | 0 | 1.7 | 85 | | |
| -20.0 | | | | 20.0 | S-10 | 2-1-1-2 Pen=0.50 tsf | 3 | 2.0 | 100 | | |
| -26.0 | | | | 26.0 | S-11 | WOH-2-2-4 Pen=0.25 tsf | 5 | 1.2 | 60 | | |
| -16.1 | | 29.0'/El. -16.1 | a-3 / sp | 29.0 | S-12 | 5-4-6-6 | 13 | 1.0 | 50 | | |
| -31.0 | | 31.0 | | | | | | | | | |
| -34.0 | | | | 34.0 | | | | | | | |

ENGINEER'S LOG

Boring **WH-04** ECMS

District: _____ County: Philadelphia

Sheet 3 of 5

SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

Lab Testing Performed on Sample

PENNDOT ENGINEERS LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL/MT7001-13 PRPA PORT DEVELOPMENT/GEOTECH/DRILLING/LOGS/WAREHOUSE/PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | Soil/Rock Rec. % | | |
|-------|---------|--|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|------|--|
| | | | | | | | | | | Soil | Rock | |
| -25 | | SAND and GRAVEL , trace Silt, medium dense, wet, heterogeneous, gap graded, sub-rounded, non-plastic, red gray, alluvium. <i>(Layer continued from the previous page.)</i> | | 36.0 | S-13 | 6-8-7-9 | 20 | 1.8 | 90 | | | |
| 39.0 | | | | | a-3 / sp | | | | | | | |
| 41.0 | | | | | S-14 | 12-14-7-16 | 28 | 1.6 | 80 | | | |
| -30 | | 44.0'/El. -31.1 | | 44.0 | S-15 | 10-12-11-13 | 31 | 1.8 | 90 | | | |
| 46.0 | | | | | a-2-6 / gc | | | | | | | |
| -35 | | 49.0'/El. -36.1 | | 49.0 | S-16 | 7-19-47-47 | 88 | 2.0 | 100 | | | |
| 51.0 | | | | | A-1-a / SW-SM | | | | | | | |
| 54.0 | | | | | | | | | | | | |

ENGINEER'S LOG

Boring **WH-04** ECMS _____

District: _____ County: Philadelphia

Sheet 4 of 5




SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

Lab Testing Performed on Sample

PENNDOT ENGINEERS LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEOTECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | Soil/Rock Rec. % | |
|-------|---|--|---------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|------|
| | | | | | | | | | | Soil | Rock |
| -45 |  | <p>GRAVEL, some Sand, trace Silt, medium dense to very dense, wet, heterogeneous, poorly graded, angular, non-plastic, brown, alluvium,</p> <p><i>Class. on jar samples collected from S-17 to S-18</i> A-1-a/SW-SM N.M.C.=17.2%. (Layer continued from the previous page.)</p> | A-1-a / SW-SM | 56.0 | S-17 | 6-9-18-16 | 36 | 1.2 | 60 | 60 | 60 |
| 59.0 | | | | 59.0 | S-18 | 14-11-7-8 | 24 | 2.0 | 100 | 100 | 100 |
| 65.0 | | 65.0'/El. -52.1 | | 64.0 | | | | | | | |
| -55 |  | <p>CLAY and SILT, some Sand, very stiff, wet, homogeneous, poorly graded, rounded, medium plastic fines, gray to tan, alluvium.</p> | a-6 / cl | 66.0 | S-19 | 6-7-10-14 Pen=3.50 tsf | 23 | 2.0 | 100 | 100 | 100 |
| 69.0 | | 69.0'/El. -56.1 | | 69.0 | | | | | | | |
| -60 |  | <p>SAND and SILT, some Clay, very dense, wet, homogeneous, gap graded, sub-rounded to sub-angular, low plastic fines, tan to light brown, alluvium.</p> | a-3 / sw | 71.0 | S-20 | 16-26-32-42 | 77 | 2.0 | 100 | 100 | 100 |
| 74.0 | | 75.0'/El. -62.1 | | 74.0 | | | | | | | |

ENGINEER'S LOG

Boring **WH-04** ECMS _____

District: _____ County: Philadelphia

Sheet 5 of 5


SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample

PENNDOT ENGINEERS LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:\16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEOCHDRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | ◇ RQD % ◇ | | | |
|-------|---|--|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|----------------------------|------------------|----|----|
| | | | | | | | | | | Soil/Rock Rec. % | Soil/Rock Rec. % | | |
| | | | | | | | | | | ▲ SPT (N ₆₀) ▲ | | | |
| | | | | | | | | | | 10 | 20 | 30 | 40 |
| -65 |  | <p>CLAY and SILT, little Sand, stiff, wet, homogeneous, poorly graded, rounded, medium plastic fines, white to gray, alluvium. (Layer continued from the previous page.) 76.0'/El. -63.1'</p> <p>Hole collapsed between 10.0' and 11.0' as noticed on 8/1/17 when attempting to grout. Bottom of boring.</p> | a-6 / cl | | S-21 | 18-12-9-16 | 28 | 2.0 | 100 | | | | |
| -70 | | | | | | | | | | | | | |
| -75 | | | | | | | | | | | | | |
| -80 | | | | | | | | | | | | | |

ENGINEER'S LOG

Boring **WH-05** ECMS
 District: _____ County: Philadelphia
 SR _____ Section _____
 Baseline: FDC Site - Port Authority
 Sta. _____ Offset _____
 Segment _____ Offset _____
 Coordinates:
 Lat. _____ Long. _____
218421.0550 E 2696425.4050 N
 Ground Elev. 13.1 ft.
 Water Level Elev./Elapsed Time:
 ▽ Initial 11.6 ft. Elapsed -0.1 hr.
 ▼ Final 7.2 ft. Elapsed 47.9 hr.
 Driller: Gary B.
 Company: Allied Well Drilling

Drilling Start: 07/28/2017 2:40 pm
 Drilling Complete: 07/30/2017 12:46 pm
 Grouting Complete: 08/02/2017 10:30 am
 Rig: Acker XLS Track Rig
 Hammer Type: Automatic
 SPT Hammer Efficiency:
 Assumed 0.8 Measured _____
 Hammer Calibration Date: _____
 Hole Type: _____
 Casing Type: HSA/FJC - Spun
 Casing I.D.: 3.25 in Casing Depth: 30.0 ft.
 Rock Core Method: _____
 Inspector: Carmin Sbarro
 Inspector Cert. No. 272-12



Final Log Checked and Approved
 By: Carrie Nicholson
 Date: 9/21/2017

Lab Testing Performed on Sample
 NOTE: N values and all graphical plots are for information only.

PENNDOT ENGINEER'S LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL/MT7001-13 PRPA PORT DEVELOPMENT/GEOTECH/DRILLING LOGS/WAREHOUSE/PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | ◇ RQD % ◇ | |
|-------|---------|---|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|----------------------------|------------------|
| | | | | | | | | | | Soil/Rock Rec. % | Soil/Rock Rec. % |
| | | | | | | | | | | ▲ SPT (N ₆₀) ▲ | |
| 13.1 | | BITUMINOUS CONCRETE. 0.5'/El. 12.6 | | 1.0 | | | | | | | |
| | | <i>Subbase (pulled from hole with hand).</i> 1.0'/El. 12.1 | | 2.0 | S-1 | 6-6 | 8 | 1.0 | 100 | | |
| 10 | | SAND and CLAY , medium dense, moist, heterogeneous, gap graded, medium plastic fines, dark gray, fill, - brick, mica and asphalt millings in S-2 - burnt shale waste from 4.0'-6.0'. | a-2-4 / sm | 4.0 | S-2 | 5-5-6-10 | 15 | 2.0 | 100 | | |
| 7.2 | | SILT and CLAY , some Sand, trace Gravel, soft, wet, heterogeneous, poorly graded, rounded to sub-angular, low plastic fines, black, fill, - burnt shale waste in S-4. | a-4 / ml | 8.0 | S-3 | 8-11-12-13 | 31 | 2.0 | 100 | | |
| 5 | | SAND and SILT , very loose to medium dense, wet, heterogeneous, poorly graded, sub-angular to sub-rounded, non-plastic, black, fill, - tar odor and black liquid throughout. | a-2-4 / sm | 10.0 | S-4 | 6-6-8-9 | 19 | 2.0 | 100 | | |
| | | | | 12.0 | S-5 | 2-1-2-1 | 4 | 1.0 | 50 | | |
| | | | | 14.0 | S-6 | 2-8-2-1 | 13 | 1.6 | 80 | | |
| | | | | | S-7 | 1-WOH-1-1 | 1 | 0.4 | 20 | | |
| | | | | | | WOH-WOH- | | | | | |

ENGINEER'S LOG

Boring **WH-05** ECMS

District: _____ County: Philadelphia

Sheet 2 of 4

SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample

PENNDOT ENGINEER'S LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEO\TECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | Soil/Rock Rec. % | |
|-------|---------|--|------------------|-----------------|---------------|-------------------------------------|------------------------------------|--------------|------------|------------------|------|
| | | | | | | | | | | Soil | Rock |
| | | 16.0'/El. -2.9 | a-2-4 / sm | 16.0 | S-8 | 1-2 | 1 | 1.2 | 60 | | |
| | | CLAY and SILT , trace Sand, soft, wet, homogeneous, poorly graded, rounded, medium plastic fines, gray, alluvium. | | | S-9 | 1-1-2-2 Pen=0.25 tsf | 4 | 2.0 | 100 | | |
| -5 | | | | 18.0 | S-10 | 2-2-1-1 Pen=0.25 tsf | 4 | 2.0 | 100 | | |
| | | | a-6 / cl | 20.0 | | | | | | | |
| | | 25.0'/El. -11.9 | | 24.0 | S-11 | 3-3-4-4 Pen=0.50 tsf | 9 | 2.0 | 100 | | |
| | | Coarse SAND , little Clay, little Gravel, medium dense, wet, heterogeneous, poorly graded, sub-rounded to sub-angular, medium plastic fines, brown, alluvium. | | 26.0 | | | | | | | |
| -10 | | | | 29.0 | S-12 | 4-4-5-6 | 12 | 2.0 | 100 | | |
| | | | a-3 / sp | 31.0 | | | | | | | |
| -15 | | | | 34.0 | | | | | | | |
| -20 | | | | | | | | | | | |

ENGINEER'S LOG

Boring **WH-05** ECMS _____

District: _____ County: Philadelphia

Sheet 3 of 4




SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample

PENNDOT ENGINEER'S LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL\17001-13 PRPA PORT DEVELOPMENT\GEOTECH\DRILLING\LOGS\WAREHOUSE\PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ RQD % | REC (ft.) | REC (%) | Soil/Rock Rec. % | |
|-------|---|--|---------------|--------------|------------|----------------------------|-----------------------|-----------|---------|------------------|------|
| | | | | | | | | | | Soil | Rock |
| -25 |  | Coarse SAND , little Clay, little Gravel, medium dense, wet, heterogeneous, poorly graded, sub-rounded to sub-angular, medium plastic fines, brown, alluvium. <i>(Layer continued from the previous page.)</i> | | 36.0 | S-13 | 17-12-8-10 | 27 | 1.6 | 80 | | |
| | | | a-3 / sp | 39.0 | | | | | | | |
| | | | | 41.0 | S-14 | 7-6-7-12 | 17 | 1.7 | 85 | | |
| | | 44.0'/El. -30.9 | | 44.0 | | | | | | | |
| |  | GRAVEL and SAND , trace Silt, very dense, wet, heterogeneous, poorly graded, sub-angular to angular, low plastic fines, brown, alluvium. | | 46.0 | S-15 | 25-18-24-30 | 56 | 1.7 | 85 | | |
| | | 49.0'/El. -35.9 | a-1-b / gp | 49.0 | | | | | | | |
| |  | SAND , little Silt, little Gravel, dense to very dense, wet, homogeneous, poorly graded, sub-rounded to sub-angular, non-plastic, light brown to tan, alluvium, <i>Class. on jar samples collected from S-17 to S-21 A-2-4(0)/SM N.M.C.=17.3%.</i> | | 51.0 | S-16 | 15-15-21-31 | 48 | 2.0 | 100 | | |
| | | | A-2-4 / SM | 54.0 | | | | | | | |
| | | | | | | 25-27-19- | | | | | |

ENGINEER'S LOG

Boring **WH-05** ECMS

District: _____ County: Philadelphia

Sheet 4 of 4


SR _____ Section _____

Sta. _____ Offset _____

NOTE: N values and all graphical plots are for information only.

 Lab Testing Performed on Sample


PENNDOT ENGINEER'S LOG - PENNDOT_GINT_VERSION_1.2.2.3_9-21-2016.GDT - 9/21/17 08:55 - P:16 - (M) MUNICIPAL/17001-13 PRPA PORT DEVELOPMENT/GEOTECH/DRILLING/LOGS/WAREHOUSE/PORT AUTH LOGS.GPJ

| ELEV. | GRAPHIC | MATERIAL DESCRIPTION COMMENTS - OBSERVATIONS | AASHTO / USCS | SAMPLE DEPTH | SAMPLE No. | BLOW COUNTS (Blows/ 0.5ft) | N ₆₀ --- RQD % | REC (ft.) | REC (%) | ◇ RQD % ◇ | | | |
|-------|--|---|------------------|-----------------|-----------------|-------------------------------------|------------------------------------|--------------|------------|----------------------------|------------------|----|----|
| | | | | | | | | | | Soil/Rock Rec. % | Soil/Rock Rec. % | | |
| | | | | | | | | | | ▲ SPT (N ₆₀) ▲ | | | |
| | | | | | | | | | | 10 | 20 | 30 | 40 |
| -45 |  | <p>SAND, little Silt, little Gravel, dense to very dense, wet, homogeneous, poorly graded, sub-rounded to sub-angular, non-plastic, light brown to tan, alluvium,</p> <p><i>Class. on jar samples collected from S-17 to S-21</i> A-2-4(0)/SM N.M.C.=17.3%. <i>(Layer continued from the previous page.)</i></p> <p>- clay seam 64.8'-65.2'.</p> <p>- heaving sands @ 72.0'.</p> | A-2-4 / SM | 55.9 | S-17 | 50/.4' | >61 | 1.7 | 89 | | | | |
| 59.0 | | | | S-18 | 36-43-47-50 | 120 | 1.9 | 95 | | | | | |
| 61.0 | | | | | | | | | | | | | |
| 64.0 | | | | | | | | | | | | | |
| 65.9 | | | | S-19 | 9-21-33-50/.4' | >72 | 1.9 | 100 | | | | | |
| 69.0 | | | | | | | | | | | | | |
| 70.8 | | | | S-20 | 39-46-48-50/.3' | >125 | 1.2 | 67 | | | | | |
| 74.0 | | | | | | | | | | | | | |
| 74.9 | | | | S-21 | 34-50/.4' | >67 | 0.8 | 89 | | | | | |

Bottom of boring.

APPENDIX B – Laboratory Data

Particle Size Distribution Report



| | | | | | | | |
|-------|----------|------|--------|--------|------|---------|------|
| % +3" | % Gravel | | % Sand | | | % Fines | |
| | Coarse | Fine | Coarse | Medium | Fine | Silt | Clay |


| MATERIAL DATA | | | | | |
|---------------|--------|------------|-------------|--|------|
| SYMBOL | SOURCE | SAMPLE NO. | DEPTH (ft.) | Material Description | USCS |
| ○ | B-3 | S-6 | 13-15 | SILT AND F/M SAND, TRACE ORGANICS | MH |
| □ | B-4 | S-12-15 | 43-60 | M/F/C SAND, SOME C/F GRAVEL, TRACE SILT | |
| △ | B-5 | U-2 | 22-24 | SILTY CLAY, SOME F/M SAND, LITTLE ORGANICS | OH |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

PENNONI ASSOCIATES INC.
Bethlehem, PA

Client: PHILADELPHIA PORT AUTHORITY
Project: PHILAPORT OFFSITE WAREHOUSE
Project No.: PRPAX17013

Figure S-1


Particle Size Distribution Report



| % +3" | % Gravel | | % Sand | | | % Fines | |
|-------|----------|------|--------|--------|------|---------|------|
| | Coarse | Fine | Coarse | Medium | Fine | Silt | Clay |
| | | | | | | | |

| MATERIAL DATA | | | | | |
|---------------|--------|------------|-------------|---|------|
| SYMBOL | SOURCE | SAMPLE NO. | DEPTH (ft.) | Material Description | USCS |
| ○ | B-7 | S-2-5 | 2-10 | M/F/C SAND, SOME SILT, LITTLE FINE GRAVEL | |
| □ | B-9 | S-9-11 | 28-40 | F/M SAND, LITTLE SILT | |
| △ | B-10 | S-3-5 | 4-10 | F/M/C SAND AND SILT, LITTLE FINE GRAVEL | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

UNCONFINED COMPRESSION TEST



| | | | |
|-------------------------------|--------|--|--|
| Sample No. | 1 | | |
| Unconfined strength, tsf | 0.740 | | |
| Undrained shear strength, tsf | 0.370 | | |
| Failure strain, % | 14.4 | | |
| Strain rate, in./min. | 0.03 | | |
| Water content, % | 55.7 | | |
| Wet density, pcf | 98.8 | | |
| Dry density, pcf | 63.5 | | |
| Saturation, % | 90.8 | | |
| Void ratio | 1.6559 | | |
| Specimen diameter, in. | 1.43 | | |
| Specimen height, in. | 2.75 | | |
| Height/diameter ratio | 1.92 | | |

Description:

LL = 47 PL = 33 PI = 14 Assumed GS= 2.70 Type: SPT

Project No.: PRPAX17013

Date Sampled:

Remarks:

Client: PHILADELPHIA PORT AUTHORITY

Project: PHILAPORT OFFSITE WAREHOUSE

Source of Sample: B-5 **Depth:** 6-8


Sample Number: S-4

UNCONFINED COMPRESSION TEST
PENNONI ASSOCIATES INC.
Bethlehem, PA

Figure UCC-1


Tested By: BL **Checked By:** RE

CONSOLIDATION TEST REPORT



| MATERIAL DESCRIPTION | | | | | | | | | | USCS | | AASHTO | |
|---|----|---------|------------------|-----------------|-------|----------|--------|------------|---------|--------------------|----------------|----------------------|----------------|
| SILTY CLAY, SOME F/M SAND | | | | | | | | | | MH | | A-7-5(32) | |
| LL | PI | Sp. Gr. | Overburden (tsf) | Dry Dens. (pcf) | | Moisture | | Saturation | | Void Ratio | | P _c (tsf) | C _c |
| | | | | Init. | Final | Init. | Final | Init. | Final | Init. | Final | | |
| 83 | 40 | 2.52 | 1.00 | 58.0 | | 70.9 % | 70.9 % | 104.2 % | 100.0 % | 1.714 | 0.959 | 0.79 | 0.48 |
| Preparation Process: | | | | | | | | | | D2435 Method | C _r | Swell Press. (tsf) | Heave % |
| Condition of Test: | | | | | | | | | | | 0.05 | | |
| Project No. PRPAX17013 Client: PHILADELPHIA PORT AUTHORITY Project: PHILAPORT OFFSITE WAREHOUSE | | | | | | | | | | Remarks: | | | |
| Source: B-5 Sample No.: U-2 Elev./Depth: 22-24 | | | | | | | | | | | | | |
| CONSOLIDATION TEST REPORT | | | | | | | | | | Checked By: | | | |
| PENNONI ASSOCIATES INC. | | | | | | | | | | Title: | | | |
| | | | | | | | | | | Figure CONS | | | |

CONSOLIDATION TEST REPORT



| | | | | | | | | | | | |
|-----------------------------|--|--|--|--|--|--|--|--|--|-------------|---------------|
| MATERIAL DESCRIPTION | | | | | | | | | | USCS | AASHTO |
| SILTY CLAY, SOME F/M SAND | | | | | | | | | | MH | A-7-5(32) |

| LL | PI | Sp. Gr. | Overburden (tsf) | Dry Dens. (pcf) | | Moisture | | Saturation | | Void Ratio | | P_c (tsf) | C_c |
|----|----|---------|------------------|-----------------|-------|----------|--------|------------|---------|------------|-------|-------------|-------|
| | | | | Init. | Final | Init. | Final | Init. | Final | Init. | Final | | |
| 83 | 40 | 2.52 | 1.00 | 58.0 | | 70.9 % | 80.0 % | 104.2 % | 100.0 % | 1.714 | 0.959 | 0.81 | 0.48 |

| | | | | |
|-----------------------------|--------------|-------|--------------------|---------|
| Preparation Process: | D2435 Method | C_r | Swell Press. (tsf) | Heave % |
| Condition of Test: | | 0.05 | | |

Project No. PRPAX17013 **Client:** PHILADELPHIA PORT AUTHORITY
Project: PHILAPORT OFFSITE WAREHOUSE

Source: B-5 **Sample No.:** U-2 **Elev./Depth:** 22-24

Remarks:

CONSOLIDATION TEST REPORT

PENNONI ASSOCIATES INC.

Checked By: DAC
Title: 1/16/18
 Figure CONS

Dial Reading vs. Time





Project No.: PRPAX17013

Project: PHILAPORT OFFSITE WAREHOUSE

Source: B-5

Sample No.: U-2

Elev./Depth: 22-24



Dial Reading vs. Time

PENNONI ASSOCIATES INC.

Figure

Dial Reading vs. Time





Project No.: PRPAX17013

Project: PHILAPORT OFFSITE WAREHOUSE

Source: B-5

Sample No.: U-2

Elev./Depth: 22-24



Dial Reading vs. Time

PENNONI ASSOCIATES INC.

Figure

Dial Reading vs. Time





Project No.: PRPAX17013

Project: PHILAPORT OFFSITE WAREHOUSE

Source: B-5

Sample No.: U-2

Elev./Depth: 22-24



Dial Reading vs. Time

PENNONI ASSOCIATES INC.

Figure

Dial Reading vs. Time




Project No.: PRPAX17013

Project: PHILAPORT OFFSITE WAREHOUSE

Source: B-5

Sample No.: U-2

Elev./Depth: 22-24



Dial Reading vs. Time

PENNONI ASSOCIATES INC.

Figure

LABORATORY TESTING PROCEDURES

All testing is either done in accordance with the indicated ASTM Designation-latest edition, or with other standard or generally accepted engineering practice as described:

1. Consolidation Test of Soils
Preparation of samples and testing procedures generally follow the methods described in Lambe, op. Cit. In addition, the time of loading may be selected on the basis of:
 - a. Controlled rate of percent of consolidation
 - b. Controlled pore pressure gradient
 - c. Controlled strain

The method of test is selected to suit the soil type in question and the test is conducted in accordance with generally accepted engineering practice.
2. Atterberg Limits – Plasticity Indices
 - a. Liquid limit of soils, ASTM D 4318
 - b. Plastic limit and plasticity index of soils, ASTM D 4318
 - c. Shrinkage factors of soils, ASTM D 427

(Moisture content is also determined with the Atterberg Limit test, and liquidity index is also computed)
3. Moisture Content of Soil
ASTM D 2216
4. Particle Size Analysis of Soils
ASTM D 421, Dry preparation of soil samples;
ASTM D 422, Sieve and/or hydrometer analysis.
5. Triaxial Compression Test of Soils
Sample preparation, apparatus, and testing generally follow the procedures outlined in Soil Testing for Engineers, T.W. Lambe, John Wiley & Sons, Inc., New York, 1951 and in The Measurement of Soil Properties in the Triaxial Test, Alan W. Bishop & D.J. Henkel, 2nd Edition, St. Martin's Press, New York, 1962
6. Unconfined Compression Strength of Cohesive Soil
ASTM D 2166
7. Specific Gravity of Soils
ASTM D 854
8. Unit Weight Determination of Soils
See ASTM D 2166 for preparation of specimen except that sample size may differ. For moisture content see ASTM D 2216.
9. Visual Identification of Soil Samples
All soil samples are visually identified and/or classified. The classification system used is shown in Table L-1.
10. Identification of Rock
Rock core samples are identified by the character and appearance of newly fractured surfaces of unweathered pieces, by core conditions and characteristics, and by the determination of simple physical and chemical properties.
11. Compaction Test of Soils
 - a. Moisture-density relations of soils using 5.5 lb. hammer and 12 in. drop, ASTM D 698
 - b. Moisture-density relations of soils using 10 lb. hammer and 18 in. drop, ASTM D 1557
12. Maximum and Minimum Densities of Granular Soils
Testing procedures follow D.M. Burmeister, "Suggested Method of Test for Maximum and Minimum Densities of Granular Soils" cited in Proceedings for Testing Soils, Fourth Edition, ASTM, Philadelphia. 1964, pp 175-177.
13. Bearing Ratio of Laboratory Compacted Soils
ASTM D 1883 (Sometimes called California Bearing Ratio or CBR)
14. Organic Content
A modified dichromate oxidation method using ferrous ammonium sulfate is employed in determining the percent of organic matter in soil.



WATER CONTENT DETERMINATION

(ASTM D2216-10) / (AASHTO T265)


| | | | |
|-------------------|-----------------------------------|------------|-----------|
| Client: | CH2M | Project #: | M17001-13 |
| Project: | Port Authority Off-Terminal Ph. 1 | Test Date: | 8/18/2017 |
| Project Location: | Philidelphia, PA | Tested By: | RKL |
| | | Chk'd By: | MDH |

| | | | | | |
|---------------------------|--------------|--------------|--------------|--------------|--------------|
| Lab Sample No.: | 70213 | 70214 | 70215 | 70216 | 70217 |
| Boring No.: | WH-1 | WH-1 | WH-1 | WH-2 | WH-2 |
| Depth (ft): | 10.5-13.5 | 16.0-20.0 | 49.0-66.0 | 18.9-26.0 | 39.0-51.0 |
| Sample No.: | S-6B & S-7T | S-9 & S-10 | S-15 & S-16 | S-10B & S-11 | S-14 to S-16 |
| Water Content (%): | 62.4% | 52.9% | 10.5% | 57.7% | 13.4% |

| | | | | | |
|---------------------------|--------------|--------------|--------------|--------------|--------------|
| Lab Sample No.: | 70218 | 70219 | 70220 | 70221 | 70222 |
| Boring No.: | WH-2 | WH-3 | WH-3 | WH-3 | WH-4 |
| Depth (ft): | 54.0-61.0 | 14.0-18.0 | 29.0-36.0 | 74.0-76.0 | 55.0-61.0 |
| Sample No.: | S-17 & S-18 | S-8 & S-9 | S-12 & S-13 | S-21 | S-17 & S-18 |
| Water Content (%): | 17.6% | 19.8% | 22.3% | 22.2% | 17.2% |

| | |
|---------------------------|--------------|
| Lab Sample No.: | 70223 |
| Boring No.: | WH-5 |
| Depth (ft): | 49.0-74.9 |
| Sample No.: | S-17 to S-21 |
| Water Content (%): | 17.3% |

Particle Size Distribution Report



| | | | | | |
|-------|----------|--------|------|---------|------|
| % +3" | % Gravel | % Sand | | % Fines | |
| 0.0 | 0.0 | Coarse | Fine | Silt | Clay |
| 0.0 | 0.0 | 4.3 | 7.7 | 72.7 | 15.3 |

| TEST RESULTS | | | |
|--------------|---------------|------------------|----------------|
| Opening Size | Percent Finer | Spec.* (Percent) | Pass? (X=Fail) |
| 3 | 100.0 | | |
| 2 | 100.0 | | |
| 1.5 | 100.0 | | |
| 1 | 100.0 | | |
| .75 | 100.0 | | |
| .375 | 100.0 | | |
| #4 | 100.0 | | |
| #10 | 100.0 | | |
| #20 | 97.6 | | |
| #40 | 95.7 | | |
| #60 | 93.1 | | |
| #140 | 89.8 | | |
| #200 | 88.0 | | |
| 0.0437 mm. | 59.7 | | |
| 0.0312 mm. | 57.7 | | |
| 0.0200 mm. | 53.7 | | |
| 0.0146 mm. | 45.8 | | |
| 0.0121 mm. | 41.8 | | |
| 0.0087 mm. | 35.8 | | |
| 0.0062 mm. | 31.8 | | |
| 0.0031 mm. | 21.9 | | |
| 0.0014 mm. | 10.0 | | |

* (no specification provided)

Material Description

CLAY and SILT, little Sand

Atterberg Limits (ASTM D 4318)

PL= 34 LL= 48 PI= 14

Classification

USCS (D 2487)= ML AASHTO (M 145)= A-7-5(16)

Coefficients

D₉₀= 0.1097 D₈₅= 0.0694 D₆₀= 0.0441
D₅₀= 0.0172 D₃₀= 0.0054 D₁₅= 0.0020
D₁₀= 0.0014 C_u= 32.47 C_c= 0.49

Remarks

N.M.C.=62.4%

Date Received: _____ Date Tested: 8/23/17

Tested By: RKL

Checked By: DJW


Title: _____

Source of Sample: WH-1 Depth: 10.5'-13.5'
Sample Number: S-6B to S-7T

Date Sampled:

| | |
|-------------------------------------|--|
| Raudenbush Engineering, Inc. | <p>Client: CH2M</p> <p>Project: Port Authority - Off Terminal Ph 1</p> |
| New Stanton, PA | <p>Project No: M17001-13</p> <p style="text-align: right;">Figure</p> |

Particle Size Distribution Report



| | | | | | |
|-------|----------|--------|------|---------|------|
| % +3" | % Gravel | % Sand | | % Fines | |
| 0.0 | 0.3 | Coarse | Fine | Silt | Clay |
| | | 0.6 | 1.0 | 68.9 | 29.2 |

| TEST RESULTS | | | |
|--------------|---------------|------------------|----------------|
| Opening Size | Percent Finer | Spec.* (Percent) | Pass? (X=Fail) |
| 3 | 100.0 | | |
| 2 | 100.0 | | |
| 1.5 | 100.0 | | |
| 1 | 100.0 | | |
| .75 | 100.0 | | |
| .375 | 100.0 | | |
| #4 | 100.0 | | |
| #10 | 99.7 | | |
| #20 | 99.5 | | |
| #40 | 99.1 | | |
| #60 | 98.7 | | |
| #140 | 98.3 | | |
| #200 | 98.1 | | |
| 0.0375 mm. | 93.9 | | |
| 0.0270 mm. | 89.7 | | |
| 0.0180 mm. | 79.3 | | |
| 0.0132 mm. | 70.9 | | |
| 0.0111 mm. | 62.6 | | |
| 0.0080 mm. | 58.4 | | |
| 0.0058 mm. | 50.1 | | |
| 0.0030 mm. | 35.5 | | |
| 0.0013 mm. | 22.9 | | |

* (no specification provided)

Material Description

CLAY and SILT, trace Sand, trace Gravel

Atterberg Limits (ASTM D 4318)

PL= 34 LL= 59 PI= 25

Classification

USCS (D 2487)= MH AASHTO (M 145)= A-7-5(31)

Coefficients

D₉₀= 0.0274 D₈₅= 0.0224 D₆₀= 0.0100
D₅₀= 0.0058 D₃₀= 0.0021 D₁₅=
D₁₀= C_u= C_c=

Remarks

N.M.C.=57.7%

Date Received: Date Tested: 8/23/17

Tested By: RKL

Checked By: DJW

Title: _____

Source of Sample: WH-2 Depth: 18.9'-26.0'
Sample Number: S-10B to S-11


Date Sampled:

Raudenbush Engineering, Inc.
New Stanton, PA

Client: CH2M
Project: Port Authority - Off Terminal Ph 1
Project No: M17001-13

Figure

Particle Size Distribution Report



| | | | | | |
|-------|----------|--------|------|---------|------|
| % +3" | % Gravel | % Sand | | % Fines | |
| | | Coarse | Fine | Silt | Clay |
| 0.0 | 29.0 | 33.6 | 28.6 | 6.7 | 2.1 |

| TEST RESULTS | | | |
|--------------|---------------|------------------|----------------|
| Opening Size | Percent Finer | Spec.* (Percent) | Pass? (X=Fail) |
| 3 | 100.0 | | |
| 2 | 100.0 | | |
| 1.5 | 100.0 | | |
| 1 | 97.5 | | |
| .75 | 95.9 | | |
| .375 | 86.6 | | |
| #4 | 80.5 | | |
| #10 | 71.0 | | |
| #20 | 62.0 | | |
| #40 | 37.4 | | |
| #60 | 17.6 | | |
| #140 | 10.3 | | |
| #200 | 8.8 | | |
| 0.0517 mm. | 6.3 | | |
| 0.0367 mm. | 5.6 | | |
| 0.0233 mm. | 4.9 | | |
| 0.0165 mm. | 4.2 | | |
| 0.0134 mm. | 4.2 | | |
| 0.0095 mm. | 4.2 | | |
| 0.0068 mm. | 3.5 | | |
| 0.0033 mm. | 2.8 | | |
| 0.0014 mm. | 1.4 | | |

* (no specification provided)

Material Description

SAND, some Gravel, trace Silt

Atterberg Limits (ASTM D 4318)

PL= NP LL= NP PI= NP

Classification

USCS (D 2487)= SW-SM AASHTO (M 145)= A-1-b

Coefficients

| | | |
|---------------------------|--------------------------|--------------------------|
| D ₉₀ = 12.0769 | D ₈₅ = 8.2200 | D ₆₀ = 0.7844 |
| D ₅₀ = 0.5795 | D ₃₀ = 0.3568 | D ₁₅ = 0.2222 |
| D ₁₀ = 0.0951 | C _u = 8.25 | C _c = 1.71 |

Remarks

N.M.C.=13.4%

Date Received: _____ Date Tested: 8/23/17

Tested By: RKL

Checked By: DJW

Title: _____

Source of Sample: WH-2 Depth: 39.0'-51.0'
 Sample Number: S-14 to S-16

Date Sampled:

Raudenbush Engineering, Inc.


Client: CH2M
 Project: Port Authority - Off Terminal Ph 1

New Stanton, PA

Project No: M17001-13

Figure

Particle Size Distribution Report



| | | | | | |
|-------|----------|--------|------|---------|------|
| % +3" | % Gravel | % Sand | | % Fines | |
| 0.0 | 51.3 | Coarse | Fine | Silt | Clay |
| | | 36.3 | 8.4 | 2.5 | 1.5 |

| TEST RESULTS | | | |
|--------------|---------------|------------------|----------------|
| Opening Size | Percent Finer | Spec.* (Percent) | Pass? (X=Fail) |
| 3 | 100.0 | | |
| 2 | 100.0 | | |
| 1.5 | 100.0 | | |
| 1 | 100.0 | | |
| .75 | 94.0 | | |
| .375 | 82.1 | | |
| #4 | 62.9 | | |
| #10 | 48.7 | | |
| #20 | 27.8 | | |
| #40 | 12.4 | | |
| #60 | 7.3 | | |
| #140 | 4.6 | | |
| #200 | 4.0 | | |
| 0.0514 mm. | 3.4 | | |
| 0.0365 mm. | 2.9 | | |
| 0.0232 mm. | 1.9 | | |
| 0.0164 mm. | 1.9 | | |
| 0.0134 mm. | 1.9 | | |
| 0.0095 mm. | 1.9 | | |
| 0.0067 mm. | 1.9 | | |
| 0.0033 mm. | 1.9 | | |
| 0.0014 mm. | 1.0 | | |

* (no specification provided)

Material Description

GRAVEL and SAND, trace Silt

Atterberg Limits (ASTM D 4318)

PL= NP LL= NP PI= NP

Classification

USCS (D 2487)= SP AASHTO (M 145)= A-1-a

Coefficients

D₉₀= 15.3591 D₈₅= 11.0889 D₆₀= 4.1476
D₅₀= 2.1539 D₃₀= 0.9226 D₁₅= 0.4932
D₁₀= 0.3509 C_u= 11.82 C_c= 0.58

Remarks

N.M.C.=17.6%

Date Received: _____ Date Tested: 8/23/17

Tested By: RKL

Checked By: DJW

Title: _____


Source of Sample: WH-2 Depth: 54.0'-61.0'
Sample Number: S-17 & S-18

Date Sampled: _____

| | |
|---|---|
| Raudenbush Engineering, Inc. New Stanton, PA | Client: CH2M Project: Port Authority - Off Terminal Ph 1 Project No: M17001-13 |
|---|---|

Figure

Particle Size Distribution Report



| | | | | | |
|-------|----------|--------|------|---------|------|
| % +3" | % Gravel | % Sand | | % Fines | |
| 0.0 | 2.8 | Coarse | Fine | Silt | Clay |
| | | 36.8 | 55.1 | 3.4 | 1.9 |

| TEST RESULTS | | | |
|--------------|---------------|------------------|----------------|
| Opening Size | Percent Finer | Spec.* (Percent) | Pass? (X=Fail) |
| 3 | 100.0 | | |
| 2 | 100.0 | | |
| 1.5 | 100.0 | | |
| 1 | 100.0 | | |
| .75 | 100.0 | | |
| .375 | 99.6 | | |
| #4 | 98.5 | | |
| #10 | 97.2 | | |
| #20 | 93.9 | | |
| #40 | 60.4 | | |
| #60 | 17.9 | | |
| #140 | 6.1 | | |
| #200 | 5.3 | | |
| 0.0524 mm. | 3.9 | | |
| 0.0371 mm. | 2.9 | | |
| 0.0235 mm. | 1.9 | | |
| 0.0167 mm. | 1.9 | | |
| 0.0136 mm. | 1.9 | | |
| 0.0096 mm. | 1.9 | | |
| 0.0068 mm. | 1.9 | | |
| 0.0033 mm. | 1.9 | | |
| 0.0014 mm. | 1.9 | | |

* (no specification provided)

Material Description

SAND, trace Silt, trace Gravel

Atterberg Limits (ASTM D 4318)

PL= NP LL= NP PI= NP

Classification

USCS (D 2487)= SP-SM AASHTO (M 145)= A-3

Coefficients

D₉₀= 0.7349 D₈₅= 0.6419 D₆₀= 0.4230
D₅₀= 0.3751 D₃₀= 0.2969 D₁₅= 0.2172
D₁₀= 0.1598 C_u= 2.65 C_c= 1.30

Remarks

N.M.C.=22.3%

Date Received: _____ **Date Tested:** 8/23/17

Tested By: RKL

Checked By: DJW

Title: _____


Source of Sample: WH-3 **Depth:** 29.0'-36.0'

Sample Number: S-12 & S-13

Date Sampled: _____

| | | |
|-------------------------------------|---|---------------|
| Raudenbush Engineering, Inc. | Client: CH2M Project: Port Authority - Off Terminal Ph 1 | |
| New Stanton, PA | Project No: M17001-13 | Figure |

Particle Size Distribution Report



| | | | | | |
|-------|----------|--------|------|---------|------|
| % +3" | % Gravel | % Sand | | % Fines | |
| | | Coarse | Fine | Silt | Clay |
| 0.0 | 0.3 | 0.2 | 1.4 | 40.0 | 58.1 |

| TEST RESULTS | | | |
|--------------|---------------|------------------|----------------|
| Opening Size | Percent Finer | Spec.* (Percent) | Pass? (X=Fail) |
| 3 | 100.0 | | |
| 2 | 100.0 | | |
| 1.5 | 100.0 | | |
| 1 | 100.0 | | |
| .75 | 100.0 | | |
| .375 | 100.0 | | |
| #4 | 100.0 | | |
| #10 | 99.7 | | |
| #20 | 99.6 | | |
| #40 | 99.5 | | |
| #60 | 99.5 | | |
| #140 | 98.8 | | |
| #200 | 98.1 | | |
| 0.0366 mm. | 93.9 | | |
| 0.0262 mm. | 91.9 | | |
| 0.0169 mm. | 87.9 | | |
| 0.0121 mm. | 85.9 | | |
| 0.0100 mm. | 83.9 | | |
| 0.0072 mm. | 79.9 | | |
| 0.0052 mm. | 75.9 | | |
| 0.0027 mm. | 63.9 | | |
| 0.0012 mm. | 47.9 | | |

* (no specification provided)


| Material Description |
|--|
| CLAY and SILT, trace Sand, trace Gravel |
| Atterberg Limits (ASTM D 4318) |
| PL= 22 LL= 49 PI= 27 |
| Classification |
| USCS (D 2487)= CL AASHTO (M 145)= A-7-6(30) |
| Coefficients |
| D ₉₀ = 0.0214 D ₈₅ = 0.0110 D ₆₀ = 0.0022 |
| D ₅₀ = 0.0013 D ₃₀ = D ₁₅ = |
| D ₁₀ = C _u = C _c = |
| Remarks |
| N.M.C.=22.2% |
| Date Received: Date Tested: 8/23/17 |
| Tested By: RKL |
| Checked By: DJW |
| Title: _____ |

Source of Sample: WH-3 Depth: 74.0'-76.0'
 Sample Number: S-21

Date Sampled:

| | | |
|-------------------------------------|---|--------|
| Raudenbush Engineering, Inc. | Client: CH2M | |
| New Stanton, PA | Project: Port Authority - Off Terminal Ph 1 | |
| | Project No: M17001-13 | Figure |

Particle Size Distribution Report



| | | | | | |
|-------|----------|--------|------|---------|------|
| % +3" | % Gravel | % Sand | | % Fines | |
| 0.0 | 60.2 | Coarse | Fine | Silt | Clay |
| | | 23.1 | 10.4 | 5.4 | 0.9 |

| TEST RESULTS | | | |
|--------------|---------------|------------------|----------------|
| Opening Size | Percent Finer | Spec.* (Percent) | Pass? (X=Fail) |
| 3 | 100.0 | | |
| 2 | 100.0 | | |
| 1.5 | 100.0 | | |
| 1 | 92.5 | | |
| .75 | 89.4 | | |
| .375 | 84.1 | | |
| #4 | 73.6 | | |
| #10 | 39.8 | | |
| #20 | 26.1 | | |
| #40 | 16.7 | | |
| #60 | 11.7 | | |
| #140 | 7.4 | | |
| #200 | 6.3 | | |
| 0.0515 mm. | 3.9 | | |
| 0.0366 mm. | 3.1 | | |
| 0.0232 mm. | 2.8 | | |
| 0.0165 mm. | 2.4 | | |
| 0.0135 mm. | 2.0 | | |
| 0.0096 mm. | 1.6 | | |
| 0.0068 mm. | 1.6 | | |
| 0.0033 mm. | 1.2 | | |
| 0.0014 mm. | 0.8 | | |

* (no specification provided)

Material Description

GRAVEL, some Sand, trace Silt

Atterberg Limits (ASTM D 4318)

PL= NP LL= NP PI= NP

Classification

USCS (D 2487)= SW-SM AASHTO (M 145)= A-1-a

Coefficients

D₉₀= 20.5476 D₈₅= 10.7811 D₆₀= 3.3126
D₅₀= 2.6270 D₃₀= 1.2162 D₁₅= 0.3665
D₁₀= 0.1935 C_u= 17.12 C_c= 2.31

Remarks

N.M.C.=17.2%

Date Received: _____ Date Tested: 8/23/17

Tested By: RKL

Checked By: DJW


Title: _____

Source of Sample: WH-4 Depth: 55.0'-61.0'
Sample Number: S-17 & S-18

Date Sampled:

| | | |
|-------------------------------------|---|--------|
| Raudenbush Engineering, Inc. | Client: CH2M | |
| New Stanton, PA | Project: Port Authority - Off Terminal Ph 1 | |
| | Project No: M17001-13 | Figure |

Particle Size Distribution Report



| | | | | | |
|-------|----------|--------|------|---------|------|
| % +3" | % Gravel | % Sand | | % Fines | |
| | | Coarse | Fine | Silt | Clay |
| 0.0 | 10.4 | 37.3 | 39.8 | 8.2 | 4.3 |

| TEST RESULTS | | | |
|--------------|---------------|------------------|----------------|
| Opening Size | Percent Finer | Spec.* (Percent) | Pass? (X=Fail) |
| 3 | 100.0 | | |
| 2 | 100.0 | | |
| 1.5 | 100.0 | | |
| 1 | 100.0 | | |
| .75 | 100.0 | | |
| .375 | 100.0 | | |
| #4 | 96.4 | | |
| #10 | 89.6 | | |
| #20 | 82.3 | | |
| #40 | 52.3 | | |
| #60 | 31.1 | | |
| #140 | 14.5 | | |
| #200 | 12.5 | | |
| 0.0508 mm. | 9.8 | | |
| 0.0360 mm. | 8.9 | | |
| 0.0228 mm. | 8.0 | | |
| 0.0162 mm. | 8.0 | | |
| 0.0132 mm. | 8.0 | | |
| 0.0093 mm. | 8.0 | | |
| 0.0066 mm. | 7.1 | | |
| 0.0032 mm. | 5.3 | | |
| 0.0014 mm. | 3.6 | | |

* (no specification provided)

Material Description

SAND, little Silt, little Gravel

Atterberg Limits (ASTM D 4318)

PL= NP LL= NP PI= NP

Classification

USCS (D 2487)= SM AASHTO (M 145)= A-2-4(0)

Coefficients

D₉₀= 2.2169 D₈₅= 0.9535 D₆₀= 0.4986
D₅₀= 0.4043 D₃₀= 0.2413 D₁₅= 0.1119
D₁₀= 0.0530 C_u= 9.41 C_c= 2.21

Remarks

N.M.C.=17.3%

Date Received: _____ Date Tested: 8/23/17

Tested By: RKL

Checked By: DJW

Title: _____

Source of Sample: WH-5 Depth: 49.0'-74.9'
Sample Number: S-17 to S-21

Date Sampled:

| | | |
|-------------------------------------|---|--------|
| Raudenbush Engineering, Inc. | Client: CH2M | |
| New Stanton, PA | Project: Port Authority - Off Terminal Ph 1 | |
| | Project No: M17001-13 | Figure |

APPEDIX C – Standard Symbols

STANDARD SYMBOLS

| | | | |
|-----------------|---|----------------|--|
| B | Width of footing | P | deviator stress |
| c | cohesion | P _c | estimated probable preconsolidation pressure |
| c _v | coefficient of consolidation | P _o | existing overburden pressure |
| C _c | compression index | q _a | allowable soil bearing pressure |
| C | coefficient of secondary compression | Q | triaxial compression test unconsolidated and undrained |
| C ₃ | swelling index | Q _c | triaxial compression test consolidated and undrained |
| C _u | uniformity coefficient (D ₆₀ /D ₁₀) | S | triaxial compression test consolidated and drained |
| CBR | California Bearing Ratio | S _r | degree of saturation |
| D _f | depth of foundation | υ | pore-water pressure |
| D _p | diameter of grain corresponding to percentage p on grain size curve | U | degree of consolidation |
| D ₁₀ | effective grain size | U _c | unconfined compression test |
| E | modulus of linear deformation | w _f | moisture content at end of test |
| E _s | Young's Modulus | w _l | liquid limit |
| e | void ratio | w _n | natural moisture content |
| F _s | factor of safety | w _p | plastic limit |
| G | specific gravity | γ | unit weight |
| h | hydraulic head | γ _d | dry unit weight |
| H | stratum thickness | γ _b | submerged unit weight |
| i | hydraulic gradient | ε | unit linear strain |
| I _L | liquidity index | ε _f | unit linear strain at failure |
| I _p | plasticity index | σ | normal stress |
| k | coefficient of permeability | σ ₁ | major principal stress |
| k _h | coefficient of horizontal subgrade reaction | σ ₃ | minor principal stress |
| k _v | coefficient of vertical subgrade reaction | τ | shear stress |
| l | length of footing | φ | angle of internal friction |
| n | porosity | k _a | coefficient of active pressure |
| | | k _p | coefficient of passive pressure |
| | | δ | friction angle |
| | | tan δ | friction factor |

APPEDIX D – Pavement Thickness

TABLE 1 – Pavement Thickness in Borings Performed During 2017 Study

| Boring No. | Thickness of Bituminous Concrete (in) | Thickness of Processed Aggregate (in) |
|------------|---------------------------------------|---------------------------------------|
| B-1 | 5 | 7 |
| B-2 | 5 | 6 |
| B-3 | 5 | --- |
| B-4 | 6 | --- |
| B-5 | 5 | --- |
| B-6 | 8 | 5 |
| B-7 | 7 | --- |
| B-8 | 5 | --- |
| B-9 | 6 | 4 |
| B-10 | 5 | --- |
| B-11 | 4 | 6* |
| B-12 | 4 | 6* |
| B-13 | 7 | 2 |
| B-14 | --- | 12 |
| B-15 | --- | --- |
| B-16 | --- | --- |
| B-17 | --- | --- |
| B-18 | --- | --- |
| B-19 | --- | 6 |
| B-20 | 6 | 1 |

*: Noted in boring logs as "Concrete"

** : Sand noted below processed aggregate

TABLE 2 – Pavement Thickness in Test pits Performed During 2019 Study

| Test-pit No. | Thickness of Bituminous Asphalt (in) | Thickness of Processed Aggregate (in) |
|--------------|--------------------------------------|---------------------------------------|
| TP-1 | 4 | 8 |
| TP-2 | 4 | 8 |
| TP-3 | 4 | 8 |
| TP-4 | 4 | 8 |
| TP-5 | 4 | 8 |
| TP-6 | 2.5 | 9.5 |
| TP-7 | 0.5 | 0.5 |
| TP-8 | 4 | 8 |
| TP-9 | 4 | 8 |
| TP-10 | 4 | 8 |
| P-1** | 6 | 6 |
| P-2** | 5 | 9 |
| P-3 | 5 | 8 |
| P-4 | 4 | 11 |
| P-5 | 4 | 8 |
| P-6** | 4 | 9 |
| P-7 | 4 | 10 |
| P-8 | 4 | 10 |
| P-9 | 7 | 6 |
| P-10** | 4 | 8.5 |

**APPEDIX E – Important Information
About This Geotechnical Engineering Report by GBA**

Important Information about This

Geotechnical-Engineering Report

Subsurface problems are a principal cause of construction delays, cost overruns, claims, and disputes.

While you cannot eliminate all such risks, you can manage them. The following information is provided to help.

Geotechnical Services Are Performed for Specific Purposes, Persons, and Projects

Geotechnical engineers structure their services to meet the specific needs of their clients. A geotechnical-engineering study conducted for a civil engineer may not fulfill the needs of a constructor — a construction contractor — or even another civil engineer. Because each geotechnical-engineering study is unique, each geotechnical-engineering report is unique, prepared *solely* for the client. No one except you should rely on this geotechnical-engineering report without first conferring with the geotechnical engineer who prepared it. *And no one — not even you — should apply this report for any purpose or project except the one originally contemplated.*

Read the Full Report

Serious problems have occurred because those relying on a geotechnical-engineering report did not read it all. Do not rely on an executive summary. Do not read selected elements only.

Geotechnical Engineers Base Each Report on a Unique Set of Project-Specific Factors

Geotechnical engineers consider many unique, project-specific factors when establishing the scope of a study. Typical factors include: the client's goals, objectives, and risk-management preferences; the general nature of the structure involved, its size, and configuration; the location of the structure on the site; and other planned or existing site improvements, such as access roads, parking lots, and underground utilities. Unless the geotechnical engineer who conducted the study specifically indicates otherwise, do not rely on a geotechnical-engineering report that was:

- not prepared for you;
- not prepared for your project;
- not prepared for the specific site explored; or
- completed before important project changes were made.

Typical changes that can erode the reliability of an existing geotechnical-engineering report include those that affect:

- the function of the proposed structure, as when it's changed from a parking garage to an office building, or from a light-industrial plant to a refrigerated warehouse;
- the elevation, configuration, location, orientation, or weight of the proposed structure;
- the composition of the design team; or
- project ownership.

As a general rule, *always* inform your geotechnical engineer of project changes—even minor ones—and request an

assessment of their impact. *Geotechnical engineers cannot accept responsibility or liability for problems that occur because their reports do not consider developments of which they were not informed.*

Subsurface Conditions Can Change

A geotechnical-engineering report is based on conditions that existed at the time the geotechnical engineer performed the study. *Do not rely on a geotechnical-engineering report whose adequacy may have been affected by:* the passage of time; man-made events, such as construction on or adjacent to the site; or natural events, such as floods, droughts, earthquakes, or groundwater fluctuations. *Contact the geotechnical engineer before applying this report to determine if it is still reliable.* A minor amount of additional testing or analysis could prevent major problems.

Most Geotechnical Findings Are Professional Opinions

Site exploration identifies subsurface conditions only at those points where subsurface tests are conducted or samples are taken. Geotechnical engineers review field and laboratory data and then apply their professional judgment to render an opinion about subsurface conditions throughout the site. Actual subsurface conditions may differ — sometimes significantly — from those indicated in your report. Retaining the geotechnical engineer who developed your report to provide geotechnical-construction observation is the most effective method of managing the risks associated with unanticipated conditions.

A Report's Recommendations Are Not Final

Do not overrely on the confirmation-dependent recommendations included in your report. *Confirmation-dependent recommendations are not final*, because geotechnical engineers develop them principally from judgment and opinion. Geotechnical engineers can finalize their recommendations *only* by observing actual subsurface conditions revealed during construction. *The geotechnical engineer who developed your report cannot assume responsibility or liability for the report's confirmation-dependent recommendations if that engineer does not perform the geotechnical-construction observation required to confirm the recommendations' applicability.*

A Geotechnical-Engineering Report Is Subject to Misinterpretation

Other design-team members' misinterpretation of geotechnical-engineering reports has resulted in costly

problems. Confront that risk by having your geotechnical engineer confer with appropriate members of the design team after submitting the report. Also retain your geotechnical engineer to review pertinent elements of the design team's plans and specifications. Constructors can also misinterpret a geotechnical-engineering report. Confront that risk by having your geotechnical engineer participate in prebid and preconstruction conferences, and by providing geotechnical construction observation.

Do Not Redraw the Engineer's Logs

Geotechnical engineers prepare final boring and testing logs based upon their interpretation of field logs and laboratory data. To prevent errors or omissions, the logs included in a geotechnical-engineering report should *never* be redrawn for inclusion in architectural or other design drawings. Only photographic or electronic reproduction is acceptable, *but recognize that separating logs from the report can elevate risk.*

Give Constructors a Complete Report and Guidance

Some owners and design professionals mistakenly believe they can make constructors liable for unanticipated subsurface conditions by limiting what they provide for bid preparation. To help prevent costly problems, give constructors the complete geotechnical-engineering report, *but* preface it with a clearly written letter of transmittal. In that letter, advise constructors that the report was not prepared for purposes of bid development and that the report's accuracy is limited; encourage them to confer with the geotechnical engineer who prepared the report (a modest fee may be required) and/or to conduct additional study to obtain the specific types of information they need or prefer. A prebid conference can also be valuable. *Be sure constructors have sufficient time* to perform additional study. Only then might you be in a position to give constructors the best information available to you, while requiring them to at least share some of the financial responsibilities stemming from unanticipated conditions.

Read Responsibility Provisions Closely

Some clients, design professionals, and constructors fail to recognize that geotechnical engineering is far less exact than other engineering disciplines. This lack of understanding has created unrealistic expectations that have led to disappointments, claims, and disputes. To help reduce the risk of such outcomes, geotechnical engineers commonly include a variety of explanatory provisions in their reports. Sometimes labeled "limitations," many of these provisions indicate where geotechnical engineers' responsibilities begin and end, to help

others recognize their own responsibilities and risks. *Read these provisions closely.* Ask questions. Your geotechnical engineer should respond fully and frankly.

Environmental Concerns Are Not Covered

The equipment, techniques, and personnel used to perform an *environmental* study differ significantly from those used to perform a *geotechnical* study. For that reason, a geotechnical-engineering report does not usually relate any environmental findings, conclusions, or recommendations; e.g., about the likelihood of encountering underground storage tanks or regulated contaminants. *Unanticipated environmental problems have led to numerous project failures.* If you have not yet obtained your own environmental information, ask your geotechnical consultant for risk-management guidance. *Do not rely on an environmental report prepared for someone else.*

Obtain Professional Assistance To Deal with Mold

Diverse strategies can be applied during building design, construction, operation, and maintenance to prevent significant amounts of mold from growing on indoor surfaces. To be effective, all such strategies should be devised for the *express purpose* of mold prevention, integrated into a comprehensive plan, and executed with diligent oversight by a professional mold-prevention consultant. Because just a small amount of water or moisture can lead to the development of severe mold infestations, many mold-prevention strategies focus on keeping building surfaces dry. While groundwater, water infiltration, and similar issues may have been addressed as part of the geotechnical-engineering study whose findings are conveyed in this report, the geotechnical engineer in charge of this project is not a mold prevention consultant; *none of the services performed in connection with the geotechnical engineer's study were designed or conducted for the purpose of mold prevention. Proper implementation of the recommendations conveyed in this report will not of itself be sufficient to prevent mold from growing in or on the structure involved.*

Rely, on Your GBC-Member Geotechnical Engineer for Additional Assistance

Membership in the Geotechnical Business Council of the Geoprofessional Business Association exposes geotechnical engineers to a wide array of risk-confrontation techniques that can be of genuine benefit for everyone involved with a construction project. Confer with your GBC-Member geotechnical engineer for more information.



8811 Colesville Road/Suite G106, Silver Spring, MD 20910

Telephone: 301/565-2733 Facsimile: 301/589-2017

e-mail: info@geoprofessional.org www.geoprofessional.org

Copyright 2015 by Geoprofessional Business Association (GBA). Duplication, reproduction, or copying of this document, or its contents, in whole or in part, by any means whatsoever, is strictly prohibited, except with GBA's specific written permission. Excerpting, quoting, or otherwise extracting wording from this document is permitted only with the express written permission of GBA, and only for purposes of scholarly research or book review. Only members of GBA may use this document as a complement to or as an element of a geotechnical-engineering report. Any other firm, individual, or other entity that so uses this document without being a GBA member could be committing negligent or intentional (fraudulent) misrepresentation.